

CONFIDENTIAL

COPY
FORM APPROVED
DMS NO. 10-401
Expires July 31, 2010

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. UTU-08107
1b. Type of Well: <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> Single Zone <input checked="" type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name N/A
2. Name of Operator Bill Barrett Corporation		7. If Unit or CA Agreement, Name and No. Peters Point / UTU-63014
3a. Address 1099 18th Street, Suite 2300 Denver, CO 80202		8. Lease Name and Well No. Peter's Point Unit Federal 9-27D-12-16
3b. Phone No. (include area code) 303-312-8134		9. API Well No. pending 43-607-31411
4. Location of Well (Report location clearly and in accordance with any State requirements.)* At surface SESE, 1050' FSL, 790' FEL At proposed prod. zone NESE, 1963' FSL, 608' FEL, Sec. 27		10. Field and Pool, or Exploratory Peter's Point/Wasatch-Mesaverde
14. Distance in miles and direction from nearest town or post office* approximately 50 miles from Myton, Utah		11. Sec., T. R. M. or Blk. and Survey or Area Sec. 27, T12S-R16E
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 790' SH / 608' BH	16. No. of acres in lease 640	12. County or Parish Carbon County
17. Spacing Unit dedicated to this well 40 acres	13. State UT	
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 16' SH / 910' BH	19. Proposed Depth 7900' MD	20. BLM/BIA Bond No. on file Nationwide Bond #WYB000040
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 7196' graded ground	22. Approximate date work will start* 10/01/2008	23. Estimated duration 45 days
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, must be attached to this form:

- | | |
|--|---|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the BLM. |

25. Signature <i>Tracey Fallang</i>	Name (Printed/Typed) Tracey Fallang	Date 4/28/08
Title Environmental/Regulatory Analyst		
Approved by (Signature) <i>Bradley G. Hill</i>	Name (Printed/Typed) BRADLEY G. HILL	Date 05-05-08
Title OFFICE ENVIRONMENTAL MANAGER		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

*(Instructions on page 2)

Surf

Federal Approval of this
Action is Necessary

BHL


RECEIVED
APR 29 2008
DIV. OF OIL, GAS & MINING

576 859X
439 9124Y
39. 740440
-110. 103009

576 911X
4399404Y
39. 742950
-110. 102361

T12S, R16E, S.L.B.&M.

N89°55'W - 5287.92' (G.L.O.)



BILL BARRETT CORPORATION


Well location, PETERS POINT UNIT FEDERAL #9-27D-12-16, located as shown in the SE 1/4 SE 1/4 of Section 27, T12S, R16E, S.L.B.&M., Carbon County, Utah.

BASIS OF ELEVATION

COTTON TRIANGULATION STATION LOCATED IN THE NW 1/4 OF SECTION 31, T12S, R16E, S.L.B.&M., TAKEN FROM THE TWIN HOLLOW QUADRANGLE, UTAH, CARBON COUNTY, 7.5 MINUTE SERIES (TOPOGRAPHICAL MAP) PUBLISHED BY THE UNITED STATES DEPARTMENT OF THE INTERIOR, GEOLOGICAL SURVEY. SAID ELEVATION IS MARKED AS BEING 7386 FEET.

BASIS OF BEARINGS

BASIS OF BEARINGS IS A G.P.S. OBSERVATION.



SCALE

CERTIFICATE

THIS IS TO CERTIFY THAT THE ABOVE IS A TRUE AND CORRECT COPY OF THE FIELD NOTES OF ACTUAL SURVEYS MADE BY ME OR UNDER MY SUPERVISION AND THAT THE SAME ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REGISTERED LAND SURVEYOR
REGISTRATION NO. 161319
STATE OF UTAH

UINTAH ENGINEERING & LAND SURVEYING
85 SOUTH 200 EAST - VERNAL, UTAH 84078
(435) 789-1017

LEGEND:

- └─ = 90° SYMBOL
- = PROPOSED WELL HEAD.
- ▲ = SECTION CORNERS LOCATED.

NAD 83 (TARGET BOTTOM HOLE)	NAD 83 (SURFACE LOCATION)
LATITUDE = 39°44'35.07" (39.743075)	LATITUDE = 39°44'28.05" (39.740569)
LONGITUDE = 110°08'11.23" (110.103119)	LONGITUDE = 110°08'13.58" (110.103772)
NAD 27 (TARGET BOTTOM HOLE)	NAD 27 (SURFACE LOCATION)
LATITUDE = 39°44'35.20" (39.743111)	LATITUDE = 39°44'28.18" (39.740608)
LONGITUDE = 110°08'08.68" (110.102411)	LONGITUDE = 110°08'11.03" (110.103064)
STATE PLANE NAD 27 (UTAH CENTRAL) N: 516547.52 E: 2392971.04	STATE PLANE NAD 27 (UTAH CENTRAL) N: 515631.99 E: 2392801.51

SCALE 1" = 1000'	DATE SURVEYED: 03-11-08	DATE DRAWN: 03-18-08
PARTY D.R. A.W. C.G.	REFERENCES G.L.O. PLAT	
WEATHER COOL	FILE BILL BARRETT CORPORATION	



April 28, 2008

Ms. Diana Mason
State of Utah
Division of Oil, Gas and Mining
1594 West North Temple, Suite 1210
P.O. Box 145801
Salt Lake City, Utah 84114-5801

RE: Directional Drilling R649-3-11
Peters Point Unit Federal 9-27D-12-16
SHL: 1050' FSL & 790' FEL SESE 27-T12S-R16E
BHL: 1963' FSL & 608' FEL NESE 27-T12S-R16E
Carbon County, Utah

Dear Ms. Mason:

Pursuant to the filing of Bill Barrett Corporation's ("BBC") Application for Permit to Drill ("APD") regarding the above referenced well, we are hereby submitting this letter in accordance with Oil & Gas Conservation Rule R649-3-11 pertaining to the "Exception to Location and Siting of Wells."

- The above-mentioned proposed location is within the Peters Point Unit Area;
- BBC is permitting this well as a directional well in order to minimize surface disturbance. By locating the well at the surface location and directionally drilling from this location, BBC will be able to utilize the existing road and pipelines in the area;
- BBC hereby certifies that it is the sole working interest owner within 460 feet of the entire directional well bore.

Based on the information provided, BBC requests that the permit be granted pursuant to R649-3-11. If you should have any questions or need further information, please contact me at 303-312-8129.

Sincerely,

Doug Gundry-White by RLW
Doug Gundry-White
Senior Landman

RECEIVED

APR 29 2008

DIV. OF OIL, GAS & MINING

1099 18TH STREET
SUITE 2300
DENVER, CO 80202
P 303.293.9100
F 303.291.0420

DRILLING PROGRAM

BILL BARRETT CORPORATION

Peter's Point Unit Federal #9-27D-12-16

SESE, 1050' FSL, 790' FEL, Sec. 27, T12S-R16E (surface hole)

NESE, 1963' FSL, 608' FEL, Sec. 27, T12S-R16E (bottom hole)

Carbon County, Utah

1 – 2. Estimated Tops of Geological Markers and Formations Expected to Contain Water, Oil and Gas and Other Minerals

<u>Formation</u>	<u>Depth – MD</u>	<u>Depth – TVD</u>
Green River	Surface	Surface
Wasatch	3360'*	3293'*
North Horn	5392'*	5274'*
Dark Canyon	6814'*	6696'*
Price River	7049'*	6931'*
TD	7900'*	7700'*

PROSPECTIVE PAY

*Members of the Mesaverde formation and Wasatch formation (inclusive of the North Horn) are primary objectives for oil/gas.

3. BOP and Pressure Containment Data

<u>Depth Intervals</u>	<u>BOP Equipment</u>
0 – 1000'	No pressure control required
1000' – TD	11" 3000# Ram Type BOP 11" 3000# Annular BOP
<ul style="list-style-type: none"> - Drilling spool to accommodate choke and kill lines; - Ancillary equipment and choke manifold rated at 3,000#. All BOP and BOPE tests will be in accordance with the requirements of onshore Order No. 2; - The BLM and the State of Utah Division of Oil, Gas and Mining will be notified 24 hours in advance of all BOP pressure tests. - BOP hand wheels may be underneath the sub-structure of the rig if the drilling rig used is set up to operate most efficiently in this manner. 	

4. Casing Program

<u>Hole Size</u>	<u>SETTING DEPTH</u> <u>(FROM) (TO)</u>		<u>Casing Size</u>	<u>Casing Weight</u>	<u>Casing Grade</u>	<u>Thread</u>	<u>Condition</u>
12 ¼"	surface	1,000'	9 5/8"	36#	J or K 55	ST&C	New
7 7/8" & 8 3/4"	surface	7,900'	5 ½"	17#	N-80	LT&C	New
			4 ½"	11.6#	I-100	LT&C	New

Note: BBC will use one of two options of production casing noted above. 7 7/8" hole size will begin at the point the bit is changed.

5. **Cementing Program**

9 5/8" Surface Casing	Approximately 240 sx Halliburton Light Premium with additives mixed at 12.7 ppg (yield = 1.85 ft ³ /sx) and 170 sx Premium cement with additives mixed at 15.8 ppg (yield = 1.16 ft ³ /sx) circulated to surface with 100% excess.
5 1/2" Production Casing OR	Approximately 1550 sx 50/50 Poz Premium cement with additives mixed at 13.4 ppg (yield = 1.49 ft ³ /sx). Top of cement to be determined by log and sample evaluation; estimated TOC 900'.
4 1/2" Production Casing	Approximately 1880 sx 50/50 Poz Premium cement with additives mixed at 13.4 ppg (yield = 1.49 ft ³ /sx). Top of cement to be determined by log and sample evaluation; estimated TOC 900'.
Note: Actual volumes to be calculated from caliper log.	

6. **Mud Program**

<u>Interval</u>	<u>Weight</u>	<u>Viscosity</u>	<u>Fluid Loss</u> (API filtrate)	<u>Remarks</u>
0 – 40'	8.3 – 8.6	27 – 40	--	Native Spud Mud
40' – 1000'	8.3 – 8.6	27 – 40	15 cc or less	Native/Gel/Lime
1000' – TD	8.6 – 9.5	38 – 46	15 cc or less	LSND/DAP
Note: Sufficient mud materials to maintain mud properties, control lost circulation and to contain "kicks" will be available at wellsite. BBC may require minor amounts of diesel to be added to its fluid system in order to reduce tork and drag.				
Note: In the event air drilling should occur at this location:				
<ul style="list-style-type: none"> - Fresh water would be used to suppress the dust coming out. The blooie line, approximately 37' long and 6" diameter, would run from the pit to the wellhead. There is no ignition system as burnable gas should not be encountered. - Capacity of compressor: 1250SCFM with an 1170 SCFM on standby, which would be located very near the wellbore. The compressor has switches to shut off should any problems be encountered. - The rig has mud pumps capable of pumping the kill fluid (fresh water), of which there is 500 bbls on location at all times. 				

7. **Testing, Logging and Core Programs**

Cores	None anticipated;
Testing	None anticipated;
Sampling	30' to 50' samples; surface casing to TD. Preserve samples all show intervals;
Surveys	Run every 1000' and on trips, slope only;
Logging	DIL-GR-SP, FDC-CNL-GR-CAL-Pe-Microlog, Sonic-GR, all TD to surface.

8. **Anticipated Abnormal Pressures or Temperatures**

No abnormal pressures or temperatures or other hazards are anticipated.

Maximum anticipated bottom hole pressure equals approximately 3804 psi* and maximum anticipated surface pressure equals approximately 2110 psi** (bottom hole pressure minus the pressure of a partially evacuated hole calculated at 0.22 psi/foot).

*Max Mud Wt x 0.052 x TD = A (bottom hole pressure)

**Maximum surface pressure = A - (0.22 x TD)

9. **Auxiliary Equipment**

- a) Upper kelly cock; lower Kelly cock will be installed while drilling
- b) Inside BOP or stab-in valve (available on rig floor)
- c) Safety valve(s) and subs to fit all string connections in use
- d) Mud monitoring will be visually observed

10. **Drilling Schedule**

Location Construction: October 1, 2008
Spud: October 8, 2008
Duration: 15 days drilling time
30 days completion time

Well name:	Utah: West Tavaputs
Operator:	Bill Barrett
String type:	Surface
Location:	Carbon County, UT

Design parameters:
Collapse

Mud weight: 9.50 ppg

Design is based on evacuated pipe.

Minimum design factors:
Collapse:

Design factor 1.125

Environment:

H2S considered? No
Surface temperature: 75.00 °F
Bottom hole temperature: 89 °F
Temperature gradient: 1.40 °F/100ft
Minimum section length: 1,000 ft

Burst:

Design factor 1.00

Cement top: Surface

Burst

Max anticipated surface

pressure: 2,735 psi

Internal gradient: 0.22 psi/ft

Calculated BHP 2,955 psi

Annular backup: 9.50 ppg

Tension:

8 Round STC: 1.80 (J)

8 Round LTC: 1.80 (J)

Buttress: 1.80 (J)

Premium: 1.80 (J)

Body yield: 1.80 (B)

Tension is based on buoyed weight.

Neutral point: 859 ft

Non-directional string.

Re subsequent strings:

Next setting depth: 10,000 ft
Next mud weight: 9.500 ppg
Next setting BHP: 4,935 psi
Fracture mud wt: 10.000 ppg
Fracture depth: 10,000 ft
Injection pressure 5,195 psi

Run Seq	Segment Length (ft)	Size (in)	Nominal Weight (lbs/ft)	Grade	End Finish	True Vert Depth (ft)	Measured Depth (ft)	Drift Diameter (in)	Internal Capacity (ft³)
1	1000	9.625	36.00	J/K-55	ST&C	1000	1000	8.796	71.2
Run Seq	Collapse Load (psi)	Collapse Strength (psi)	Collapse Design Factor	Burst Load (psi)	Burst Strength (psi)	Burst Design Factor	Tension Load (Kips)	Tension Strength (Kips)	Tension Design Factor
1	493	2020	4.094	2735	3520	1.29	31	453	14.64 J

Prepared Dominic Spencer
by: Bill Barrett

Phone: (303) 312-8143
FAX: (303) 312-8195

Date: August 1, 2003
Denver, Colorado

Remarks:

Collapse is based on a vertical depth of 1000 ft, a mud weight of 9.5 ppg. The casing is considered to be evacuated for collapse purposes.

Collapse strength is based on the Westcott, Dunlop & Kemler method of biaxial correction for tension.

Burst strength is not adjusted for tension.

Engineering responsibility for use of this design will be that of the purchaser.

Well name: **Uta: West Tavaputs**
 Operator: **Bill Barrett**
 String type: **Production**
 Location: **Uintah County, UT**

Design parameters:

Collapse

Mud weight: 9.50 ppg

Design is based on evacuated pipe.

Minimum design factors:

Collapse:

Design factor 1.125

Environment:

H2S considered? No
 Surface temperature: 75.00 °F
 Bottom hole temperature: 215 °F
 Temperature gradient: 1.40 °F/100ft
 Minimum section length: 1,500 ft

Burst:

Design factor 1.00

Cement top: 900 ft

Burst

Max anticipated surface

pressure: 4,705 psi

Internal gradient: 0.02 psi/ft

Calculated BHP 4,935 psi

Annular backup: 9.50 ppg

Tension:

8 Round STC: 1.80 (J)

8 Round LTC: 1.80 (J)

Buttress: 1.80 (J)

Premium: 1.80 (J)

Body yield: 1.80 (B)

Non-directional string.

Tension is based on buoyed weight.

Neutral point: 8,559 ft

Run Seq	Segment Length (ft)	Size (in)	Nominal Weight (lbs/ft)	Grade	End Finish	True Vert Depth (ft)	Measured Depth (ft)	Drift Diameter (in)	Internal Capacity (ft³)
1	10000	5.5	17.00	N-80	LT&C	10000	10000	4.767	344.6
Run Seq	Collapse Load (psi)	Collapse Strength (psi)	Collapse Design Factor	Burst Load (psi)	Burst Strength (psi)	Burst Design Factor	Tension Load (Kips)	Tension Strength (Kips)	Tension Design Factor
1	4935	6290	1.275	4705	7740	1.65	146	348	2.39 J

Prepared Dominic Spencer
 by: Bill Barrett

Phone: (303) 312-8143
 FAX: (303) 312-8195

Date: August 1, 2003
 Denver, Colorado

Remarks:

Collapse is based on a vertical depth of 10000 ft, a mud weight of 9.5 ppg. The casing is considered to be evacuated for collapse purposes.

Collapse strength is based on the Westcott, Dunlop & Kemler method of biaxial correction for tension.

Burst strength is not adjusted for tension.

Engineering responsibility for use of this design will be that of the purchaser.

Well name:

West Tavaputs GeneralOperator: **Bill Barrett Corporation**String type: **Production****Design parameters:****Collapse**

Mud weight: 9.50 ppg

Design is based on evacuated pipe.

Minimum design factors:**Collapse:**

Design factor 1.125

Burst:

Design factor 1.00

Environment:

H2S considered?

No

Surface temperature:

60.00 °F

Bottom hole temperature:

200 °F

Temperature gradient:

1.40 °F/100ft

Minimum section length:

1,500 ft

Cement top:

2,500 ft

Burst

Max anticipated surface

pressure: 2,735 psi

Internal gradient: 0.22 psi/ft

Calculated BHP 4,935 psi

No backup mud specified.

Tension:

8 Round STC: 1.80 (J)

8 Round LTC: 1.80 (J)

Buttress: 1.80 (J)

Premium: 1.80 (J)

Body yield: 1.80 (B)

Non-directional string.

Tension is based on buoyed weight.

Neutral point: 8,580 ft

Run Seq	Segment Length (ft)	Size (in)	Nominal Weight (lbs/ft)	Grade	End Finish	True Vert Depth (ft)	Measured Depth (ft)	Drift Diameter (in)	Internal Capacity (ft³)
1	10000	4.5	11.60	I-100	LT&C	10000	10000	3.875	231.8
Run Seq	Collapse Load (psi)	Collapse Strength (psi)	Collapse Design Factor	Burst Load (psi)	Burst Strength (psi)	Burst Design Factor	Tension Load (Kips)	Tension Strength (Kips)	Tension Design Factor
1	4935	7220	1.46	4935	9720	1.97	100	245	2.45

Prepared Dominic Spencer
by: Bill BarrettPhone: (303) 312-8143
FAX: (303) 312-8195Date: 7-Apr-08
Denver, Colorado**Remarks:**

Collapse is based on a vertical depth of 10000 ft, a mud weight of 9.5 ppg. The casing is considered to be evacuated for collapse purposes.

Collapse strength is based on the Westcott, Dunlop & Kemler method of biaxial correction for tension.

Burst strength is not adjusted for tension.

Engineering responsibility for use of this design will be that of the purchaser.



Bill Barrett Corporation

NINE MILE CEMENT VOLUMES

Well Name: Peter's Point Unit Federal 9-27D-12-16

Surface Hole Data:

Total Depth:	1,000'
Top of Cement:	0'
OD of Hole:	12.250"
OD of Casing:	9.625"

Calculated Data:

Lead Volume:	219.2	ft ³
Lead Fill:	700'	
Tail Volume:	94.0	ft ³
Tail Fill:	300'	

Cement Data:

Lead Yield:	1.85	ft ³ /sk
Tail Yield:	1.16	ft ³ /sk
% Excess:	100%	

Calculated # of Sacks:

# SK's Lead:	240
# SK's Tail:	170

Production Hole Data:

Total Depth:	7,900'
Top of Cement:	900'
OD of Hole:	8.750"
OD of Casing:	4.500"

Calculated Data:

Lead Volume:	2149.9	ft ³
Lead Fill:	7,000'	

Cement Data:

Lead Yield:	1.49	ft ³ /sk
% Excess:	30%	

Calculated # of Sacks:

# SK's Lead:	1880
--------------	------

Peter's Point Unit Federal 9-27D-12-16 Proposed Cementing Program

<u>Job Recommendation</u>		<u>Surface Casing</u>	
Lead Cement - (700' - 0')			
Halliburton Light Premium	Fluid Weight:	12.7	lbm/gal
2.0% Calcium Chloride	Slurry Yield:	1.85	ft ³ /sk
0.125 lbm/sk Ploy-E-Flake	Total Mixing Fluid:	9.9	Gal/sk
	Top of Fluid:	0'	
	Calculated Fill:	700'	
	Volume:	78.09	bbl
	Proposed Sacks:	240	sks
Tail Cement - (1000' - 700')			
Premium Cement	Fluid Weight:	15.8	lbm/gal
94 lbm/sk Premium Cement	Slurry Yield:	1.16	ft ³ /sk
2.0% Calcium Chloride	Total Mixing Fluid:	4.97	Gal/sk
0.125 lbm/sk Ploy-E-Flake	Top of Fluid:	700'	
	Calculated Fill:	300'	
	Volume:	33.47	bbl
	Proposed Sacks:	170	sks

<u>Job Recommendation</u>		<u>Production Casing</u>	
Lead Cement - (7900' - 900')			
50/50 Poz Premium	Fluid Weight:	13.4	lbm/gal
3.0 % KCL	Slurry Yield:	1.49	ft ³ /sk
0.75% Halad®-322	Total Mixing Fluid:	7.06	Gal/sk
3.0 lbm/sk Silicalite Compacted	Top of Fluid:	900'	
0.2% FWCA	Calculated Fill:	7,000'	
0.125 lbm/sk Poly-E-Flake	Volume:	497.76	bbl
1.0 lbm/sk Granulite TR 1/4	Proposed Sacks:	1880	sks



Bill Barrett Corporation

NINE MILE CEMENT VOLUMES

Well Name: Peter's Point Unit Federal 9-27D-12-16

Surface Hole Data:

Total Depth:	1,000'
Top of Cement:	0'
OD of Hole:	12.250"
OD of Casing:	9.625"

Calculated Data:

Lead Volume:	219.2	ft ³
Lead Fill:	700'	
Tail Volume:	94.0	ft ³
Tail Fill:	300'	

Cement Data:

Lead Yield:	1.85	ft ³ /sk
Tail Yield:	1.16	ft ³ /sk
% Excess:	100%	

Calculated # of Sacks:

# SK's Lead:	240
# SK's Tail:	170

Production Hole Data:

Total Depth:	7,900'
Top of Cement:	900'
OD of Hole:	8.750"
OD of Casing:	5.500"

Calculated Data:

Lead Volume:	1768.2	ft ³
Lead Fill:	7,000'	

Cement Data:

Lead Yield:	1.49	ft ³ /sk
% Excess:	30%	

Calculated # of Sacks:

# SK's Lead:	1550
--------------	------

Peter's Point Unit Federal 9-27D-12-16 Proposed Cementing Program

<u>Job Recommendation</u>	<u>Surface Casing</u>		
Lead Cement - (700' - 0')			
Halliburton Light Premium	Fluid Weight:	12.7	lbm/gal
2.0% Calcium Chloride	Slurry Yield:	1.85	ft ³ /sk
0.125 lbm/sk Ploy-E-Flake	Total Mixing Fluid:	9.9	Gal/sk
	Top of Fluid:	0'	
	Calculated Fill:	700'	
	Volume:	78.09	bbl
	Proposed Sacks:	240	sks
Tail Cement - (1000' - 700')			
Premium Cement	Fluid Weight:	15.8	lbm/gal
94 lbm/sk Premium Cement	Slurry Yield:	1.16	ft ³ /sk
2.0% Calcium Chloride	Total Mixing Fluid:	4.97	Gal/sk
0.125 lbm/sk Ploy-E-Flake	Top of Fluid:	700'	
	Calculated Fill:	300'	
	Volume:	33.47	bbl
	Proposed Sacks:	170	sks

<u>Job Recommendation</u>	<u>Production Casing</u>		
Lead Cement - (7900' - 900')			
50/50 Poz Premium	Fluid Weight:	13.4	lbm/gal
3.0 % KCL	Slurry Yield:	1.49	ft ³ /sk
0.75% Halad®-322	Total Mixing Fluid:	7.06	Gal/sk
3.0 lbm/sk Silicalite Compacted	Top of Fluid:	900'	
0.2% FWCA	Calculated Fill:	7,000'	
0.125 lbm/sk Poly-E-Flake	Volume:	409.37	bbl
1.0 lbm/sk Granulite TR 1/4	Proposed Sacks:	1550	sks



Bill Barrett Corporation

BILL BARRETT CORP

CARBON COUNTY, UT (NAD 27)

SECTION 27 T12S R16E

PETERS POINT UF 9-27-12-16

PT PT 9-27-12-16

Plan: Design #1

Standard Planning Report

27 March, 2008



Database: Compass
Company: BILL BARRETT CORP
Project: CARBON COUNTY, UT (NAD 27)
Site: SECTION 27 T12S R16E
Well: PETERS POINT UF 9-27-12-16
Wellbore: PT PT 9-27-12-16
Design: Design #1

Local Co-ordinate Reference: Well PETERS POINT UF 9-27-12-16
TVD Reference: WELL @ 7211.00ft (Original Well Elev)
MD Reference: WELL @ 7211.00ft (Original Well Elev)
North Reference: True
Survey Calculation Method: Minimum Curvature

Project	CARBON COUNTY, UT (NAD 27)		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	Utah Central 4302		Using geodetic scale factor

Site	SECTION 27 T12S R16E, SECTION 27			
Site Position:		Northing:	515,632.201 ft	Latitude: 39° 44' 26.180 N
From:	Lat/Long	Easting:	2,392,801.761 ft	Longitude: 110° 6' 11.0300 W
Position Uncertainty:	0.00 ft	Slot Radius:	"	Grid Convergence: 0.89 °

Well	PETERS POINT UF 9-27-12-16			
Well Position	+N/-S	0.00 ft	Northing:	515,632.201 ft
	+E/-W	0.00 ft	Easting:	2,392,801.761 ft
Position Uncertainty	0.00 ft	Wellhead Elevation:	ft	Ground Level: 7,196.00 ft

Wellbore	PT PT 9-27-12-16				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	BGGM2007	3/27/2008	11.71	65.62	52,393

Design	Design #1			
Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (ft)	+N/-S (ft)	+E/-W (ft)	Direction (°)
	0.00	0.00	0.00	11.37

Plan Sections										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
1,060.00	0.00	0.00	1,060.00	0.00	0.00	0.00	0.00	0.00	0.00	
1,851.10	15.82	11.37	1,841.09	106.41	21.40	2.00	2.00	0.00	11.37	
4,336.74	15.82	11.37	4,232.55	770.81	155.04	0.00	0.00	0.00	0.00	
5,391.54	0.00	0.00	5,274.00	912.68	183.57	1.50	-1.50	0.00	180.00	
7,673.54	0.00	0.00	7,556.00	912.68	183.57	0.00	0.00	0.00	0.00	PBHL_PT PT 9-27-12



Database: Compass
 Company: BILL BARRETT CORP
 Project: CARBON COUNTY, UT (NAD 27)
 Site: SECTION 27 T12S R16E
 Well: PETERS POINT UF 9-27-12-16
 Wellbore: PT PT 9-27-12-16
 Design: Design #1

Local Co-ordinate Reference: Well PETERS POINT UF 9-27-12-16
 TVD Reference: WELL @ 7211.00ft (Original Well Elev)
 MD Reference: WELL @ 7211.00ft (Original Well Elev)
 North Reference: True
 Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
1,060.00	0.00	0.00	1,060.00	0.00	0.00	0.00	0.00	0.00	0.00
Start Build 2.00									
1,100.00	0.80	11.37	1,100.00	0.27	0.06	0.28	2.00	2.00	0.00
1,200.00	2.80	11.37	1,199.94	3.35	0.67	3.42	2.00	2.00	0.00
1,300.00	4.80	11.37	1,299.72	9.85	1.98	10.05	2.00	2.00	0.00
1,400.00	6.80	11.37	1,399.20	19.76	3.97	20.15	2.00	2.00	0.00
1,500.00	8.80	11.37	1,498.27	33.06	6.65	33.72	2.00	2.00	0.00
1,600.00	10.80	11.37	1,596.81	49.75	10.01	50.74	2.00	2.00	0.00
1,700.00	12.80	11.37	1,694.69	69.79	14.04	71.19	2.00	2.00	0.00
1,800.00	14.80	11.37	1,791.80	93.18	18.74	95.04	2.00	2.00	0.00
1,851.10	15.82	11.37	1,841.09	106.41	21.40	108.54	2.00	2.00	0.00
Start 2485.64 hold at 1851.10 MD									
1,900.00	15.82	11.37	1,888.13	119.48	24.03	121.87	0.00	0.00	0.00
2,000.00	15.82	11.37	1,984.34	146.21	29.41	149.13	0.00	0.00	0.00
2,100.00	15.82	11.37	2,080.55	172.94	34.78	176.40	0.00	0.00	0.00
2,200.00	15.82	11.37	2,176.77	199.67	40.16	203.66	0.00	0.00	0.00
2,300.00	15.82	11.37	2,272.98	226.40	45.54	230.93	0.00	0.00	0.00
2,400.00	15.82	11.37	2,369.19	253.12	50.91	258.19	0.00	0.00	0.00
2,500.00	15.82	11.37	2,465.40	279.85	56.29	285.46	0.00	0.00	0.00
2,600.00	15.82	11.37	2,561.61	306.58	61.66	312.72	0.00	0.00	0.00
2,700.00	15.82	11.37	2,657.82	333.31	67.04	339.99	0.00	0.00	0.00
2,800.00	15.82	11.37	2,754.03	360.04	72.42	367.25	0.00	0.00	0.00
2,900.00	15.82	11.37	2,850.24	386.77	77.79	394.52	0.00	0.00	0.00
3,000.00	15.82	11.37	2,946.46	413.50	83.17	421.78	0.00	0.00	0.00
3,100.00	15.82	11.37	3,042.67	440.23	88.55	449.05	0.00	0.00	0.00
3,200.00	15.82	11.37	3,138.88	466.96	93.92	476.31	0.00	0.00	0.00
3,300.00	15.82	11.37	3,235.09	493.69	99.30	503.58	0.00	0.00	0.00
3,360.19	15.82	11.37	3,293.00	509.78	102.53	519.99	0.00	0.00	0.00
WASATCH									
3,400.00	15.82	11.37	3,331.30	520.42	104.67	530.84	0.00	0.00	0.00
3,500.00	15.82	11.37	3,427.51	547.15	110.05	558.11	0.00	0.00	0.00
3,600.00	15.82	11.37	3,523.72	573.88	115.43	585.37	0.00	0.00	0.00
3,700.00	15.82	11.37	3,619.94	600.61	120.80	612.64	0.00	0.00	0.00
3,800.00	15.82	11.37	3,716.15	627.34	126.18	639.90	0.00	0.00	0.00
3,900.00	15.82	11.37	3,812.36	654.07	131.56	667.17	0.00	0.00	0.00
4,000.00	15.82	11.37	3,908.57	680.80	136.93	694.43	0.00	0.00	0.00
4,100.00	15.82	11.37	4,004.78	707.53	142.31	721.70	0.00	0.00	0.00
4,200.00	15.82	11.37	4,100.99	734.26	147.69	748.96	0.00	0.00	0.00
4,300.00	15.82	11.37	4,197.20	760.99	153.06	776.23	0.00	0.00	0.00
4,336.74	15.82	11.37	4,232.55	770.81	155.04	786.25	0.00	0.00	0.00
Start Drop -1.50									
4,400.00	14.87	11.37	4,293.55	787.22	158.34	802.99	1.50	-1.50	0.00
4,500.00	13.37	11.37	4,390.53	811.14	163.15	827.39	1.50	-1.50	0.00
4,600.00	11.87	11.37	4,488.11	832.57	167.46	849.24	1.50	-1.50	0.00
4,700.00	10.37	11.37	4,586.23	851.48	171.26	868.53	1.50	-1.50	0.00
4,800.00	8.87	11.37	4,684.82	867.87	174.56	885.25	1.50	-1.50	0.00
4,900.00	7.37	11.37	4,783.81	881.72	177.34	899.38	1.50	-1.50	0.00
5,000.00	5.87	11.37	4,883.14	893.03	179.62	910.91	1.50	-1.50	0.00
5,100.00	4.37	11.37	4,982.74	901.78	181.38	919.84	1.50	-1.50	0.00
5,200.00	2.87	11.37	5,082.54	907.98	182.63	926.16	1.50	-1.50	0.00
5,300.00	1.37	11.37	5,182.47	911.61	183.36	929.87	1.50	-1.50	0.00
5,391.54	0.00	0.00	5,274.00	912.68	183.57	930.96	1.50	-1.50	0.00
Start 2282.00 hold at 5391.54 MD - NORTH HORN									
5,400.00	0.00	0.00	5,282.46	912.68	183.57	930.96	0.00	0.00	0.00

Database: Compass
 Company: BILL BARRETT CORP
 Project: CARBON COUNTY, UT (NAD 27)
 Site: SECTION 27 T12S R16E
 Well: PETERS POINT UF 9-27-12-16
 Wellbore: PT PT 9-27-12-16
 Design: Design #1

Local Co-ordinate Reference:
 TVD Reference:
 MD Reference:
 North Reference:
 Survey Calculation Method:

Well PETERS POINT UF 9-27-12-16
 WELL @ 7211.00ft (Original Well Elev)
 WELL @ 7211.00ft (Original Well Elev)
 True
 Minimum Curvature

Planned Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
5,500.00	0.00	0.00	5,382.46	912.68	183.57	930.96	0.00	0.00	0.00
5,600.00	0.00	0.00	5,482.46	912.68	183.57	930.96	0.00	0.00	0.00
5,700.00	0.00	0.00	5,582.46	912.68	183.57	930.96	0.00	0.00	0.00
5,800.00	0.00	0.00	5,682.46	912.68	183.57	930.96	0.00	0.00	0.00
5,900.00	0.00	0.00	5,782.46	912.68	183.57	930.96	0.00	0.00	0.00
6,000.00	0.00	0.00	5,882.46	912.68	183.57	930.96	0.00	0.00	0.00
6,100.00	0.00	0.00	5,982.46	912.68	183.57	930.96	0.00	0.00	0.00
6,200.00	0.00	0.00	6,082.46	912.68	183.57	930.96	0.00	0.00	0.00
6,300.00	0.00	0.00	6,182.46	912.68	183.57	930.96	0.00	0.00	0.00
6,400.00	0.00	0.00	6,282.46	912.68	183.57	930.96	0.00	0.00	0.00
6,500.00	0.00	0.00	6,382.46	912.68	183.57	930.96	0.00	0.00	0.00
6,600.00	0.00	0.00	6,482.46	912.68	183.57	930.96	0.00	0.00	0.00
6,700.00	0.00	0.00	6,582.46	912.68	183.57	930.96	0.00	0.00	0.00
6,800.00	0.00	0.00	6,682.46	912.68	183.57	930.96	0.00	0.00	0.00
6,813.54	0.00	0.00	6,696.00	912.68	183.57	930.96	0.00	0.00	0.00
DARK CANYON									
6,900.00	0.00	0.00	6,782.46	912.68	183.57	930.96	0.00	0.00	0.00
7,000.00	0.00	0.00	6,882.46	912.68	183.57	930.96	0.00	0.00	0.00
7,048.54	0.00	0.00	6,931.00	912.68	183.57	930.96	0.00	0.00	0.00
PRICE RIVER									
7,100.00	0.00	0.00	6,982.46	912.68	183.57	930.96	0.00	0.00	0.00
7,200.00	0.00	0.00	7,082.46	912.68	183.57	930.96	0.00	0.00	0.00
7,300.00	0.00	0.00	7,182.46	912.68	183.57	930.96	0.00	0.00	0.00
7,400.00	0.00	0.00	7,282.46	912.68	183.57	930.96	0.00	0.00	0.00
7,451.54	0.00	0.00	7,334.00	912.68	183.57	930.96	0.00	0.00	0.00
PRICE RIVER 6840_SAND									
7,473.54	0.00	0.00	7,356.00	912.68	183.57	930.96	0.00	0.00	0.00
PRICE RIVER_6840 BASE									
7,500.00	0.00	0.00	7,382.46	912.68	183.57	930.96	0.00	0.00	0.00
7,600.00	0.00	0.00	7,482.46	912.68	183.57	930.96	0.00	0.00	0.00
7,673.54	0.00	0.00	7,556.00	912.68	183.57	930.96	0.00	0.00	0.00

Casing Points

Measured Depth (ft)	Vertical Depth (ft)	Name	Casing Diameter (")	Hole Diameter (")
1,000.00	1,000.00	9 5/8"	9-5/8	12-1/4

Formations

Measured Depth (ft)	Vertical Depth (ft)	Name	Lithology	Dip (°)	Dip Direction (°)
3,360.19	3,293.00	WASATCH		0.00	
5,391.54	5,274.00	NORTH HORN		0.00	
6,813.54	6,696.00	DARK CANYON		0.00	
7,048.54	6,931.00	PRICE RIVER		0.00	
7,451.54	7,334.00	PRICE RIVER 6840_SAND		0.00	
7,473.54	7,356.00	PRICE RIVER_6840 BASE		0.00	



Database: Compass
Company: BILL BARRETT CORP
Project: CARBON COUNTY, UT (NAD 27)
Site: SECTION 27 T12S R16E
Well: PETERS POINT UF 9-27-12-16
Wellbore: PT PT 9-27-12-16
Design: Design #1

Local Co-ordinate Reference: Well PETERS POINT UF 9-27-12-16
TVD Reference: WELL @ 7211.00ft (Original Well Elev)
MD Reference: WELL @ 7211.00ft (Original Well Elev)
North Reference: True
Survey Calculation Method: Minimum Curvature


Plan Annotations

Measured Depth (ft)	Vertical Depth (ft)	Local Coordinates		Comment
		+N/-S (ft)	+E/-W (ft)	
1,060.00	1,060.00	0.00	0.00	Start Build 2.00
1,851.10	1,841.09	106.41	21.40	Start 2485.64 hold at 1851.10 MD
4,336.74	4,232.55	770.81	155.04	Start Drop -1.50
5,391.54	5,274.00	912.68	183.57	Start 2282.00 hold at 5391.54 MD
7,673.54	7,556.00	912.68	183.57	TD at 7673.54



Bill Barrett Corporation

PETERS POINT UF 9-27-12-16
1050' FSL, 790' FEL
SECTION 27 T12S R16E
CARBON COUNTY, UT
Latitude: 39° 44' 26.180 N
Longitude: 110° 6' 11.0300 W



Azimuths to True North
Magnetic North: 11.71°

Magnetic Field
Strength: 52383.5nT
Dip Angle: 65.62°
Date: 3/27/2008
Model: BGGM2007

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	DLeg	TFace	VSec	Target
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2	1060.00	0.00	0.00	1060.00	0.00	0.00	0.00	0.00	0.00	
3	1851.10	15.82	11.37	1841.09	106.41	21.40	2.00	11.37	108.54	
4	4336.74	15.82	11.37	4232.55	770.81	155.04	0.00	0.00	786.25	
5	5391.54	0.00	0.00	5274.00	912.68	183.57	1.50	180.00	930.96	
6	7673.54	0.00	0.00	7556.00	912.68	183.57	0.00	0.00	930.96	PBHL_PT PT 9-27-12-16



FORMATION TOP DETAILS

TVDPath	MDPath	Formation
3293.00	3360.19	WASATCH
5274.00	5391.54	NORTH HORN
6696.00	6813.54	DARK CANYON
6931.00	7048.54	PRICE RIVER
7334.00	7451.54	PRICE RIVER 6840 SAND
7356.00	7473.54	PRICE RIVER 6840 BASE

WELLBORE TARGET DETAILS (LAT/LONG)

Name	TVD	+N/-S	+E/-W	Latitude	Longitude	Shape
PBHL	7556.00	912.68	183.57	39° 44' 35.200 N	110° 6' 8.6800 W	Circle (Radius: 100.00)

KB ELEV: WELL @ 7211.00ft (Original Well Elev)
GRD ELEV: 7196.00



Plan Design #1 (PETERS POINT UF 9-27-12-16/PT PT 9-27-12-16)
Created By: ROBERT H. SCOTT Date: 10:02, March 27 2008



Bill Barrett Corporation

BILL BARRETT CORP

CARBON COUNTY, UT (NAD 27)

SECTION 27 T12S R16E

PETERS POINT UF 9-27-12-16

PT PT 9-27-12-16

Design #1

Anticollision Report

27 March, 2008



Company: BILL BARRETT CORP
 Project: CARBON COUNTY, UT (NAD 27)
 Reference Site: SECTION 27 T12S R16E
 Site Error: 0.00ft
 Reference Well: PETERS POINT UF 9-27-12-16
 Well Error: 0.00ft
 Reference Wellbore: PT PT 9-27-12-16
 Reference Design: Design #1

Local Co-ordinate Reference: Well PETERS POINT UF 9-27-12-16
 TVD Reference: WELL @ 7211.00ft (Original Well Elev)
 MD Reference: WELL @ 7211.00ft (Original Well Elev)
 North Reference: True
 Survey Calculation Method: Minimum Curvature
 Output errors are at: 2.00 sigma
 Database: Compass
 Offset TVD Reference: Offset Datum

Reference	Design #1		
Filter type:	NO GLOBAL FILTER: Using user defined selection & filtering criteria		
Interpolation Method:	MD + Stations Interval 100.00ft	Error Model:	ISCWSA
Depth Range:	0.00 to 20,000.00ft	Scan Method:	Closest Approach 3D
Results Limited by:	Maximum center-center distance of 10,000.00ft	Error Surface:	Elliptical Conic
Warning Levels Evaluated at:	2.00 Sigma		

Survey Tool Program	Date	3/27/2008		
From (ft)	To (ft)	Survey (Wellbore)	Tool Name	Description
0.00	7,673.54	Design #1 (PT PT 9-27-12-16)	MWD	MWD - Standard

Site Name	Reference Measured Depth (ft)	Offset Measured Depth (ft)	Distance Between Centres (ft)	Distance Between Ellipses (ft)	Separation Factor	Warning
Offset Well - Wellbore - Design						
SECTION 27 T12S R16E						
PETERS POINT UF 10-27D-12-16 - PT PT 10-27D-12-16	1,060.00	1,060.00	32.29	27.78	7.165	CC
PETERS POINT UF 10-27D-12-16 - PT PT 10-27D-12-16	1,100.00	1,099.46	32.43	27.75	6.926	ES
PETERS POINT UF 10-27D-12-16 - PT PT 10-27D-12-16	1,200.00	1,198.00	34.19	29.07	6.681	SF
PETERS POINT UF 11-27-12-16 - PT PT 11-27-12-16 - D	233.44	233.44	48.09	47.30	60.801	CC, ES
PETERS POINT UF 11-27-12-16 - PT PT 11-27-12-16 - D	700.00	691.38	78.93	76.03	27.287	SF
PETERS POINT UF 15-27-12-16 - PT PT 15-27-12-16 - D	1,153.34	1,153.07	15.86	10.96	3.238	CC, ES
PETERS POINT UF 15-27-12-16 - PT PT 15-27-12-16 - D	1,200.00	1,199.41	16.30	11.20	3.201	SF

Offset Design SECTION 27 T12S R16E - PETERS POINT UF 10-27D-12-16 - PT PT 10-27D-12-16 - Design #1													Offset Site Error: 0.00 ft
Survey Program: O-MWD													Offset Well Error: 0.00 ft
Reference Measured Depth (ft)	Vertical Depth (ft)	Offset Measured Depth (ft)	Vertical Depth (ft)	Semi Major Axis Reference (ft)	Semi Major Axis Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	Offset Wellbore Centre +E/-W (ft)	Distance Between Centres (ft)	Distance Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor	Warning
0.00	0.00	0.00	0.00	0.00	0.00	-35.49	26.29	-18.75	32.29				
100.00	100.00	100.00	100.00	0.10	0.10	-35.49	26.29	-18.75	32.29	32.10	0.19	169.014	
200.00	200.00	200.00	200.00	0.32	0.32	-35.49	26.29	-18.75	32.29	31.65	0.64	50.408	
300.00	300.00	300.00	300.00	0.55	0.55	-35.49	26.29	-18.75	32.29	31.20	1.09	29.621	
400.00	400.00	400.00	400.00	0.77	0.77	-35.49	26.29	-18.75	32.29	30.75	1.54	20.973	
500.00	500.00	500.00	500.00	0.99	0.99	-35.49	26.29	-18.75	32.29	30.30	1.99	16.233	
600.00	600.00	600.00	600.00	1.22	1.22	-35.49	26.29	-18.75	32.29	29.85	2.44	13.241	
700.00	700.00	700.00	700.00	1.44	1.44	-35.49	26.29	-18.75	32.29	29.40	2.89	11.180	
800.00	800.00	800.00	800.00	1.67	1.67	-35.49	26.29	-18.75	32.29	28.95	3.34	9.674	
900.00	900.00	900.00	900.00	1.89	1.89	-35.49	26.29	-18.75	32.29	28.50	3.79	8.526	
1,000.00	1,000.00	1,000.00	1,000.00	2.12	2.12	-35.49	26.29	-18.75	32.29	28.05	4.24	7.621	
1,060.00	1,060.00	1,060.00	1,060.00	2.25	2.25	-35.49	26.29	-18.75	32.29	27.78	4.51	7.165	CC
1,100.00	1,100.00	1,099.46	1,099.46	2.34	2.34	-47.39	26.50	-19.02	32.43	27.75	4.68	6.926	ES
1,200.00	1,199.94	1,198.00	1,197.92	2.57	2.55	-52.98	28.83	-22.03	34.19	29.07	5.12	6.681	SF
1,300.00	1,299.72	1,296.14	1,295.73	2.80	2.78	-62.81	33.73	-28.36	38.82	33.26	5.55	6.988	
1,400.00	1,399.20	1,393.61	1,392.43	3.03	3.01	-73.52	41.12	-37.92	47.51	41.51	6.00	7.916	
1,500.00	1,498.27	1,490.12	1,487.60	3.28	3.28	-82.57	50.92	-50.58	60.89	54.42	6.47	9.412	
1,600.00	1,596.81	1,585.45	1,580.85	3.55	3.58	-89.27	62.99	-66.18	78.96	71.99	6.97	11.328	
1,700.00	1,694.69	1,679.35	1,671.84	3.87	3.93	-93.98	77.19	-84.54	101.46	93.94	7.52	13.499	
1,800.00	1,791.80	1,771.63	1,760.25	4.22	4.34	-97.23	93.35	-105.43	128.12	120.00	8.12	15.782	
1,851.10	1,841.09	1,818.10	1,804.35	4.43	4.56	-98.48	102.32	-117.02	143.27	134.82	8.45	16.959	

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Company: BILL BARRETT CORP
Project: CARBON COUNTY, UT (NAD 27)
Reference Site: SECTION 27 T12S R16E
Site Error: 0.00ft
Reference Well: PETERS POINT UF 9-27-12-16
Well Error: 0.00ft
Reference Wellbore: PT PT 9-27-12-16
Reference Design: Design #1

Local Co-ordinate Reference: Well PETERS POINT UF 9-27-12-16
TVD Reference: WELL @ 7211.00ft (Original Well Elev)
MD Reference: WELL @ 7211.00ft (Original Well Elev)
North Reference: True
Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma
Database: Compass
Offset TVD Reference: Offset Datum

Offset Design SECTION 27 T12S R16E - PETERS POINT UF 10-27D-12-16 - PT PT 10-27D-12-16 - Design #1														Offset Site Error:	0.00 ft
Survey Program: O-MWD														Offset Well Error:	0.00 ft
Reference		Offset		Semi Major Axis		Distance									
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor	Warning		
1,900.00	1,888.13	1,862.15	1,845.87	4.63	4.80	-99.64	111.32	-128.65	158.63	149.85	8.78	18.064			
2,000.00	1,984.34	1,955.99	1,933.88	5.06	5.34	-101.24	131.25	-154.41	191.21	181.70	9.50	20.118			
2,100.00	2,080.55	2,050.41	2,022.42	5.52	5.91	-102.38	151.32	-180.35	223.90	213.64	10.26	21.822			
2,200.00	2,176.77	2,144.84	2,110.97	5.99	6.50	-103.23	171.39	-206.30	256.65	245.60	11.05	23.231			
2,300.00	2,272.98	2,239.26	2,199.51	6.47	7.11	-103.89	191.46	-232.24	289.44	277.58	11.86	24.404			
2,400.00	2,369.19	2,333.69	2,288.06	6.96	7.73	-104.41	211.53	-258.18	322.26	309.57	12.69	25.387			
2,500.00	2,465.40	2,428.11	2,376.60	7.46	8.36	-104.84	231.60	-284.12	355.10	341.55	13.54	26.218			
2,600.00	2,561.61	2,522.54	2,465.15	7.97	9.00	-105.19	251.67	-310.07	387.95	373.54	14.41	26.926			
2,700.00	2,657.82	2,616.96	2,553.69	8.48	9.64	-105.49	271.74	-336.01	420.81	405.53	15.28	27.534			
2,800.00	2,754.03	2,711.39	2,642.24	8.99	10.29	-105.75	291.81	-361.95	453.69	437.52	16.17	28.060			
2,900.00	2,850.24	2,805.81	2,730.78	9.51	10.95	-105.97	311.88	-387.89	486.56	469.50	17.06	28.518			
3,000.00	2,946.46	2,900.24	2,819.32	10.03	11.60	-106.16	331.95	-413.84	519.45	501.49	17.96	28.920			
3,100.00	3,042.67	2,994.66	2,907.87	10.55	12.26	-106.33	352.02	-439.78	552.34	533.47	18.87	29.274			
3,200.00	3,138.88	3,089.08	2,996.41	11.08	12.92	-106.48	372.09	-465.72	585.23	565.45	19.78	29.588			
3,300.00	3,235.09	3,183.51	3,084.96	11.61	13.59	-106.62	392.16	-491.66	618.13	597.43	20.69	29.869			
3,400.00	3,331.30	3,277.93	3,173.50	12.14	14.25	-106.74	412.24	-517.61	651.03	629.41	21.61	30.121			
3,500.00	3,427.51	3,372.36	3,262.05	12.67	14.92	-106.85	432.31	-543.55	683.93	661.39	22.54	30.347			
3,600.00	3,523.72	3,466.78	3,350.59	13.20	15.59	-106.95	452.38	-569.49	716.83	693.37	23.46	30.552			
3,700.00	3,619.94	3,561.21	3,439.14	13.73	16.26	-107.04	472.45	-595.43	749.74	725.35	24.39	30.738			
3,800.00	3,716.15	3,656.63	3,527.68	14.26	16.93	-107.12	492.52	-621.38	782.65	757.33	25.32	30.908			
3,900.00	3,812.36	3,750.06	3,616.23	14.80	17.60	-107.20	512.59	-647.32	815.56	789.30	26.25	31.063			
4,000.00	3,908.57	3,844.48	3,704.77	15.34	18.27	-107.27	532.66	-673.26	848.47	821.28	27.19	31.206			
4,100.00	4,004.78	3,938.91	3,793.32	15.87	18.95	-107.34	552.73	-699.20	881.38	853.25	28.13	31.337			
4,200.00	4,100.99	4,033.33	3,881.86	16.41	19.62	-107.40	572.80	-725.15	914.29	885.22	29.06	31.458			
4,300.00	4,197.20	4,127.76	3,970.41	16.95	20.30	-107.45	592.87	-751.09	947.20	917.20	30.00	31.570			
4,336.74	4,232.55	4,162.45	4,002.94	17.14	20.54	-107.47	600.25	-760.62	959.29	928.94	30.35	31.609			
4,400.00	4,293.55	4,222.23	4,059.00	17.44	20.97	-107.79	612.95	-777.05	979.96	949.00	30.96	31.649			
4,500.00	4,390.53	4,316.93	4,147.80	17.84	21.65	-108.15	633.08	-803.06	1,012.02	980.17	31.85	31.772			
4,600.00	4,488.11	4,411.81	4,236.77	18.21	22.33	-108.37	653.25	-829.13	1,043.32	1,010.61	32.71	31.899			
4,700.00	4,586.23	4,506.79	4,325.84	18.55	23.01	-108.44	673.44	-855.23	1,073.86	1,040.34	33.52	32.033			
4,800.00	4,684.82	4,601.82	4,414.95	18.86	23.69	-108.40	693.64	-881.33	1,103.67	1,069.38	34.30	32.179			
4,900.00	4,783.81	4,696.83	4,504.04	19.15	24.37	-108.23	713.83	-907.44	1,132.79	1,097.76	35.03	32.340			
5,000.00	4,883.14	4,791.75	4,593.05	19.40	25.05	-107.97	734.01	-933.52	1,161.25	1,125.54	35.71	32.519			
5,100.00	4,982.74	4,886.52	4,681.92	19.61	25.73	-107.61	754.15	-959.55	1,189.12	1,152.78	36.34	32.719			
5,200.00	5,082.54	4,981.08	4,770.59	19.80	26.41	-107.15	774.25	-985.53	1,216.47	1,179.54	36.92	32.945			
5,300.00	5,182.47	5,075.36	4,859.09	19.95	27.09	-106.62	794.29	-1,011.44	1,243.35	1,205.90	37.45	33.200			
5,391.54	5,274.00	5,161.36	4,939.65	20.07	27.71	-94.70	812.57	-1,035.06	1,267.63	1,232.39	38.24	33.970			
5,400.00	5,282.46	5,169.29	4,947.08	20.07	27.76	-94.61	814.26	-1,037.24	1,269.86	1,234.60	35.27	36.008			
5,500.00	5,382.46	5,320.83	5,090.44	20.20	28.61	-93.11	844.25	-1,076.01	1,294.80	1,259.27	35.53	36.438			
5,600.00	5,482.46	5,493.81	5,257.61	20.32	29.37	-91.83	871.37	-1,111.07	1,314.67	1,278.88	35.79	36.733			
5,700.00	5,582.46	5,672.86	5,433.64	20.44	29.94	-90.93	891.24	-1,136.75	1,328.86	1,292.79	36.06	36.847			
5,800.00	5,682.46	5,656.03	5,615.79	20.57	30.33	-90.42	902.80	-1,151.70	1,336.97	1,300.59	36.38	36.752			
5,900.00	5,782.46	5,622.79	5,782.46	20.70	30.52	-90.30	905.62	-1,155.34	1,338.93	1,305.63	33.30	40.212			
6,000.00	5,882.46	6,122.79	5,882.46	20.83	30.61	-90.30	905.62	-1,155.34	1,338.93	1,305.32	33.61	39.837			
6,100.00	5,982.46	6,222.79	5,982.46	20.96	30.70	-90.30	905.62	-1,155.34	1,338.93	1,305.00	33.93	39.459			
6,200.00	6,082.46	6,322.79	6,082.46	21.09	30.80	-90.30	905.62	-1,155.34	1,338.93	1,304.67	34.26	39.084			
6,300.00	6,182.46	6,422.79	6,182.46	21.22	30.89	-90.30	905.62	-1,155.34	1,338.93	1,304.34	34.59	38.714			
6,400.00	6,282.46	6,522.79	6,282.46	21.36	30.99	-90.30	905.62	-1,155.34	1,338.93	1,304.01	34.82	38.347			
6,500.00	6,382.46	6,622.79	6,382.46	21.50	31.09	-90.30	905.62	-1,155.34	1,338.93	1,303.68	35.25	37.985			
6,600.00	6,482.46	6,722.79	6,482.46	21.63	31.19	-90.30	905.62	-1,155.34	1,338.93	1,303.34	35.58	37.627			
6,700.00	6,582.46	6,822.79	6,582.46	21.77	31.29	-90.30	905.62	-1,155.34	1,338.93	1,303.01	35.92	37.273			
6,800.00	6,682.46	6,922.79	6,682.46	21.92	31.39	-90.30	905.62	-1,155.34	1,338.93	1,302.67	36.26	36.923			

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation



Company: BILL BARRETT CORP
 Project: CARBON COUNTY, UT (NAD 27)
 Reference Site: SECTION 27 T12S R16E
 Site Error: 0.00ft
 Reference Well: PETERS POINT UF 9-27-12-16
 Well Error: 0.00ft
 Reference Wellbore: PT PT 9-27-12-16
 Reference Design: Design #1

Local Co-ordinate Reference: Well PETERS POINT UF 9-27-12-16
 TVD Reference: WELL @ 7211.00ft (Original Well Elev)
 MD Reference: WELL @ 7211.00ft (Original Well Elev)
 North Reference: True
 Survey Calculation Method: Minimum Curvature
 Output errors are at 2.00 sigma
 Database: Compass
 Offset TVD Reference: Offset Datum

Offset Design SECTION 27 T12S R16E - PETERS POINT UF 10-27D-12-16 - PT PT 10-27D-12-16 - Design #1												Offset Site Error:	0.00 ft
Survey Program: 0-MWD												Offset Well Error:	0.00 ft
Reference		Offset		Semi Major Axis			Distance						Warning
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor	
6,900.00	6,782.46	7,022.79	6,782.46	22.06	31.49	-90.30	905.62	-1,155.34	1,338.93	1,302.32	36.61	36.577	
7,000.00	6,882.46	7,122.79	6,882.46	22.20	31.60	-90.30	905.62	-1,155.34	1,338.93	1,301.98	36.95	36.236	
7,100.00	6,982.46	7,222.79	6,982.46	22.35	31.70	-90.30	905.62	-1,155.34	1,338.93	1,301.63	37.30	35.898	
7,200.00	7,082.46	7,322.79	7,082.46	22.49	31.81	-90.30	905.62	-1,155.34	1,338.93	1,301.28	37.65	35.565	
7,300.00	7,182.46	7,422.79	7,182.46	22.64	31.92	-90.30	905.62	-1,155.34	1,338.93	1,300.93	38.00	35.236	
7,400.00	7,282.46	7,522.79	7,282.46	22.79	32.03	-90.30	905.62	-1,155.34	1,338.93	1,300.58	38.35	34.912	
7,500.00	7,382.46	7,622.79	7,382.46	22.94	32.14	-90.30	905.62	-1,155.34	1,338.93	1,300.22	38.71	34.591	
7,600.00	7,482.46	7,722.79	7,482.46	23.09	32.25	-90.30	905.62	-1,155.34	1,338.93	1,299.87	39.06	34.275	
7,673.54	7,556.00	7,796.34	7,556.00	23.21	32.33	-90.30	905.62	-1,155.34	1,338.93	1,299.60	39.33	34.045	

Company: BILL BARRETT CORP
Project: CARBON COUNTY, UT (NAD 27)
Reference Site: SECTION 27 T12S R16E
Site Error: 0.00ft
Reference Well: PETERS POINT UF 9-27-12-16
Well Error: 0.00ft
Reference Wellbore: PT PT 9-27-12-16
Reference Design: Design #1

Local Co-ordinate Reference: Well PETERS POINT UF 9-27-12-16
TVD Reference: WELL @ 7211.00ft (Original Well Elev)
MD Reference: WELL @ 7211.00ft (Original Well Elev)
North Reference: True
Survey Calculation Method: Minimum Curvature
Output errors are at 2.00 sigma
Database: Compass
Offset TVD Reference: Offset Datum

Offset Design SECTION 27 T12S R16E - PETERS POINT UF 11-27-12-16 - PT PT 11-27-12-16 - Design #1													Offset Site Error: 0.00 ft
Survey Program: 0-MWD													Offset Well Error: 0.00 ft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Distance		Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor	Warning
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)		Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)					
0.00	0.00	0.00	0.00	0.00	0.00	-36.95	38.43	-28.90	48.09				
100.00	100.00	100.00	100.00	0.10	0.10	-36.95	38.43	-28.90	48.09	47.90	0.19	251.702	
200.00	200.00	200.00	200.00	0.32	0.32	-36.95	38.43	-28.90	48.09	47.45	0.64	75.069	
233.44	233.44	233.44	233.44	0.40	0.40	-36.95	38.43	-28.90	48.09	47.30	0.79	60.801	CC, ES
300.00	300.00	299.31	299.31	0.55	0.54	-37.23	38.57	-29.31	48.44	47.36	1.08	44.657	
400.00	400.00	397.81	397.75	0.77	0.76	-39.33	39.67	-32.51	51.34	49.81	1.53	33.644	
500.00	500.00	495.97	495.66	0.99	0.99	-42.89	41.86	-38.88	57.30	55.32	1.98	28.967	
600.00	600.00	593.55	592.72	1.22	1.24	-46.99	45.11	-48.36	66.54	64.10	2.43	27.335	
700.00	700.00	691.38	689.68	1.44	1.53	-50.89	49.36	-60.72	78.93	76.03	2.89	27.287	SF
800.00	800.00	790.40	787.74	1.67	1.85	-53.88	53.83	-73.75	92.13	88.79	3.34	27.604	
900.00	900.00	889.43	885.80	1.89	2.17	-56.11	58.31	-86.79	105.52	101.73	3.78	27.889	
1,000.00	1,000.00	988.46	983.87	2.12	2.50	-57.83	62.78	-99.82	119.02	114.79	4.23	28.130	
1,060.00	1,060.00	1,045.65	1,040.45	2.25	2.70	-58.70	65.48	-107.69	127.55	123.05	4.50	28.350	
1,100.00	1,100.00	1,083.02	1,077.31	2.34	2.83	-70.63	67.49	-113.52	133.91	129.17	4.74	28.250	
1,200.00	1,199.94	1,175.51	1,168.05	2.57	3.20	-72.74	73.27	-130.38	151.92	146.73	5.20	29.228	
1,300.00	1,299.72	1,266.38	1,256.44	2.80	3.62	-75.45	80.11	-150.30	173.21	167.55	5.66	30.615	
1,400.00	1,399.20	1,355.35	1,342.11	3.03	4.08	-78.38	87.91	-173.01	198.06	191.93	6.13	32.333	
1,500.00	1,498.27	1,442.16	1,424.74	3.28	4.60	-81.25	96.55	-198.17	226.69	220.08	6.61	34.281	
1,600.00	1,596.81	1,526.60	1,504.09	3.55	5.15	-83.90	105.92	-225.48	259.24	252.11	7.13	36.360	
1,700.00	1,694.69	1,608.49	1,579.97	3.87	5.74	-86.25	115.92	-254.58	295.70	288.01	7.69	38.461	
1,800.00	1,791.80	1,687.70	1,652.28	4.22	6.38	-88.27	126.41	-285.14	336.03	327.73	8.30	40.495	
1,851.10	1,841.09	1,727.10	1,687.82	4.43	6.72	-89.17	131.93	-301.22	358.09	349.46	8.63	41.488	
1,900.00	1,888.13	1,764.17	1,720.99	4.63	7.05	-90.39	137.31	-316.88	380.10	371.13	8.97	42.396	
2,000.00	1,984.34	1,838.29	1,786.49	5.06	7.76	-92.42	148.57	-349.70	427.64	417.96	9.67	44.205	
2,100.00	2,080.55	1,910.07	1,848.81	5.52	8.48	-93.96	160.14	-383.37	478.25	467.84	10.41	45.956	
2,200.00	2,176.77	1,979.50	1,908.00	5.99	9.24	-95.12	171.91	-417.68	531.62	520.46	11.16	47.639	
2,300.00	2,272.98	2,050.34	1,967.24	6.47	10.06	-96.04	184.53	-454.42	587.52	575.58	11.94	49.192	
2,400.00	2,369.19	2,127.29	2,030.93	6.96	10.99	-96.83	198.55	-495.26	644.75	631.99	12.76	50.518	
2,500.00	2,465.40	2,208.94	2,098.51	7.46	11.98	-97.54	213.43	-538.60	702.08	688.46	13.62	51.563	
2,600.00	2,561.61	2,290.59	2,166.09	7.97	12.98	-98.14	228.31	-581.94	759.47	744.98	14.49	52.422	
2,700.00	2,657.82	2,372.24	2,233.67	8.48	13.99	-98.66	243.19	-625.28	816.91	801.53	15.37	53.135	
2,800.00	2,754.03	2,453.89	2,301.25	8.99	15.01	-99.11	258.07	-668.62	874.38	858.11	16.27	53.732	
2,900.00	2,850.24	2,535.54	2,368.83	9.51	16.02	-99.51	272.95	-711.96	931.89	914.71	17.18	54.235	
3,000.00	2,946.46	2,617.18	2,436.41	10.03	17.04	-99.86	287.83	-755.30	989.43	971.33	18.10	54.662	
3,100.00	3,042.67	2,698.83	2,503.98	10.55	18.06	-100.17	302.71	-798.64	1,046.99	1,027.96	19.03	55.026	
3,200.00	3,138.88	2,780.48	2,571.56	11.08	19.09	-100.45	317.59	-841.98	1,104.56	1,084.60	19.96	55.337	
3,300.00	3,235.09	2,862.13	2,639.14	11.61	20.11	-100.70	332.47	-885.31	1,162.16	1,141.26	20.90	55.605	
3,400.00	3,331.30	2,943.78	2,706.72	12.14	21.14	-100.93	347.35	-928.65	1,219.76	1,197.92	21.84	55.838	
3,500.00	3,427.51	3,025.43	2,774.30	12.67	22.17	-101.13	362.23	-971.99	1,277.38	1,254.59	22.79	56.041	
3,600.00	3,523.72	3,107.08	2,841.88	13.20	23.20	-101.32	377.11	-1,015.33	1,335.01	1,311.26	23.75	56.218	
3,700.00	3,619.94	3,188.73	2,909.46	13.73	24.23	-101.50	391.99	-1,058.67	1,392.65	1,367.94	24.70	56.374	
3,800.00	3,716.15	3,270.38	2,977.03	14.26	25.26	-101.66	406.87	-1,102.01	1,450.29	1,424.63	25.66	56.511	
3,900.00	3,812.36	3,352.03	3,044.61	14.80	26.30	-101.80	421.75	-1,145.35	1,507.94	1,481.32	26.63	56.633	
4,000.00	3,908.57	3,433.67	3,112.19	15.34	27.33	-101.94	436.63	-1,188.69	1,565.60	1,538.01	27.59	56.741	
4,100.00	4,004.78	3,515.32	3,179.77	15.87	28.37	-102.07	451.51	-1,232.03	1,623.26	1,594.70	28.56	56.838	
4,200.00	4,100.99	3,596.97	3,247.35	16.41	29.40	-102.19	466.39	-1,275.37	1,680.93	1,651.40	29.53	56.924	
4,300.00	4,197.20	3,678.62	3,314.93	16.95	30.44	-102.30	481.27	-1,318.71	1,738.61	1,708.10	30.50	57.002	
4,336.74	4,232.55	3,708.62	3,339.76	17.14	30.82	-102.34	486.74	-1,334.63	1,759.80	1,728.94	30.86	57.028	
4,400.00	4,293.55	3,760.35	3,382.57	17.44	31.47	-103.03	496.17	-1,362.09	1,796.19	1,764.56	31.63	56.789	
4,500.00	4,390.53	3,842.42	3,450.50	17.84	32.52	-104.04	511.12	-1,405.65	1,853.32	1,820.54	32.78	56.538	
4,600.00	4,488.11	3,924.80	3,518.68	18.21	33.56	-104.93	526.14	-1,449.38	1,909.93	1,876.02	33.91	56.326	
4,700.00	4,586.23	4,007.44	3,587.08	18.55	34.61	-105.72	541.20	-1,493.24	1,966.00	1,930.99	35.01	56.156	

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation



BILL BARRETT CORPORATION

Anticollision Report

Company: BILL BARRETT CORP
Project: CARBON COUNTY, UT (NAD 27)
Reference Site: SECTION 27 T12S R16E
Site Error: 0.00ft
Reference Well: PETERS POINT UF 9-27-12-16
Well Error: 0.00ft
Reference Wellbore: PT PT 9-27-12-16
Reference Design: Design #1

Local Co-ordinate Reference: Well PETERS POINT UF 9-27-12-16
TVD Reference: WELL @ 7211.00ft (Original Well Elev)
MD Reference: WELL @ 7211.00ft (Original Well Elev)
North Reference: True
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: Compass
Offset TVD Reference: Offset Datum

Offset Design SECTION 27 T12S R16E - PETERS POINT UF 11-27-12-16 - PT PT 11-27-12-16 - Design #1													Offset Site Error: 0.00 ft
Survey Program: 0-MWD													Offset Well Error: 0.00 ft
Reference		Offset		Semi Major Axis			Distance						Warning
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)	Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor	
4,800.00	4,684.82	4,090.27	3,655.64	18.86	35.66	-106.42	556.29	-1,537.21	2,021.49	1,985.42	36.08	56.031	
4,900.00	4,783.81	4,173.25	3,724.32	19.15	36.72	-107.04	571.42	-1,581.26	2,076.41	2,039.30	37.11	55.953	
5,000.00	4,883.14	4,256.32	3,793.07	19.40	37.77	-107.58	586.55	-1,625.35	2,130.75	2,092.65	38.10	55.923	
5,100.00	4,982.74	4,339.42	3,861.85	19.61	38.83	-108.04	601.70	-1,669.45	2,184.50	2,145.45	39.05	55.942	
5,200.00	5,082.54	4,422.48	3,930.60	19.80	39.89	-108.44	616.84	-1,713.55	2,237.67	2,197.72	39.95	56.010	
5,300.00	5,182.47	4,505.46	3,999.28	19.95	40.94	-108.78	631.96	-1,757.59	2,290.29	2,249.48	40.81	56.127	
5,391.54	5,274.00	4,581.31	4,062.05	20.07	41.91	-97.67	645.78	-1,797.85	2,337.97	2,298.45	39.52	59.166	
5,400.00	5,282.46	4,588.31	4,067.85	20.07	42.00	-97.62	647.06	-1,801.56	2,342.35	2,302.81	39.54	59.234	
5,500.00	5,382.46	4,671.07	4,136.35	20.20	43.05	-97.04	662.14	-1,845.50	2,394.30	2,354.41	39.89	60.021	
5,600.00	5,482.46	4,753.84	4,204.86	20.32	44.10	-96.48	677.22	-1,889.43	2,446.43	2,406.20	40.23	60.806	
5,700.00	5,582.46	4,836.61	4,273.36	20.44	45.16	-95.94	692.31	-1,933.36	2,498.74	2,458.17	40.57	61.588	
5,800.00	5,682.46	4,919.37	4,341.86	20.57	46.21	-95.43	707.39	-1,977.29	2,551.21	2,510.30	40.91	62.365	
5,900.00	5,782.46	5,002.14	4,410.37	20.70	47.27	-94.93	722.48	-2,021.23	2,603.83	2,562.59	41.24	63.138	
6,000.00	5,882.46	5,084.91	4,478.87	20.83	48.32	-94.45	737.56	-2,065.16	2,656.60	2,615.03	41.57	63.906	
6,100.00	5,982.46	6,687.43	5,982.46	20.96	57.13	-90.56	886.49	-2,498.94	2,682.64	2,643.42	39.22	68.398	
6,200.00	6,082.46	6,787.43	6,082.46	21.09	57.18	-90.56	886.49	-2,498.94	2,682.64	2,643.14	39.50	67.910	
6,300.00	6,182.46	6,887.43	6,182.46	21.22	57.23	-90.56	886.49	-2,498.94	2,682.64	2,642.85	39.79	67.424	
6,400.00	6,282.46	6,987.43	6,282.46	21.36	57.29	-90.56	886.49	-2,498.94	2,682.64	2,642.56	40.07	66.941	
6,500.00	6,382.46	7,087.43	6,382.46	21.50	57.34	-90.56	886.49	-2,498.94	2,682.64	2,642.27	40.36	66.460	
6,600.00	6,482.46	7,187.43	6,482.46	21.63	57.39	-90.56	886.49	-2,498.94	2,682.64	2,641.98	40.66	65.982	
6,700.00	6,582.46	7,287.43	6,582.46	21.77	57.45	-90.56	886.49	-2,498.94	2,682.64	2,641.69	40.95	65.506	
6,800.00	6,682.46	7,387.43	6,682.46	21.92	57.50	-90.56	886.49	-2,498.94	2,682.64	2,641.39	41.25	65.033	
6,900.00	6,782.46	7,487.43	6,782.46	22.06	57.56	-90.56	886.49	-2,498.94	2,682.64	2,641.09	41.55	64.563	
7,000.00	6,882.46	7,587.43	6,882.46	22.20	57.62	-90.56	886.49	-2,498.94	2,682.64	2,640.78	41.85	64.096	
7,100.00	6,982.46	7,687.43	6,982.46	22.35	57.68	-90.56	886.49	-2,498.94	2,682.64	2,640.48	42.16	63.632	
7,200.00	7,082.46	7,787.43	7,082.46	22.49	57.74	-90.56	886.49	-2,498.94	2,682.64	2,640.17	42.47	63.171	
7,300.00	7,182.46	7,887.43	7,182.46	22.64	57.80	-90.56	886.49	-2,498.94	2,682.64	2,639.86	42.78	62.713	
7,400.00	7,282.46	7,987.43	7,282.46	22.79	57.86	-90.56	886.49	-2,498.94	2,682.64	2,639.55	43.09	62.259	
7,500.00	7,382.46	8,087.43	7,382.46	22.94	57.92	-90.56	886.49	-2,498.94	2,682.64	2,639.24	43.40	61.808	
7,600.00	7,482.46	8,187.43	7,482.46	23.09	57.98	-90.56	886.49	-2,498.94	2,682.64	2,638.92	43.72	61.360	
7,673.54	7,556.00	8,260.98	7,556.00	23.21	58.03	-90.56	886.49	-2,498.94	2,682.64	2,638.68	43.95	61.034	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation



Company: BILL BARRETT CORP
 Project: CARBON COUNTY, UT (NAD 27)
 Reference Site: SECTION 27 T12S R16E
 Site Error: 0.00ft
 Reference Well: PETERS POINT UF 9-27-12-16
 Well Error: 0.00ft
 Reference Wellbore: PT PT 9-27-12-16
 Reference Design: Design #1

Local Co-ordinate Reference: Well PETERS POINT UF 9-27-12-16
 TVD Reference: WELL @ 7211.00ft (Original Well Elev)
 MD Reference: WELL @ 7211.00ft (Original Well Elev)
 North Reference: True
 Survey Calculation Method: Minimum Curvature
 Output errors are at 2.00 sigma
 Database: Compass
 Offset TVD Reference: Offset Datum

Offset Design SECTION 27 T12S R16E - PETERS POINT UF 15-27-12-16 - PT PT 15-27-12-16 - Design #1													Offset Site Error: 0.00 ft
Survey Program: 0-MWD													Offset Well Error: 0.00 ft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Distance		Minimum Separation (ft)	Separation Factor	Warning		
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)		Offset Wellbore Centre +N/-S (ft)	+E/-W (ft)					Between Centres (ft)
0.00	0.00	0.00	0.00	0.00	0.00	-35.50	13.14	-9.37	16.14				
100.00	100.00	100.00	100.00	0.10	0.10	-35.50	13.14	-9.37	16.14	15.95	0.19	84.488	
200.00	200.00	200.00	200.00	0.32	0.32	-35.50	13.14	-9.37	16.14	15.50	0.64	25.198	
300.00	300.00	300.00	300.00	0.55	0.55	-35.50	13.14	-9.37	16.14	15.05	1.09	14.807	
400.00	400.00	400.00	400.00	0.77	0.77	-35.50	13.14	-9.37	16.14	14.60	1.54	10.484	
500.00	500.00	500.00	500.00	0.99	0.99	-35.50	13.14	-9.37	16.14	14.15	1.99	8.115	
600.00	600.00	600.00	600.00	1.22	1.22	-35.50	13.14	-9.37	16.14	13.70	2.44	6.619	
700.00	700.00	700.00	700.00	1.44	1.44	-35.50	13.14	-9.37	16.14	13.25	2.89	5.589	
800.00	800.00	800.00	800.00	1.67	1.67	-35.50	13.14	-9.37	16.14	12.80	3.34	4.836	
900.00	900.00	900.00	900.00	1.89	1.89	-35.50	13.14	-9.37	16.14	12.35	3.79	4.262	
1,000.00	1,000.00	1,000.00	1,000.00	2.12	2.12	-35.50	13.14	-9.37	16.14	11.90	4.24	3.810	
1,060.00	1,060.00	1,060.00	1,060.00	2.25	2.25	-35.50	13.14	-9.37	16.14	11.63	4.51	3.582	
1,100.00	1,100.00	1,099.92	1,099.92	2.34	2.34	-48.80	13.02	-9.70	16.05	11.37	4.68	3.431	
1,153.34	1,153.32	1,153.07	1,153.04	2.46	2.44	-57.53	12.47	-11.14	15.86	10.96	4.90	3.238 CC, ES	
1,200.00	1,199.94	1,199.41	1,199.32	2.57	2.53	-70.68	11.64	-13.34	16.30	11.20	5.09	3.201 SF	
1,300.00	1,299.72	1,297.88	1,297.45	2.80	2.73	-103.52	8.79	-20.91	23.03	17.52	5.52	4.175	
1,400.00	1,399.20	1,394.62	1,393.44	3.03	2.95	-123.18	4.53	-32.19	39.66	33.71	5.95	6.661	
1,500.00	1,498.27	1,489.02	1,486.52	3.28	3.20	-132.31	-1.00	-46.83	64.49	58.09	6.40	10.080	
1,600.00	1,596.81	1,580.49	1,576.03	3.55	3.49	-136.85	-7.64	-64.43	96.26	89.41	6.85	14.052	
1,700.00	1,694.69	1,668.57	1,661.45	3.87	3.82	-139.30	-15.22	-84.53	134.34	127.03	7.31	18.367	
1,800.00	1,791.80	1,752.87	1,742.36	4.22	4.18	-140.67	-23.56	-106.62	178.29	170.50	7.79	22.881	
1,851.10	1,841.09	1,794.39	1,781.88	4.43	4.38	-141.12	-28.05	-118.52	202.88	194.84	8.04	25.238	
1,900.00	1,888.13	1,833.25	1,818.67	4.63	4.58	-141.71	-32.48	-130.27	227.43	219.13	8.30	27.413	
2,000.00	1,984.34	1,912.69	1,893.19	5.06	5.03	-142.43	-42.19	-156.00	279.60	270.76	8.84	31.624	
2,100.00	2,080.55	1,997.49	1,972.46	5.52	5.55	-142.91	-52.82	-184.17	332.55	323.15	9.40	35.370	
2,200.00	2,176.77	2,082.30	2,051.74	5.99	6.09	-143.25	-63.46	-212.34	385.51	375.53	9.98	38.617	
2,300.00	2,272.98	2,167.10	2,131.02	6.47	6.65	-143.51	-74.09	-240.52	438.48	427.91	10.58	41.452	
2,400.00	2,369.19	2,251.91	2,210.30	6.96	7.22	-143.71	-84.72	-268.69	491.46	480.27	11.19	43.933	
2,500.00	2,465.40	2,336.71	2,289.57	7.46	7.81	-143.87	-95.35	-296.87	544.44	532.63	11.81	46.113	
2,600.00	2,561.61	2,421.51	2,368.85	7.97	8.39	-144.01	-105.98	-325.04	597.42	584.98	12.44	48.037	
2,700.00	2,657.82	2,506.32	2,448.13	8.48	8.99	-144.12	-116.62	-353.21	650.40	637.33	13.08	49.743	
2,800.00	2,754.03	2,591.12	2,527.41	8.99	9.59	-144.22	-127.25	-381.39	703.39	689.66	13.72	51.261	
2,900.00	2,850.24	2,675.93	2,606.68	9.51	10.19	-144.30	-137.88	-409.56	756.37	742.00	14.37	52.618	
3,000.00	2,946.46	2,760.73	2,685.96	10.03	10.80	-144.37	-148.51	-437.73	809.36	794.32	15.03	53.837	
3,100.00	3,042.67	2,845.54	2,765.24	10.55	11.41	-144.43	-159.15	-465.91	862.35	846.65	15.70	54.938	
3,200.00	3,138.88	2,930.34	2,844.52	11.08	12.02	-144.49	-169.78	-494.08	915.33	898.97	16.36	55.935	
3,300.00	3,235.09	3,015.14	2,923.80	11.61	12.64	-144.54	-180.41	-522.26	968.32	951.29	17.04	56.841	
3,400.00	3,331.30	3,099.95	3,003.07	12.14	13.26	-144.58	-191.04	-550.43	1,021.31	1,003.60	17.71	57.668	
3,500.00	3,427.51	3,184.75	3,082.35	12.67	13.87	-144.62	-201.67	-578.60	1,074.30	1,055.91	18.39	58.423	
3,600.00	3,523.72	3,269.56	3,161.63	13.20	14.49	-144.66	-212.31	-606.78	1,127.29	1,108.22	19.07	59.116	
3,700.00	3,619.94	3,354.36	3,240.91	13.73	15.12	-144.69	-222.94	-634.95	1,180.28	1,160.53	19.75	59.754	
3,800.00	3,716.15	3,439.16	3,320.18	14.26	15.74	-144.72	-233.57	-663.12	1,233.27	1,212.83	20.44	60.342	
3,900.00	3,812.36	3,523.97	3,399.46	14.80	16.36	-144.75	-244.20	-691.30	1,286.26	1,265.14	21.13	60.887	
4,000.00	3,908.57	3,608.77	3,478.74	15.34	16.98	-144.77	-254.84	-719.47	1,339.25	1,317.44	21.81	61.393	
4,100.00	4,004.78	3,693.58	3,558.02	15.87	17.61	-144.80	-265.47	-747.65	1,392.24	1,369.74	22.51	61.863	
4,200.00	4,100.99	3,778.38	3,637.29	16.41	18.23	-144.82	-276.10	-775.82	1,445.23	1,422.04	23.20	62.300	
4,300.00	4,197.20	3,863.18	3,716.57	16.95	18.86	-144.84	-286.73	-803.99	1,498.23	1,474.33	23.89	62.708	
4,336.74	4,232.55	3,894.34	3,745.70	17.14	19.09	-144.85	-290.64	-814.34	1,517.69	1,493.55	24.15	62.852	
4,400.00	4,293.55	3,948.21	3,796.06	17.44	19.49	-145.18	-297.39	-832.24	1,550.85	1,526.20	24.65	62.918	
4,500.00	4,390.53	4,034.27	3,876.51	17.84	20.13	-145.63	-308.18	-860.83	1,601.76	1,576.37	25.40	63.071	
4,600.00	4,488.11	4,121.38	3,957.94	18.21	20.77	-146.00	-319.10	-889.77	1,650.81	1,624.67	26.13	63.174	
4,700.00	4,586.23	4,209.46	4,040.28	18.55	21.42	-146.29	-330.15	-919.04	1,697.95	1,671.10	26.85	63.239	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation



Company: BILL BARRETT CORP
 Project: CARBON COUNTY, UT (NAD 27)
 Reference Site: SECTION 27 T12S R16E
 Site Error: 0.00ft
 Reference Well: PETERS POINT UF 9-27-12-16
 Well Error: 0.00ft
 Reference Wellbore: PT PT 9-27-12-16
 Reference Design: Design #1

Local Co-ordinate Reference: Well PETERS POINT UF 9-27-12-16
 TVD Reference: WELL @ 7211.00ft (Original Well Elev)
 MD Reference: WELL @ 7211.00ft (Original Well Elev)
 North Reference: True
 Survey Calculation Method: Minimum Curvature
 Output errors are at: 2.00 sigma
 Database: Compass
 Offset TVD Reference: Offset Datum

Offset Design SECTION 27 T12S R16E - PETERS POINT UF 15-27-12-16 - PT PT 15-27-12-16 - Design #1													Offset Site Error: 0.00 ft
Survey Program: 0-MWD													Offset Well Error: 0.00 ft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Distance		Between Centres (ft)	Between Ellipses (ft)	Minimum Separation (ft)	Separation Factor	Warning
Measured Depth (ft)	Vertical Depth (ft)	Measured Depth (ft)	Vertical Depth (ft)	Reference (ft)	Offset (ft)		Offset Wellbore Centre +N/S (ft)	+E/W (ft)					
4,800.00	4,684.82	4,298.48	4,123.50	18.86	22.08	-146.50	-341.31	-948.61	1,743.18	1,715.63	27.55	63.274	
4,900.00	4,783.81	4,388.36	4,207.52	19.15	22.75	-146.65	-352.57	-978.47	1,786.48	1,758.25	28.23	63.286	
5,000.00	4,883.14	4,479.04	4,292.30	19.40	23.42	-146.75	-363.94	-1,008.60	1,827.82	1,798.94	28.88	63.283	
5,100.00	4,982.74	4,505.72	4,304.52	19.61	25.02	-146.24	-397.54	-1,097.62	1,862.03	1,831.91	30.12	61.824	
5,200.00	5,082.54	5,191.38	4,985.93	19.80	26.04	-146.12	-416.59	-1,148.09	1,880.05	1,848.89	31.17	60.324	
5,300.00	5,182.47	5,387.99	5,182.47	19.95	26.25	-146.25	-417.87	-1,151.49	1,883.97	1,861.82	22.14	85.080	
5,391.54	5,274.00	5,479.52	5,274.00	20.07	26.33	-134.90	-417.87	-1,151.49	1,884.88	1,862.41	22.47	83.878	
5,400.00	5,282.46	5,487.98	5,282.46	20.07	26.34	-134.90	-417.87	-1,151.49	1,884.88	1,862.37	22.51	83.734	
5,500.00	5,382.46	5,587.98	5,382.46	20.20	26.43	-134.90	-417.87	-1,151.49	1,884.88	1,861.89	22.99	81.989	
5,600.00	5,482.46	5,687.98	5,482.46	20.32	26.52	-134.90	-417.87	-1,151.49	1,884.88	1,861.42	23.46	80.333	
5,700.00	5,582.46	5,787.98	5,582.46	20.44	26.62	-134.90	-417.87	-1,151.49	1,884.88	1,860.95	23.93	78.758	
5,800.00	5,682.46	5,887.98	5,682.46	20.57	26.71	-134.90	-417.87	-1,151.49	1,884.88	1,860.48	24.40	77.256	
5,900.00	5,782.46	5,987.98	5,782.46	20.70	26.81	-134.90	-417.87	-1,151.49	1,884.88	1,860.02	24.86	75.820	
6,000.00	5,882.46	6,087.98	5,882.46	20.83	26.91	-134.90	-417.87	-1,151.49	1,884.88	1,859.56	25.32	74.445	
6,100.00	5,982.46	6,187.98	5,982.46	20.96	27.01	-134.90	-417.87	-1,151.49	1,884.88	1,859.10	25.78	73.127	
6,200.00	6,082.46	6,287.98	6,082.46	21.09	27.11	-134.90	-417.87	-1,151.49	1,884.88	1,858.65	26.23	71.860	
6,300.00	6,182.46	6,387.98	6,182.46	21.22	27.21	-134.90	-417.87	-1,151.49	1,884.88	1,858.20	26.68	70.642	
6,400.00	6,282.46	6,487.98	6,282.46	21.36	27.32	-134.90	-417.87	-1,151.49	1,884.88	1,857.75	27.13	69.468	
6,500.00	6,382.46	6,587.98	6,382.46	21.50	27.43	-134.90	-417.87	-1,151.49	1,884.88	1,857.30	27.58	68.337	
6,600.00	6,482.46	6,687.98	6,482.46	21.63	27.53	-134.90	-417.87	-1,151.49	1,884.88	1,856.85	28.03	67.245	
6,700.00	6,582.46	6,787.98	6,582.46	21.77	27.64	-134.90	-417.87	-1,151.49	1,884.88	1,856.40	28.48	66.190	
6,800.00	6,682.46	6,887.98	6,682.46	21.92	27.75	-134.90	-417.87	-1,151.49	1,884.88	1,855.96	28.92	65.170	
6,900.00	6,782.46	6,987.98	6,782.46	22.06	27.87	-134.90	-417.87	-1,151.49	1,884.88	1,855.51	29.37	64.183	
7,000.00	6,882.46	7,087.98	6,882.46	22.20	27.98	-134.90	-417.87	-1,151.49	1,884.88	1,855.07	29.81	63.227	
7,100.00	6,982.46	7,187.98	6,982.46	22.35	28.09	-134.90	-417.87	-1,151.49	1,884.88	1,854.63	30.25	62.301	
7,200.00	7,082.46	7,287.98	7,082.46	22.49	28.21	-134.90	-417.87	-1,151.49	1,884.88	1,854.18	30.70	61.402	
7,300.00	7,182.46	7,387.98	7,182.46	22.64	28.33	-134.90	-417.87	-1,151.49	1,884.88	1,853.74	31.14	60.531	
7,400.00	7,282.46	7,487.98	7,282.46	22.79	28.45	-134.90	-417.87	-1,151.49	1,884.88	1,853.30	31.58	59.684	
7,500.00	7,382.46	7,587.98	7,382.46	22.94	28.57	-134.90	-417.87	-1,151.49	1,884.88	1,852.86	32.02	58.862	
7,600.00	7,482.46	7,687.98	7,482.46	23.09	28.69	-134.90	-417.87	-1,151.49	1,884.88	1,852.42	32.46	58.062	
7,648.69	7,531.15	7,736.67	7,531.15	23.17	28.75	-134.90	-417.87	-1,151.49	1,884.88	1,852.20	32.68	57.681	
7,673.54	7,556.00	7,760.52	7,555.00	23.21	28.78	-134.90	-417.87	-1,151.49	1,884.88	1,852.09	32.79	57.492	



Company: BILL BARRETT CORP
Project: CARBON COUNTY, UT (NAD 27)
Reference Site: SECTION 27 T12S R16E
Site Error: 0.00ft
Reference Well: PETERS POINT UF 9-27-12-16
Well Error: 0.00ft
Reference Wellbore: PT PT 9-27-12-16
Reference Design: Design #1

Local Co-ordinate Reference: Well PETERS POINT UF 9-27-12-16
TVD Reference: WELL @ 7211.00ft (Original Well Elev)
MD Reference: WELL @ 7211.00ft (Original Well Elev)
North Reference: True
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: Compass
Offset TVD Reference: Offset Datum

Reference Depths are relative to WELL @ 7211.00ft (Original Well Elev)

Offset Depths are relative to Offset Datum


Central Meridian is 111° 30' 0.0000 W°

Coordinates are relative to: PETERS POINT UF 9-27-12-16

Coordinate System is US State Plane 1927 (Exact solution), Utah Central 4302

Grid Convergence at Surface is: 0.89°

Ladder Plot



LEGEND

12-16, PT PT 10-27D-12-16, Design #1 PETERS POINT UF 15-27-12-16, PT PT 15-27-12-16, Design #1 PETERS POINT UF 11-27-12-16, PT PT 11-27-12-16, Design #1




Company: BILL BARRETT CORP
Project: CARBON COUNTY, UT (NAD 27)
Reference Site: SECTION 27 T12S R16E
Site Error: 0.00ft
Reference Well: PETERS POINT UF 9-27-12-16
Well Error: 0.00ft
Reference Wellbore: PT PT 9-27-12-16
Reference Design: Design #1

Local Co-ordinate Reference: Well PETERS POINT UF 9-27-12-16
TVD Reference: WELL @ 7211.00ft (Original Well Elev)
MD Reference: WELL @ 7211.00ft (Original Well Elev)
North Reference: True
Survey Calculation Method: Minimum Curvature
Output errors are at: 2.00 sigma
Database: Compass
Offset TVD Reference: Offset Datum

Reference Depths are relative to WELL @ 7211.00ft (Original Well Elev)
Offset Depths are relative to Offset Datum
Central Meridian is 111° 30' 0.0000 W°

Coordinates are relative to: PETERS POINT UF 9-27-12-16
Coordinate System is US State Plane 1927 (Exact solution), Utah Central 4302
Grid Convergence at Surface is: 0.89°

Separation Factor Plot



LEGEND

12-16, PT PT 10-27D-12-16, Design #1 PETERS POINT UF 15-27-12-16, PT PT 15-27-12-16, Design #1 PETERS POINT UF 11-27-12-16

PRESSURE CONTROL EQUIPMENT – Schematic Attached

A. Type: Eleven (11) Inch Double Gate Hydraulic BOP with Eleven (11) Inch Annular Preventer. The blow out preventer will be equipped as follows:

1. One (1) blind ram (above).
2. One (1) pipe ram (below).
3. Drilling spool with two (2) side outlets (choke side 3-inch minimum, kill side 2-inch minimum).
4. 3-inch diameter choke line.
5. Two (2) choke line valves (3-inch minimum).
6. Kill line (2-inch minimum).
7. Two (2) chokes.
8. Two (2) kill line valves, one of which shall be a check valve (2-inch minimum).
9. Upper kelly cock valve with handles available.
10. Safety valve(s) & subs to fit all drill string connections in use.
11. Pressure gauge on choke manifold.
12. Fill-up line above the uppermost preventer.

B. Pressure Rating: 3,000 psi

C. Testing Procedure:

Annular Preventer

At a minimum, the Annular Preventer will be pressure tested to 50% of the rated working pressure for a period of ten (10) minutes or until provisions of the test are met, whichever is longer.

At a minimum the above pressure test will be performed:

1. When the annular preventer is initially installed;
2. Whenever any seal subject to test pressure is broken;
3. Following related repairs; and
4. At thirty (30) day intervals.

In addition, the Annular Preventer will be functionally operated at least weekly.

Blow-Out Preventer

At a minimum, the BOP, choke manifold, and related equipment will be pressure tested to the approved working pressure of the BOP stack (if isolated from the surface casing by a test plug) or to 70% of the internal yield strength of the surface casing (if the BOP is not isolated from the casing by a test plug). Pressure will be

maintained for a period of at least ten (10) minutes or until the requirements of the test are met, whichever is longer.

At a minimum, the above pressure test will be performed:

1. When the BOP is initially installed;
2. Whenever any seal subject to test pressure is broken;
3. Following related repairs; and
4. At thirty (30) day intervals.

In addition the pipe and blind rams will be activated each trip, but not more than once each day. All BOP drills and tests will be recorded in the IADC driller's log.

D. Choke Manifold Equipment:

All choke lines will be straight lines unless turns use tee blocks or are targeted with running tees, and will be anchored to prevent whip and vibration.

E. Accumulator:

The accumulator will have sufficient capacity to open the hydraulically-controlled choke line valve (if so equipped), close all rams plus the annular preventer, and retain a minimum of 200 psi above precharge on the closing manifold without the use of closing unit pumps. The fluid reservoir capacity will be double the usable fluid volume of the accumulator system capacity and the fluid level of the reservoir will be maintained at the manufacturer's recommendations.

The BOP system will have two (2) independent power sources to close the preventers. Nitrogen bottles (3 minimum) will be one (1) of these independent power sources and will maintain a charge equal to the manufacturer's specifications.

The accumulator precharge pressure test will be conducted prior to connecting the closing unit to the BOP stack and at least once every six (6) months thereafter. The accumulator pressure will be corrected if the measured precharge pressure is found to be above or below the maximum or minimum limits specified in the *Onshore Oil & Gas Order Number 2*.

A manual locking device (i.e. hand wheels) or automatic locking device will be installed on all systems of 2M or greater. A valve will be installed in the closing line as close as possible to the annular preventer to act as a locking device. This valve will be maintained in the open position and will be closed only when the power source for the accumulator is inoperative.

Remote controls shall be readily accessible to the driller. Remote controls for all 3M or greater systems will be capable of closing all preventers. Remote controls for 5M or greater systems will be capable of both opening and closing all preventers. Master controls will be at the accumulator and will be capable of opening and closing all preventers and the choke line valve (if so equipped).


F. Miscellaneous Information:

The Blow-Out Preventer and related pressure control equipment will be installed, tested and maintained in compliance with the specifications in and requirements of *Onshore Oil & Gas Order Number 2*. The choke manifold will be located outside the rig sub-structure. The hydraulic BOP closing unit will be located at least twenty-five (25) feet from the well head but readily accessible to the driller. Exact locations and configurations of the hydraulic BOP closing unit will depend upon the particular rig contracted to drill this hole.

A flare line will be installed after the choke manifold, extending 125 feet (minimum) from the center of the drill hole to a separate flare pit.


BILL BARRETT CORPORATION

TYPICAL 3,000 p.s.i. CHOKE MANIFOLD



BILL BARRETT CORPORATION

TYPICAL 3,000 p.s.i. BLOWOUT PREVENTER



SURFACE USE PLAN

BILL BARRETT CORPORATION **Peter's Point Unit Federal 16-27-12-16 Pad Wells**

<u>Peter's Point Unit Federal #9-27D-12-16</u> SESE, 1050' FSL, 790' FEL, Sec. 27, T12S-R16E (surface hole) NESE, 1963' FSL, 608' FEL, T12S-R16E (bottom hole) Carbon County, Utah	<u>Peter's Point Unit Federal #15-27D-12-16</u> SESE, 1063' FSL, 799' FEL, Sec. 27, T12S-R16E (surface hole) SWSE, 628' FSL, 1941' FEL, Sec. 27, T12S-R16E (bottom hole) Carbon County, Utah
<u>Peter's Point Unit Federal #10-27D-12-16</u> SESE, 1075' FSL, 809' FEL, Sec. 27, T12S-R16E (surface hole) NWSE, 1952' FSL, 1947' FEL, Sec. 27, T12S-R16E (bottom hole) Carbon County, Utah	<u>Peter's Point Unit Federal #11-27D-12-16</u> SESE, 1088' FSL, 819' FEL, Sec. 27, T12S-R16E (surface hole) NESW, 1929' FSL, 1993' FWL, Sec. 27, T12S-R16E (bottom hole) Carbon County, Utah

The onsite for this pad occurred on April 11, 2008. This is an existing pad with one vertical well (the 16-27-12-15) and four additional directional wells are planned. Minimal additional disturbance is required for expansion to accommodate the additional wells.

The excavation contractor would be provided with an approved copy of the surface use plan of operations before initiating construction.

1. **Existing Roads:**

- a. The existing well pad is located approximately 50 miles from Myton, Utah. Maps reflecting directions to the proposed well pad are included (see Topographic Maps A and B).
- b. An access road, approximately 663 feet in length exists to this pad. Total road disturbance requested for this access is 50-feet.
- c. Surface disturbance and vehicular travel would be limited to the approved existing access road. Adequate signs would be posted, as necessary, to warn the public of project related traffic.
- d. BBC would be responsible for all maintenance of the access road including drainage structures.
- e. The use of roads under State and County Road Department maintenance is necessary to access the Peter's Point Unit. However, an encroachment permit is not anticipated since there are no upgrades proposed to the State or County road systems at this time.
- f. All existing roads would be maintained and kept in good repair during all phases of operation.
- g. Vehicle operators would obey posted speed restrictions and observe safe speeds commensurate with road and weather conditions.

2. **Planned Access Road:**

- a. See 1. b. under Existing Roads.

3. Location of Existing Wells (see Topographic Map C):

- a. Following is a list of wells with surface hole locations within a one-mile radius of the proposed well:

i. water wells	none
ii. injection wells	none
iii. disposal wells	none
iv. drilling wells	none
v. temp shut-in wells	none
vi. producing wells	six
vii. abandoned wells	none

4. Location of Production Facilities (see enclosed "Proposed Facility Layout"):

- a. All facilities for this pad would be located adjacent to the existing facilities for the Peter's Point 16-27. Each well would have its own meter run and separator and four (4) additional 400-bbl tanks would be installed as necessary.
- b. All permanent above-ground structures would be painted a flat, non-reflective Olive Black to match the standard environmental colors. All facilities would be painted the designated color at the time of installation. Facilities required to comply with the Occupational Safety and Health Act (OSHA) may be excluded.
- d. Site security guidelines identified in 43 CFR 3162.7-5 and Onshore Oil and Gas Order No. 3 would be adhered to.
- e. Gas meter runs would be constructed and located on lease within 500 feet of the wellheads. Meter runs are housed and/or fenced. All gas production and measurement shall comply with the provisions of 43 CFR 3162.7-3, Onshore Oil and Gas Order No. 5, and American Gas Association (AGA) Report No. 3. Use of electronic flow meter (EFMs) for gas measurement purposes is requested with this application as well as use of flow conditioners (versus straightening vanes) for each new well.
- f. A tank battery exists on this lease and would be modified as per the proposed facility layout to include additional equipment. All loading lines and valves would be placed inside the berm surrounding the tank battery or would have a secondary containment vessel. All liquid hydrocarbon production and measurement shall conform to the provisions of 43 CFR 3162.7-2 and Onshore Oil and Gas Order No. 4 for the measurement of oil. BBC requests permission to install the necessary production/operation facilities with this application.
- g. Any necessary pits would be properly fenced to prevent any wildlife and livestock entry.
- h. All access roads would be maintained as necessary to prevent erosion and accommodate year-round traffic as practicable. The roads would be maintained in a safe, useable condition.

- i. The site would require periodic maintenance to ensure that drainages are kept open and free of debris and that surfaces are properly treated to reduce erosion, fugitive dust, and impacts to adjacent areas.
- j. A 6-inch buried gas pipeline, approximately 783 feet in length, exists to this location.

5. Location and Type of Water Supply:

- a. Bill Barrett Corporation would use water consistent with approvals granted by the Utah State Engineer's Office under Application Number 90-1853 (T76109) which expires April 3, 2009 or an existing water well in Sec. 13, T12S-R14E granted by the Utah State Engineer's Office under Application Number 90-1849 (T75896) which expires September 13, 2008.
- b. Water use for this location will most likely be diverted from Nine Mile Creek, the S¼ of Section 8, T12S-R16E or from a water well located in the N¼ of State Section 32-T12S-R16E. For either of these sources, bobtail trucks would haul the water, traveling Cottonwood Canyon dugway to Peter's Point road.

6. Source of Construction Material:

- a. The use of materials would conform to 43 CFR 3610.2-3.
- b. No construction materials would be taken off-lease.
- c. If any additional gravel is required, it would be obtained from SITLA materials permits or from federal BBC locations within the Peter's Point unit.

7. Methods of Handling Waste Disposal:

- a. All wastes associated with this application would be contained and disposed of utilizing approved facilities.
- b. Drill cuttings would be contained and buried on site.
- c. The fluids in the existing reserve pit for the Peter's Point 16-27 well will be disposed of or evaporated prior to the expansion of the pit, which is necessary to accommodate the additional wells. The reserve pit is located outboard of the location along the southwest side of the pad.
- d. The reserve pit would be constructed so as not to leak, break or allow any discharge.
- e. Due to the expansion necessary, the reserve pit would be re-lined with a 12 mil minimum thickness polyethylene nylon reinforced liner material. The liner would overlay straw, soil and/or bentonite if rock is encountered during excavation. The pit liner would overlap the pit walls and be anchored with soil and/or rocks to hold it in place. No trash, scrap pipe, etc., that could puncture the liner would be disposed of in the pit. Pit walls would be sloped no greater than 2:1 and the depth of the reserve pit would be approximately 8-feet with a minimum of 2 foot freeboard.

- f. The reserve pit has been located in cut material. Three sides of the reserve pit would be fenced before drilling starts. The fourth side would be fenced as soon as drilling is completed and shall remain until the pit is dry. After the reserve pit has dried, all areas not needed for production would be rehabilitated as per the plans for reclamation of surface (10. below).
- g. Chemicals on the EPA's Consolidated List of Chemicals subject to reporting under Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) in quantities over 10,000 pounds that may be used, produced, stored, transported or disposed of annually in association with the drilling, testing or completion of each well include diesel fuel, hydrochloric acid and silica sand. This material would be consumed in the drilling and completion process. No extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities would be used, produced, stored, transported or disposed of in association with the drilling, testing or completion of the wells.
- h. Trash would be contained in a trash cage or roll-off container and hauled away to an approved disposal site as necessary but no later than at the completion of drilling operations. The contents of the trash container would be hauled off periodically to the approved Carbon or Uintah County Landfill.
- i. Produced fluids from each well other than water would be produced into a test tank until such time as construction of production facilities is completed. Any spills of oil, gas, salt water or other produced fluids would be cleaned up and removed.
- j. After initial clean-up and based on volumes, BBC would install a tank (maximum size 400 barrel capacity) to contain produced waste water. After first production, produced wastewater would be confined to a lined pit or storage tank for a period not to exceed ninety (90) days. Thereafter, produced water would be used in further drilling and completion activities, evaporated in the pit, or hauled to a State approved disposal facility.
- k. Any salts and/or chemicals, which are an integral part of the drilling system, would be disposed of in the same manner as the drilling fluid.
- l. Sanitary facilities would be on site at all times during operations. Sewage would be placed in a portable chemical toilet and the toilet replaced periodically utilizing a licensed contractor to transport by truck the portable chemical toilet so that its contents can be delivered to the Price or Vernal Wastewater Treatment Facility in accordance with state and county regulations.
- m. Any liquid hydrocarbons produced during completion work would be contained in test tanks on the well location. The tanks would be removed from location at a later date. A flare pit may be constructed a minimum of 110' from the wellheads and may be used during completion work. In the event a flare pit proves to be unworkable in this situation, a flare stack would be installed. BBC would flow back as much fluid and gas as possible into vessels, separating the fluid from the gas. The fluid would then be either returned to the reserve pit or placed into a tank. Gas would be then directed into the flare pit or the flare stack with a constant source of ignition. Natural gas would be directed to the pipeline as soon as pipeline gas quality standards are met.

- n. Hydrocarbons would be removed from the reserve pit as soon as practical. In the event immediate removal is not practical, the reserve pit would be flagged overhead or covered with wire or plastic mesh to protect migrating birds.

8. Ancillary Facilities:

- a. Garbage containers and portable toilets are the only ancillary facilities proposed in this application

9. Well Site Layout:

- a. Each well would be properly identified in accordance with 43 CFR 3162.6.
- b. The rig layout and cross section diagrams are enclosed (see Location Layout and Cross Section Plats).
- c. The pad and road designs are consistent with BLM specifications.
- d. Minimal additional disturbance is necessary to accommodate the additional wells being added. The pad dimensions are 490' x 175' with a reserve pit of 248' x 100'.
- e. All surface disturbing activities would be supervised by a qualified, responsible company representative who is aware of the terms and conditions of the APD and specifications in the approved plans.
- f. All cut and fill slopes would be such that stability can be maintained for the life of the activity.
- g. Diversion ditches would be constructed, if necessary, around the well pad to prevent surface waters from entering the area.
- h. The stockpiled topsoil (first 6 inches or maximum available) would be stored in a windrow on the uphill side of the location to prevent any possible contamination. All topsoil would be stockpiled for reclamation in such a way as to prevent soil loss and contamination.
- i. Pits would remain fenced until site cleanup.
- j. If air drilling occurs, the blooie line would be located at least 100 feet from the individual well head and would run from the each wellhead directly to the pit.
- k. Water application may be implemented if necessary to minimize the amount of fugitive dust.

10. Plan for Restoration of the Surface:

Producing Wells

- a. Rat and mouse holes would be filled and compacted from bottom to top immediately upon release of the drilling rig from location.
- b. The reserve pit would be closed as soon as reasonably practical, but no later than 90 days from completion of the last well on the pad, provided favorable weather conditions and that there are no plans to re-use the pit within one year. An extension may be given at the discretion of the BLM Authorized Officer. The following are requirements for pit closures:
 - Squeezing of pit fluids and cuttings is prohibited;
 - Pits must be dry of fluids or they must be removed via vac-truck or other environmentally acceptable method prior to backfilling, re-contouring and replacement of topsoil;
 - Mud and cuttings left in pit must be buried at least 3-feet below re-contoured grade;
 - If a liner was used, the polyethylene nylon reinforced liner shall be torn and perforated before backfilling;
 - The operator would be responsible for re-contouring any subsidence areas that develop from closing a pit before it is sufficiently dry.
 - The operator shall contact the BLM Authorized Officer at least 48-hours prior to the filling and reclamation of pits and the start of any reclamation such as recontouring and reseeding.
- c. Reclamation requirements would be dependant upon plans for subsequent drilling activity on the pad. The operator shall contact the BLM Authorized Officer **within 90 days of completion of the last well on the pad** and provide plans for subsequent pad use.
 - In the event that the operator plans to re-occupy the pad within three years, the operator shall seed the unused portions of the pad with a cover crop as approved for this use by the BLM. If necessary, this cover crop would be replanted each year that the pad remains in an un-reclaimed state. Unless otherwise specifically authorized, no pad shall remain in an un-reclaimed state for more than three years.
 - Cover crops would be seeded by broadcasting seed over all unused portions of the pad. Seed would be covered with soil to the appropriate depth by raking or other methods.
 - In the event there are no plans to re-occupy the pad within three years, interim reclamation activities would begin within 90 days. The operator would use the BLM approved seed mix and would seed during the first suitable seeding season.
 - Interim reclamation drill seeding would be conducted on the contour to a depth of 0.5 inch, followed by cultipaction to compact the seedbed, preventing soil and seed losses. To maintain quality and purity, the current years tested, certified seed with a minimum germination rate of 80% and a minimum purity of 90% would be used.

- Topsoil salvaged from the drill site and stored for more than one year would be placed at the location indicated on the well site layout drawing and graded to a depth optimum to maintain topsoil viability, seeded with the BLM prescribed seed mixture and covered with mulch for protection from wind and water erosion and to discourage the invasion of weeds.
- d. The operator would control noxious weeds along access road use authorizations, pipeline route authorizations, well sites or other applicable facilities by spraying or mechanical removal. A list of noxious weeds may be obtained from the BLM or the appropriate county extension office. On BLM administered land it is required that a Pesticide Use Proposal be submitted and approved prior to the application of herbicides, pesticides or possibly hazardous chemicals.

Dry Hole


- a. All disturbed lands associated with this project, including the pipelines, access roads, water management facilities, etc. would be expediently reclaimed and reseeded in accordance with the reclamation plan and any pertinent site-specific COAs.
11. Surface and Mineral Ownership:
- a. Surface ownership – Federal under the management of the Bureau of Land Management – Price Field Office, 125 South 600 West, Price Utah 84078; (435) 636-3600.
 - b. Mineral ownership – Federal under the management of the Bureau of Land Management – Price Field Office, 125 South 600 West, Price Utah 84078; (435) 636-3600.
12. Other Information:
- a. Montgomery Archaeological Consultants conducted Class III archeological surveys. Copies of the reports were submitted under separate cover to the appropriate agencies by Montgomery as MOAC Report No. 07-251 dated July 16, 2007.
 - b. Intermountain Paleo Consulting, Inc. conducted monitoring activities at the time of construction on the Peter's Point 16-27 pad, IPC Report No. 07-201 dated September 24, 2007. No fossils were found and additional disturbance is minimal; BBC therefore requests relief on monitoring for this location.
 - c. Areas in the proposed drilling program where fluids escaping the wellbore and exiting onto a hillside might occur will be identified. In those cases, cement and/ or fluid loss compounds (types of lost circulation fluids) would be utilized to heal up vags and cracks. Upon individual evaluation of the proposed well sites, air drilling the hole to surface casing depth may occur.
 - d. A combustor may be installed at this location for control of associated condensate tank emissions. A combustor ranges from 24" to 48" wide and is approximately 10' tall. Combustor placement would be on existing disturbance and would not be closer than 100' to any tank or wellhead.

Proposed Facility Layout

BILL BARRETT CORPORATION


LOCATION LAYOUT FOR

PETERS POINT UNIT FEDERAL #9-270-12-16,
#15-270-12-16, #10-270-12-16 & #11-270-12-16
SECTION 27, T12S, R16E, S.L.B.&M.
SE 1/4 SE 1/4



SCALE: 1" = 50'
DATE: 03-19-08
DRAWN BY: C.G.

NOTE:
Flare Pit is to
be located a min.
of 100' from the
Well Head.



Elev. Ungraded Ground at #9-270-12-16 Location Stake = 7195.8'
Elev. Graded Ground at #9-270-12-16 Location Stake = 7195.5'

UINTAN ENGINEERING & LAND SURVEYING
61 So. 300 East • Vernal, Utah 84078 • (435) 392-1997

OPERATOR CERTIFICATION

Certification:

I hereby certify that I, or someone under my direction supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein would be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filings of false statements.

Executed this 28th day of April 2008

Name: Tracey Fallang

Position Title: Regulatory Analyst

Address: 1099 18th Street, Suite 2300, Denver, CO 80202

Telephone: 303-312-8134

Field Representative Fred Goodrich

Address: 1820 W. Hwy 40, Roosevelt, UT 84066

Telephone: 435-725-3515

E-mail: _____

Tracey Fallang
Tracey Fallang, Environmental/Regulatory Analyst

BILL BARRETT CORPORATION
PRICKLY PEAR UNIT FEDERAL #9-27D-12-16,
#15-27D-12-16, #10-27D-12-16 & #11-27D-12-16
SECTION 27, T12S, R16E, S.L.B.&M.

PROCEED IN A SOUTHWESTERLY DIRECTION FROM MYTON, UTAH ALONG U.S. HIGHWAY 40 APPROXIMATELY 1.4 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE SOUTH; TURN LEFT AND PROCEED IN A SOUTHERLY, THEN SOUTHWESTERLY, THEN SOUTHERLY DIRECTION APPROXIMATELY 1.5 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE SOUTHWEST; TURN RIGHT AND PROCEED IN A SOUTHWESTERLY DIRECTION APPROXIMATELY 28.9 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE SOUTHEAST; TURN LEFT AND PROCEED IN A SOUTHEASTERLY DIRECTION APPROXIMATELY 6.4 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE SOUTHEAST; TURN RIGHT AND PROCEED IN A SOUTHEASTERLY, THEN SOUTHERLY, THEN SOUTHWESTERLY DIRECTION APPROXIMATELY 7.4 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE SOUTHWEST; TURN RIGHT AND PROCEED IN A SOUTHWESTERLY, THEN NORTHEASTERLY DIRECTION APPROXIMATELY 1.4 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE NORTHEAST; TURN LEFT AND PROCEED IN A NORTHEASTERLY DIRECTION APPROXIMATELY 3.1 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE NORTH; TURN LEFT AND PROCEED IN A NORTHERLY DIRECTION APPROXIMATELY 0.1 MILES TO THE PROPOSED LOCATION.

TOTAL DISTANCE FROM MYTON, UTAH TO THE PROPOSED WELL LOCATION IS APPROXIMATELY 50.2 MILES.

BILL BARRETT CORPORATION

PRICKLY PEAR UNIT FEDERAL #9-27D-12-16, #15-27D-12-15, #10-27D-12-15 & #11-27D-12-15
LOCATED IN CARBON COUNTY, UTAH
SECTION 27, T12S, R16E, S.L.B.&M.




PHOTO: VIEW OF LOCATION STAKES

CAMERA ANGLE: SOUTHWESTERLY



PHOTO: VIEW FROM BEGINNING OF PROPOSED ACCESS

CAMERA ANGLE: NORTHEASTERLY



UELS

Uintah Engineering & Land Surveying

85 South 200 East Vernal, Utah 84078
435-789-1017 uels@uelsinc.com

• Since 1964 •

LOCATION PHOTOS

03 24 08
MONTH DAY YEAR

PHOTO

TAKEN BY: D.R. DRAWN BY: C.P. REVISED: 00-00-00

BILL BARRETT CORPORATION


LOCATION LAYOUT FOR

PETERS POINT UNIT FEDERAL #9-27D-12-16,
#15-27D-12-16, #10-27D-12-16 & #11-27D-12-16
SECTION 27, T12S, R16E, S.L.B.&M.
SE 1/4 SE 1/4



SCALE: 1" = 50'
DATE: 03-19-08
DRAWN BY: C.G.

NOTE:
Flare Pit is to
be located a min.
of 100' from the
Well Head.



Elev. Ungraded Ground at #9-27D-12-16 Location Stake = 7195.8'
Elev. Graded Ground at #9-27D-12-16 Location Stake = 7195.5'





UINTAH ENGINEERING & LAND SURVEYING
85 So. 200 East • Vernal, Utah 84078 • (435) 789-1017

1" = 20'
X-Section
Scale
1" = 50'
DATE: 03-19-08
DRAWN BY: C.G.

BILL BARRETT CORPORATION

TYPICAL CROSS SECTIONS FOR

PETERS POINT UNIT FEDERAL #9-27D-12-16,
#15-27D-12-16, #10-27D-12-16 & #11-27D-12-16
SECTION 27, T12S, R16E, S.L.B.&M.
SE 1/4 SE 1/4



APPROXIMATE ACREAGES

EXISTING WELL SITE DISTURBANCE = ± 3.696 ACRES
PROPOSED WELL SITE DISTURBANCE = ± 0.464 ACRES
TOTAL = ± 4.160 ACRES

* NOTE:
FILL QUANTITY INCLUDES
5% FOR COMPACTION

APPROXIMATE YARDAGES

CUT
(6") Topsoil Stripping = 370 Cu. Yds.
(New Construction Only)
Remaining Location = 3,820 Cu. Yds.
TOTAL CUT = 4,190 CU.YDS.
FILL = 6,640 CU.YDS.

DEFICIT MATERIAL = <2,450> Cu. Yds.
Topsoil & Pit Backfill = 3,460 Cu. Yds.
(1/2 Pit Vol.)
EXCESS UNBALANCE = <5,910> Cu. Yds.
(After Rehabilitation)

UINTAH ENGINEERING & LAND SURVEYING
85 So. 200 East • Vernal, Utah 84078 • (435) 782-1011

R 16 E
R 17 E



PROPOSED LOCATION:
PRICKLY PEAR UNIT FEDERAL #9-27D-12-16,
#15-27D-12-16, #10-27D-12-16 & #11-27D-12-16

LEGEND:

⊙ PROPOSED LOCATION



BILL BARRETT CORPORATION

PRICKLY PEAR UNIT FEDERAL #9-27D-12-16,
 #15-27D-12-16, #10-27D-12-16 & #11-27D-12-16
 SECTION 27, T12S, R16E, S.L.B.&M.
 SE 1/4 SE 1/4



Uintah Engineering & Land Surveying
 85 South 200 East Vernal, Utah 84078
 (435) 789-1017 * FAX (435) 789-1813

TOPOGRAPHIC
MAP

03 24 08
 MONTH DAY YEAR

SCALE: 1:100,000 DRAWN BY: C.P. REVISED: 00-00-00



PROPOSED LOCATION:
PRICKLY PEAR UNIT FEDERAL #9-27D-12-16,
#15-27D-12-16, #10-27D-12-16 & #11-27D-12-16

0.1 ML. +/-

BRUSH
MYTON 50.1 MI. +/-
HIGHWAY 40 48.6 MI. +/-

T13S

**PRICKLY PEAR UNIT FEDERAL #9-27D-12-16,
#15-27D-12-16, #10-27D-12-16 & #11-27D-12-16
SECTION 27, T12S, R16E, S.L.B.&M.
SE 1/4 SE 1/4**

Existing Pipeline


Utah Engineering & Land Surveying
85 South 200 East Vernal, Utah 84078
(435) 789-1017 * FAX (435) 789-1813

B

TOPO

**R
16
E**

**PROPOSED LOCATION:
PRICKLY PEAR UNIT FEDERAL #9-27D-12-16,
#15-27D-12-16, #10-27D-12-16 & #11-27D-12-16**



T12S

T13S

LEGEND:

- | | |
|-------------------|-------------------------|
| ○ DISPOSAL WELLS | ● WATER WELLS |
| ● PRODUCING WELLS | ● ABANDONED WELLS |
| ● SHUT IN WELLS | ● TEMPORARILY ABANDONED |



BILL BARRETT CORPORATION

**PRICKLY PEAR UNIT FEDERAL #9-27D-12-16,
#15-27D-12-16, #10-27D-12-16 & #11-27D-12-16
SECTION 27, T12S, R16E, S.L.B.&M.
SE 1/4 SE 1/4**



Uintah Engineering & Land Surveying
85 South 200 East Vernal, Utah 84078
(435) 789-1017 * FAX (435) 789-1813

TOPOGRAPHIC MAP
03 24 08
MONTH DAY YEAR
SCALE: 1"=2000' DRAWN BY: C.P. REVISED: 00-00-00



WORKSHEET
APPLICATION FOR PERMIT TO DRILL

APD RECEIVED: 04/29/2008

API NO. ASSIGNED: 43-007-31411

WELL NAME: PPU FED 9-27D-12-16

OPERATOR: BILL BARRETT CORP (N2165)

PHONE NUMBER: 303-312-8134

CONTACT: TRACEY FALLANG

PROPOSED LOCATION:

SESE 27 120S 160E

SURFACE: 1050 FSL 0790 FEL

NESE BOTTOM: 1963 FSL 0608 FEL

COUNTY: CARBON

LATITUDE: 39.74044 LONGITUDE: -110.1030

UTM SURF EASTINGS: 576859 NORTHINGS: 4399124

FIELD NAME: PETER'S POINT (40)

INSPECT LOCATN BY: / /		
Tech Review	Initials	Date
Engineering		
Geology		
Surface		

LEASE TYPE: 1 - Federal

LEASE NUMBER: UTU-08107

SURFACE OWNER: 1 - Federal

PROPOSED FORMATION: WSMVD

COALBED METHANE WELL? NO

RECEIVED AND/OR REVIEWED:

☒ Plat
☒ Bond: Fed[1] Ind[] Sta[] Fee[]
(No. WYB000040)
☒ Potash (Y/N)
☒ Oil Shale 190-5 (B) or 190-3 or 190-13
☒ Water Permit
(No. 90-1853)
☒ RDCC Review (Y/N)
(Date:)
☒ Fee Surf Agreement (Y/N)
☒ Intent to Commingle (Y/N)

LOCATION AND SITING:


____ R649-2-3.
Unit: PETERS POINT *OK*
____ R649-3-2. General
Siting: 460 From Qtr/Qtr & 920' Between Wells
____ R649-3-3. Exception
☒ Drilling Unit
Board Cause No: 157-03
Eff Date: 5-29-2001
Siting: *PHL must be at least 400' fr cont bdr.*
☒ R649-3-11. Directional Drill

COMMENTS: _____

STIPULATIONS: *1- Federal Approval*

22

23



PREPARED BY: DIANA MASON
DATE: 01-MAY-2008



JON M. HUNTSMAN, JR.
Governor

GARY R. HERBERT
Lieutenant Governor

State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER
Executive Director

Division of Oil, Gas and Mining

JOHN R. BAZA
Division Director

May 5, 2008

Bill Barrett Corporation
1099 18th St., Ste. 2300
Denver, CO 80202

Re: Peter's Point Unit Federal 9-27D-12-16 Well, Surface Location 1050' FSL, 790' FEL, SE SE, Sec. 27, T. 12 South, R. 16 East, Bottom Location 1963' FSL, 608' FEL, NE SE, Sec. 27, T. 12 South, R. 16 East, Carbon County, Utah

Gentlemen:

Pursuant to the provisions and requirements of Utah Code Ann. § 40-6-1 *et seq.*, Utah Administrative Code R649-3-1 *et seq.*, and the attached Conditions of Approval, approval to drill the referenced well is granted.

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date. The API identification number assigned to this well is 43-007-31411.

Sincerely,

Gil Hunt
Associate Director

pab
Enclosures

cc: Carbon County Assessor
Bureau of Land Management, Moab Office

Operator: Bill Barrett Corporation
Well Name & Number Peter's Point Unit Federal 9-27D-12-16
API Number: 43-007-31411
Lease: UTU-08107

Surface Location: SE SE **Sec.** 27 **T.** 12 South **R.** 16 East
Bottom Location: NE SE **Sec.** 27 **T.** 12 South **R.** 16 East

Conditions of Approval

1. General

Compliance with the requirements of Utah Admin. R. 649-1 *et seq.*, the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

2. Notification Requirements

Notify the Division within 24 hours of spudding the well.

- Contact Carol Daniels at (801) 538-5284

Notify the Division prior to commencing operations to plug and abandon the well.

- Contact Dustin Doucet at (801) 538-5281 (801) 733-0983 home

3. Reporting Requirements

All required reports, forms and submittals will be promptly filed with the Division, including but not limited to the Entity Action Form (Form 6), Report of Water Encountered During Drilling (Form 7), Weekly Progress Reports for drilling and completion operations, and Sundry Notices and Reports on Wells requesting approval of change of plans or other operational actions.

4. State approval of this well does not supersede the required federal approval, which must be obtained prior to drilling.

5. In accordance with Utah Admin. R.649-3-11, Directional Drilling, the operator shall submit a complete angular deviation and directional survey report to the Division within 30 days following completion of the well.

CONFIDENTIAL

COPY
 FOR APPROVAL
 BY THE BLM
 Expires June 1, 2010

Form 3160-3
 (August 2007)
 MOAD FIELD OFFICE

2008 APR 29 3:12

UNITED STATES
 DEPARTMENT OF THE INTERIOR
 BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. UTU-08107
1b. Type of Well: <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> Single Zone <input checked="" type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name N/A
2. Name of Operator Bill Barrett Corporation		7. If Unit or CA Agreement, Name and No. Peters Point / UTU-63014
3a. Address 1099 18th Street, Suite 2300 Denver, CO 80202		8. Lease Name and Well No. Peter's Point Unit Federal 9-27D-12-16
3b. Phone No. (include area code) 303-312-8134		9. API Well No. pending 4300731411
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface SESE, 1050' FSL, 790' FEL At proposed prod. zone NESE, 1963' FSL, 608' FEL, Sec. 27		10. Field and Pool, or Exploratory Peter's Point/Wasatch-Mesaverde
14. Distance in miles and direction from nearest town or post office* approximately 50 miles from Myton, Utah		11. Sec., T. R. M. or Blk. and Survey or Area Sec. 27, T12S-R16E
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig, unit line, if any) 790' SH / 608' BH	16. No. of acres in lease 640	12. County or Parish Carbon County
17. Spacing Unit dedicated to this well 40 acres	13. State UT	
18. Distance from proposed* location to nearest well, drilling, completed, applied for, on this lease, ft. 16' SH / 910' BH	19. Proposed Depth 7900' MD	20. BLM/BIA Bond No. on file Nationwide Bond #WYB000040
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 7196' graded ground	22. Approximate date work will start* 10/01/2008	23. Estimated duration 45 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- | | |
|--|---|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the BLM. |

25. Signature <i>Tracey Fallang</i>	Name (Printed/Typed) Tracey Fallang	Date 4/28/08
Title Environmental/Regulatory Analyst		
Approved by (Signature) <i>Steve Rigby</i>	Name (Printed/Typed) Steve Rigby	Date 10-21-08
Title AFM - Acting	Office PFO	

Application approval does not warrant or certify that the applicant holds legal or equitable title to these rights in the subject lease which would entitle the applicant to conduct operations thereon.
 Conditions of approval, if any, are attached.

CONDITIONS OF APPROVAL ATTACHED

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

*(Instructions on page 2)

NOTICE OF APPROVAL


RECEIVED

OCT 27 2008

DIV. OF OIL, GAS & MINING
UDOGM

T12S, R16E, S.L.B.&M.

N89°55'W - 5287.92' (G.L.O.)



DISTANCE TABLE			
FROM	TO	BEARING	DISTANCE
#9-27D-12-16	#18-27-12-16	S38°58'26\"W	18.18'

PETERS POINT UNIT FEDERAL
#9-27D-12-16
Elev. Graded Ground = 7196'

BILL BARRETT CORPORATION


Well location, PETERS POINT UNIT FEDERAL
#9-27D-12-16, located as shown in the
SE 1/4 SE 1/4 of Section 27, T12S, R16E,
S.L.B.&M., Carbon County, Utah.

BASIS OF ELEVATION

COTTON TRIANGULATION STATION LOCATED IN THE NW 1/4 OF
SECTION 31, T12S, R16E, S.L.B.&M., TAKEN FROM THE TWIN
HOLLOW QUADRANGLE, UTAH, CARBON COUNTY, 7.5 MINUTE
SERIES (TOPOGRAPHICAL MAP) PUBLISHED BY THE UNITED
STATES DEPARTMENT OF THE INTERIOR, GEOLOGICAL SURVEY.
SAID ELEVATION IS MARKED AS BEING 7386 FEET.


BASIS OF BEARINGS

BASIS OF BEARINGS IS A G.P.S. OBSERVATION.



CERTIFICATE

THIS IS TO CERTIFY THAT THE ABOVE IS A PREPARED FROM
FIELD NOTES OF ACTUAL SURVEYS BY ME OR UNDER MY
SUPERVISION AND THAT THE SAME ARE TRUE AND CORRECT TO THE
BEST OF MY KNOWLEDGE AND BELIEF.



1909 Brass Cap
2.5' High, Pile
of Stones, Bearing
Tree

UINTAH ENGINEERING & LAND SURVEYING
85 SOUTH 200 EAST - VERNAL, UTAH 84078
(435) 789-1017

LEGEND:

- = 90° SYMBOL
- = PROPOSED WELL HEAD.
- ▲ = SECTION CORNERS LOCATED.

NAD 83 (TARGET BOTTOM HOLE)	NAD 83 (SURFACE LOCATION)
LATITUDE = 39°44'35.07" (39.743075)	LATITUDE = 39°44'26.05" (39.740569)
LONGITUDE = 110°06'11.23" (110.103119)	LONGITUDE = 110°06'13.58" (110.103772)
NAD 27 (TARGET BOTTOM HOLE)	NAD 27 (SURFACE LOCATION)
LATITUDE = 39°44'35.20" (39.743111)	LATITUDE = 39°44'26.18" (39.740608)
LONGITUDE = 110°06'08.68" (110.102411)	LONGITUDE = 110°06'11.03" (110.103064)
STATE PLANE NAD 27 (UTAH CENTRAL)	STATE PLANE NAD 27 (UTAH CENTRAL)
N: 516547.52 E: 2392971.04	N: 515831.99 E: 2392801.51

SCALE 1" = 1000'	DATE SURVEYED: 03-11-08	DATE DRAWN: 03-18-08
PARTY D.R. A.W. C.G.	REFERENCES G.L.O. PLAT	
WEATHER COOL	FILE BILL BARRETT CORPORATION	



UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
PRICE FIELD OFFICE

125 SOUTH 600 WEST

PRICE, UT 84501

(435) 636-3600



CONDITIONS OF APPROVAL FOR APPLICATION FOR PERMIT TO DRILL

Company:	Bill Barrett Corporation	Location:	SESE-Sec. 27-T12S-R16E
Well No:	Peters Point Unit Federal 9-27D-12-16	Lease No:	UTU-08107
API No:	43-007-31411	Agreement:	Peters Point (UTU-63014)

Title	Name	Office Phone Number	Cell Phone Number
Acting Field Manager & Authorized Officer:	Michael Stiewig	(435) 636-3633	(435) 650-9135
Senior Petroleum Engineer:	Matthew Baker	(435) 781-4490	(435) 828-4470
Petroleum Engineer:	Ryan Angus (Alt.)	(435) 781-4430	(435) 828-7368
Petroleum Engineering Technician	Walton Willis (Primary)	(435) 636-3662	(435) 650-9140
Petroleum Engineering Technician	Randy Knight (Alt.)	(435) 636-3615	(435) 650-9143
NRS/Enviro Scientist:	Don Stephens	(435) 636-3608	

Fax: (435) 636-3657

**A COPY OF THESE CONDITIONS SHALL BE FURNISHED TO YOUR
FIELD REPRESENTATIVE TO INSURE COMPLIANCE**

All lease and/or unit operations are to be conducted in such a manner that full compliance is made with the applicable laws, regulations (43 CFR Part 3160), and this approved Application for Permit to Drill including Surface and Downhole Conditions of Approval. The operator is considered fully responsible for the actions of his subcontractors. A copy of the approved APD must be on location during construction, drilling, and completion operations. **This permit is approved for a two (2) year period, or until lease expiration, whichever occurs first. An additional extension, up to two (2) years, may be applied for by sundry notice prior to expiration.**

NOTIFICATION REQUIREMENTS

Location Construction (Notify NRS)	- Forty-Eight (48) hours prior to construction of location and access roads.
Location Completion (Notify NRS)	- Prior to moving on the drilling rig.
Spud Notice (Notify Petroleum Engineer)	- Twenty-Four (24) hours prior to spudding the well.
Casing String & Cementing (Notify Petroleum Tech.)	- Twenty-Four (24) hours prior to running casing and cementing all casing strings.
BOP & Related Equipment Tests (Notify Petroleum Tech.)	- Twenty-Four (24) hours prior to initiating pressure tests.
First Production Notice (Notify Petroleum Engineer)	- Within Five (5) business days after new well begins or production resumes after well has been off production for more than ninety (90) days.

SURFACE USE PROGRAM CONDITIONS OF APPROVAL (COAs)

SITE SPECIFIC COAs:

- A pre-construction field meeting may be conducted prior to beginning any dirt work approved under this APD. The operator shall contact the BLM Representative Don Stephens at 435-636-3608 at least 48-hours prior to beginning operations so that the meeting can be scheduled. The operator is responsible for having all contractors present (dirt contractors, drilling contractor, pipeline contractor, project oversight personnel, etc.) including the overall field operations superintendent, and for providing all contractors copies of the approved APD(s), project map and BLM Conditions of Approval pertinent to the work that each will be doing.
- The following appendices are attached for your reference. They are to be followed as conditions of approval:
 - SM-A, Seed Mixture for Berms, Topsoil Piles, Pad Margins
 - SM-B, Seed Mixture for Final Reclamation (buried pipelines, abandoned pads, roads, etc.)
 - TMC1, Browse Hand Planting Tubeling Mixtures
 - Applicant-committed environmental protection measures, see attached Appendix B
 - Lease Stipulations, see attached Table 2.3 from EA for West Tavaputs Plateau Drilling Program.
- The company shall furnish and apply water or other means satisfactory to the Authorized Officer for dust control. Dust is controlled when the following standards are met: (1) no dust is generated above the cab of the vehicle, or (2) no hanging dust plumes. These standards are applicable to Nine Mile Canyon between Harmon and Cottonwood Canyons, and in Harmon and Cottonwood Canyons. If dust exceeds these standards, operations shall be shut down until the standards are met.
- The company shall supply a third party monitor to report directly to the BLM which shall monitor for dust on a daily basis as necessary. A written monitoring report shall be submitted to the BLM on a weekly basis, and a phone report shall be made to the authorized officer on a daily basis as necessary. If dust control standards are not met, operations shall be shut down.
- The company shall submit interim reclamation plans and location layout with proposed interim reclaimed areas to the authorized office within 90 days of the spudding of the well.
- The area that encompasses the well location and road is environmentally sensitive including fragile soils and vegetation. The operator may be required to perform special measures such as mulching, erosion fencing, use of erosion fabric, etc. per the direction of the BLM Authorized Officer to stabilize any disturbed areas and ensure the reestablishment of long-term perennial vegetation.
- The operator will be responsible for performing any remediation and/or necessary road upgrading (e.g. elevating, surfacing, culverts, low-water crossings, water-wings, surfacing, etc.) as directed by the BLM Authorized Officer, resulting from untimely access.
- All equipment and personnel used during drilling and construction activities will be restricted to only approved access roads.
- If the well is productive and after completion operations, the road will be upgraded to a **Resource Road** status in accordance with the *Surface Operating Standards for Oil & Gas Exploration and Development*, Fourth Edition and/or BLM Manual Section 9113 concerning road construction standards on projects subject to federal jurisdiction.
- All permanent above-ground structures (e.g., production equipment, tanks, etc.) not subject to safety requirements will be painted to blend with the natural color of the landscape. The paint used will be a color which simulates "Standard Environmental Colors." The color selected for the Peters Point Unit Federal 9-27D-12-16 well is Olive Black, 5WA20-6. All facilities will be painted the designated color at the time of installation.
- All trees salvaged from the construction of the well pad will be clearly segregated from the spoil material, to prevent burying of trees in the spoil material.
- No salvaged trees will be pushed up against live trees or buried in the spoil material.
- All areas not needed for production of the well will be reclaimed within 90 days of completion of the last well if weather conditions are favorable, unless the BLM Authorized Officer gives an extension.

- Reserve pits will be closed as soon as possible, but no later than 90 days from time of drilling/well completion, unless the BLM Authorized Officer gives an extension. Squeezing of pit fluids and cuttings is prohibited. Pits must be dry of fluids or they must be removed via vac-truck or other environmentally acceptable method prior to backfilling, re-contouring and replacement of topsoil. Mud and cuttings left in pit must be buried at least 3-feet below re-contoured grade. The operator will be responsible for re-contouring any subsidence areas that develop from closing a pit before it is sufficiently dry.
- The operator will drill seed on the contour to a depth of 0.5 inch, followed by cultipaction to compact the seedbed, preventing soil and seed losses. To maintain quality and purity, the current years tested, certified seed with a minimum germination rate of 80% and a minimum purity of 90% will be used.
- Please contact Don Stephens, Natural Resource Specialist, (435) 636-3608, Bureau of Land Management, Price Field Office, if there are any questions concerning these surface use COAs.
- A Paleontologist acceptable to the BLM will monitor during surface disturbing activities. If paleontologic resources are uncovered during surface disturbing activities, the paleontologist shall immediately notify the Authorized Officer (AO). The AO will arrange for a determination of significance and, if necessary, recommend a recovery or avoidance plan.
- The pipeline(s) shall be buried.
- During the activities of road maintenance, new road construction or the construction of well pads, if any standing live or dead trees are damaged, cut down or knocked over by grading or construction equipment, actions would be taken to remove excessive vegetation from the road or pad edge.
- An impermeable liner shall be used in the containment area of all permanent condensate and water tanks.
- Gas shall be measured on the well pad unless the BLM Authorized Officer authorizes another location.
- If the well has not been spudded by APD Approval date + 2 years the APD will expire and the operator is to cease all operations related to preparing to drill the well.
- The Mexican Spotted Owl Conservation Measures to avoid impacts:
 - Employ best available technology on production wells and compression equipment within .5 miles of canyon habitat model.
 - Upon discovery of individuals or sightings of this species, halt construction/drilling activities and notify authorized official.
- Centralize tanks and facilities with old wells.
- Leave trees on the edge of the well site.
- The operator shall contact the BLM Authorized Officer or Don Stephens @ 435-636-3608 at least 48-hours prior to the filling and reclamation of pits.

Winter Conditions of Approval

- To prevent erosion, snow must be removed within 48-hours of cessation of each winter storm producing greater than 4-inches of snowfall; snow removal would occur only on those roads necessary to access wells and production facilities.
- On well pads where winter drilling is occurring, snow must be removed within 48-hours of cessation of each winter storm producing greater than 4-inches of snowfall; snow removal would occur on the portions of the pad where access with snow removal equipment is feasible. Snow would be stockpiled in a retention structure per The Gold Book standards.
- To reduce erosion and soil loss during heavy rain events and snow melt, drainage on or around the well pads would be designed to reduce erosion and sedimentation. Storm water would be diverted away from the well locations with ditches, berms, or waterbars above the cut slopes. Rain water or snow melt collected on the well pads would be contained and drained into the reserve pit or directed into a water retention ponds to ensure no sediment leaves the pad.
- The following travel restrictions would be adhered to by all types of vehicles from November 1, 2008, to May 15, 2009, to minimize disturbances during periods of major animal movement (6:00-8:00 AM and 5:00-7:00 PM or 6:00-8:00 AM and 6:00-8:00 PM during daylight savings time). These restrictions would be contingent on the presence of elk and deer in the areas.

- Contractors and vendors for non-critical rig visits would not travel during these periods.
- Rig shift changes would be adjusted to not coincide with these periods.
- Routine delivery of drilling supplies would not occur during these periods.

These restrictions would not apply to vehicles directly involved in casing, cementing and/or emergency operations necessary to maintain viable hole conditions.

- Monitoring would be required to ensure compliance with restricted travel times and routes from November 1, 2008, to May 15, 2009. The proponent would contract with a third party monitor to assess compliance with these restrictions. Monitoring would occur at least twice weekly at random intervals and a compliance report would be submitted to the Price Field Office on a weekly basis. *Bill Barrett Corporation 2007-2008 Prickly Pear Unit Winter Drilling EA 2-17.*
- If snow depths equal 16-inches or greater, edges of plowed roads would be opened at intervals of approximately 0.25 mi to create wildlife exit points and crossing areas when snow walls develop. Exits would be opened to approximately 15 ft, down to the top of vegetation, and would remain within the ROW.
- Access roads must meet The Gold Book standards, where practicable, prior to the winter closure to ensure ruts would not be created during winter use.
- All pipelines associated with wells would be buried within the 50-ft pipeline ROW. BBC could request a waiver if surface conditions are such that blasting would be required to bury the pipeline.
- Trucks used for moving rigs would be kept on top of each applicable mesa until the rig has been fully moved.
- As feasible, all supplies, including casing, would be stockpiled on top of each applicable mesa prior to the winter closure.

SURFACE USE COAs:

- If any cultural values [sites, artifacts, human remains] are observed during operation of this lease/permit/right-of-way, they will be left intact and the Price Field Manager notified. The authorized officer will conduct an evaluation of the cultural values to establish appropriate mitigation, salvage or treatment. The operator is responsible for informing all persons in the area who are associated with this project that they will be subject to prosecution for knowingly disturbing historic or archaeological sites, or for collecting artifacts. If historic or archaeological materials are uncovered during construction, the operator is to immediately stop work that might further disturb such materials, and contact the authorized BLM officer (AO). Within five working days the AO will inform the operator as to:
 - whether the materials appear eligible for the National Register of Historic Places;
 - the mitigation measures the operator will likely have to undertake before the site can be used (assuming in situ preservation is not necessary); and,
 - a time-frame for the AO to complete an expedited review under 36 CFR 800.11 to confirm, through the State Historic Preservation Officer, that the findings of the AO are correct and that mitigation is appropriate. The AO will provide technical and procedural guidelines for the conduct of mitigation. Upon verification from the AO that the required mitigation has been completed, the operator will then be allowed to resume construction measures.
- The operator shall restrict travel on unimproved roads during periods of inclement weather or spring thaw when the possibility exists for excessive surface resource damage (e.g., rutting in excess of 4-inches, travel outside roadway, etc.).
- The Companies will provide georeferenced spatial data depicting as-built locations of all facilities, wells, roads, pipelines, power lines, and other related facilities to the BLM by November 1 of each year until completion of project construction activities has occurred.
- If any dead or injured threatened, endangered, proposed, or candidate species is located during construction or operation, the BLM Price Field Office (435-636-3600) shall be notified within 24 hours.
- The Company will conduct clearance surveys for threatened, endangered or other special-concern species at the optimum time. This will require coordination with the BLM before November 1 annually to review the potential for disturbance and to agree on inventory parameters.

Construction

- The operator will limit vegetation removal and the degree of surface disturbance wherever possible. Where surface disturbance cannot be avoided, all practicable measures will be utilized to minimize erosion and stabilize disturbed soils.
- Construction and drilling activity will not be conducted using frozen or saturated soil material during periods when watershed damage or excessive rutting is likely to occur.
- Remove all available topsoil from constructed well locations including areas of cut and fill, and stockpile at the site. Topsoil will also be salvaged for use in reclamation on all other areas of surface disturbance (roads, pipelines, etc.). Clearly segregate topsoil from excess spoil material. Any topsoil stockpiled for one year or longer will be signed and stabilized with annual ryegrass or other suitable cover crop.
- The operator will not push soil material and overburden over side slopes or into drainages. All soil material disturbed will be placed in an area where it can be retrieved without creating additional undue surface disturbance and where it does not impede watershed and drainage flows.
- Construct the backslope no steeper than 1½:1, and construct the foreslope no steeper than 2:1, unless otherwise directed by the BLM Authorized Officer.
- Maintain a minimum 20-foot undisturbed vegetative border between toe-of-fill of pad and/or pit areas and the edge of adjacent drainages, unless otherwise directed by the BLM Authorized Officer.
- With the overall objective of minimizing surface disturbance and retaining land stability and productivity, the operator shall utilize equipment that is appropriate to the scope and scale of work being done for roads and well pads (utilize equipment no larger than needed for the job).
- Reserve pits will be adequately fenced during and after drilling operations until pit is reclaimed so as to effectively keep out wildlife and livestock. Adequate fencing, in lieu of more stringent requirements by the surface owner, is defined as follows:
- Construction materials will consist of steel or wood posts. Three or four strand wire (smooth or barbed) fence or hog panel (16-foot length by 50-inch height) or plastic snow fence must be used with connectors such as fence staples, quick-connect clips, hog rings, hose clamps, twisted wire, etc. Electric fences will not be allowed.
- Construction standards: Posts shall be firmly set in ground. If wire is used, it must be taut and evenly spaced, from ground level to top wire, to effectively keep out animals. Hog panels must be tied securely into posts and one another using fence staples, clamps, etc. Plastic snow fencing must be taut and sturdy. Fence must be at least 2-feet from edge of pit. 3 sides fenced before beginning drilling, the fourth side fenced immediately upon completion of drilling and prior to rig release. Fence must be left up and maintained in adequate condition until pit is closed.
- The reserve pit will be oriented to prevent collection of surface runoff. After the drilling rig is removed, the operator may need to construct a trench on the uphill side of the reserve pit to divert surface drainage around it. If constructed, the trench will be left intact until the pit is closed.
- The reserve pit will be lined with an impermeable liner if permeable subsurface material is encountered. An impermeable liner is any liner having a permeability of less than 10^{-7} cm/sec. The liner will be installed so that it will not leak and will be chemically compatible with all substances that may be put in the pit. Liners made of any man-made synthetic material will be of sufficient strength and thickness to withstand normal installation and pit use. In gravelly or rocky soils, a suitable bedding material such as sand will be used prior to installing the liner.
- The reserve pit will be constructed so that at least half of its total volume is in solid cut material (below natural ground level).
- The reserve pit shall have 2 foot of freeboard maintained at all times to prevent overflow of fluids.
- Culverts will be placed on channel bottoms on firm, uniform beds, which have been shaped to accept them, and aligned parallel to the channel to minimize erosion. Backfill will be thoroughly compacted.
- The minimum diameter for culverts will be 18 inches. However, all culverts will be appropriately sized in accordance with standards in BLM Manual 9113.
- Construction and other project-related traffic will be restricted to approved routes. Cross-country vehicle travel will not be allowed.
- Maximum design speed on all operator-constructed and maintained roads will not exceed 25 miles per hour.

- Pipeline construction shall not block nor change the natural course of any drainage. Pipelines shall cross perpendicular to drainages. Pipelines shall not be run parallel in drainage bottoms. Suspended pipelines shall provide adequate clearance for maximum runoff.
- Pipeline trenches shall be compacted during backfilling. Pipeline trenches shall be routinely inspected and maintained to ensure proper settling, stabilization and reclamation.
- The pipeline right-of-way will be brush-hogged to prevent unnecessary disturbance. Only those areas where safety, absolute need for construction or other regulations may warrant the use of topsoil removal by blading or scalping.
- During construction, emissions of particulate matter from well pad and road construction would be minimized by application of water or other non-saline dust suppressants with at least 50 percent control efficiency. Dust inhibitors (surfacing materials, non-saline dust suppressants, and water) will be used as necessary on unpaved roads that present a fugitive dust problem. The use of chemical dust suppressants on public surface will require prior approval from the BLM Authorized Officer.
- The operator shall submit a Sundry Notice (Form 3160-5) to BLM for approval prior to construction of any new surface disturbing activities that are not specifically addressed in the approved APD.

Operations/Maintenance

- If in the process of air drilling the wells there is a need to utilize mud, all circulating fluids will be contained either in an approved pit or in an aboveground containment tank. The pit or containment tank will be large enough to safely contain the capacity of all expected fluids without danger of overflow. Fluid and cuttings will not be squeezed out of the pit, and the pit will be reclaimed in an expedient manner.
- Confine all equipment and vehicles to the access road(s), pad(s), and area(s) specified in the approved APD.
- All waste, other than human waste and drilling fluids, will be contained in a portable trash cage. This waste will be transported to a State approved waste disposal site immediately upon completion of drilling operations. No trash or empty barrels will be placed in the reserve pit or buried on location. All state and local laws and regulations pertaining to disposal of human and solid waste will be complied with.
- Rat and mouse holes shall be filled and compacted from the bottom to the top immediately upon release of the drilling rig from the location.
- The operator will be responsible for prevention and control of noxious weeds and weeds of concern on all areas of surface disturbance associated with this project (well locations, roads, water management facilities, etc.) Use of pesticides shall comply with the applicable Federal and State laws. Pesticides shall be used only in accordance with their registered uses and within limitations imposed by the Secretary of Interior. Prior to the use of pesticides on public land, the holder shall obtain from the BLM authorized officer written approval of a plan showing the type and quantity of material to be used, pest(s) to be controlled, method of application, location of storage and disposal of containers, and any other information deemed necessary by the authorized officer to such use.
- Sewage shall be placed in a self-contained, chemically treated porta-potty on location.
- The operator and their contractors shall ensure that all use, production, storage, transport and disposal of hazardous and extremely hazardous materials associated with the drilling, completion and production of these wells will be in accordance with all applicable existing or hereafter promulgated federal, state and local government rules, regulations and guidelines. All project-related activities involving hazardous materials will be conducted in a manner to minimize potential environmental impacts. In accordance with OSHA requirements, a file will be maintained onsite containing current Material Safety Data Sheets (MSDS) for all chemicals, compounds and/or substances which are used in the course of construction, drilling, completion and production operations.
- Produced fluids shall be put in test tanks on location during completion work. Produced water will be put in the reserve pit during completion work per Onshore Order #7.
- The only fluids/waste materials which are authorized to go into the reserve pit are RCRA exempt exploration and production wastes. These include:
 - drilling muds & cuttings
 - rigwash

- excess cement and certain completion & stimulation fluids defined by EPA as exempt
- It does not include drilling rig waste, such as:
 - spent hydraulic fluids
 - used engine oil
 - used oil filter
 - empty cement, drilling mud, or other product sacks
 - empty paint, pipe dope, chemical or other product containers
 - excess chemicals or chemical rinsate
- Any evidence of non-exempt wastes being put into the reserve pit may result in the BLM Authorized Officer requiring specific testing and closure requirements.
- If this well is drilled during the fire season (June-October), the operator shall institute all necessary precautions to ensure that fire hazard is minimized, including but not limited to mowing vegetation on the access route(s) and well location(s), keeping fire fighting equipment readily available when drilling, etc.

Dry Hole/Reclamation

- All disturbed lands associated with this project, including the pipelines, access roads, water management facilities, etc will be expediently reclaimed and reseeded in accordance with the surface use plan and any pertinent site-specific COAs.
- Disturbed lands will be re-contoured back to conform with existing undisturbed topography. No depressions will be left that trap water or form ponds.
- Before the location has been reshaped and prior to redistributing the topsoil, the operator will rip or scarify the drilling platform and access road on the contour, to a depth of at least 12 inches. The rippers are to be no farther than 24 inches apart.
- Distribute the topsoil evenly over the entire location and other disturbed areas. Prepare the seedbed by disking to a depth of 4-to-6 inches following the contour.
- Phased reclamation plans will be submitted to BLM for approval prior to individual POD facility abandonment via a Notice of Intent (NOI) Sundry Notice. Individual facilities, such as well locations, pipelines, discharge points, impoundments, etc. need to be addressed in these plans as they are no longer needed. Individual items that will need to be addressed in reclamation plans include:
- Pit closure (Close ASAP after suitably dry, but no later than 90 days from time of drilling unless an extension is given by BLM Authorized Officer.) BLM may require closure prior to 90 days in some cases due to land use or environmental concerns.
- Configuration of reshaped topography, drainage systems, and other surface manipulations
- Waste disposal
- Revegetation methods, including specific seed mix (pounds pure live seed/acre) and soil treatments (seedbed preparation, fertilization, mulching, etc.). On private surface, the landowner should be consulted for the specific seed mix.
- Other practices that will be used to reclaim and stabilize all disturbed areas, such as water bars, erosion fabric, hydro-mulching, etc.
- An estimate of the timetables for beginning and completing various reclamation operations relative to weather and local land uses.
- Methods and measures that will be used to control noxious weeds, addressing both ingress and egress to the individual well or POD.
- Decommissioning/removal of all surface facilities
- BLM will not release the performance bond until all disturbed areas associated with the APD/POD have been successfully revegetated (evaluation will be made after the second complete growing season) and has met all other reclamation goals of the surface owner and surface management agency.
- A Notice of Intent to Abandon and a Subsequent Report of Abandonment must be submitted for abandonment approval.
- For performance bond release approval, a Final Abandonment Notice (with a surface owner release letter on split-estate) must be submitted prior to a final abandonment evaluation by BLM.

- Soil fertility testing and the addition of soil amendments may be required to stabilize some disturbed lands.
- Any mulch utilized for reclamation needs to be certified weed free.
- Waterbars are to be constructed at least one (1) foot deep, on the contour with approximately two (2) feet of drop per 100 feet of waterbar to ensure drainage, and extended into established vegetation. All waterbars are to be constructed with the berm on the downhill side to prevent the soft material from silting in the trench. The initial waterbar should be constructed at the top of the backslope. Subsequent waterbars should follow the following general spacing guidelines:

<u>Slope (percent)</u>	<u>Spacing Interval (feet)</u>
≤ 2	200
2 – 4	100
4 – 5	75
≥ 5	50

Producing Well

- Reclaim those areas not required for production as soon as possible. The fluids and mud must be dry in the reserve pit before re-contouring pit area. The operator will be responsible for re-contouring and reseeding of any subsidence areas that develop from closing a pit before it is completely dry.
- Reduce the backslope to 2:1 and the foreslope to 3:1, unless otherwise directed by the BLM Authorized Officer. Reduce slopes by pulling fill material up from foreslope into the toe of cut slopes.
- Production facilities (including dikes) must be placed on the cut portion of the location and a minimum of 15 feet from the toe of the back cut unless otherwise approved by the BLM Authorized Officer.
- Any spilled or leaked oil, produced water or treatment chemicals must be reported in accordance with NTL-3A and immediately cleaned up in accordance with BLM requirements. This includes clean-up and proper disposition of soils contaminated as a result of such spills/leaks.
- Distribute stockpiled topsoil evenly over those areas not required for production and reseed as recommended.
- Upgrade and maintain access roads and drainage control (e.g., culverts, drainage dips, ditching, crowning, surfacing, etc.) as necessary and as directed by the BLM Authorized Officer to prevent soil erosion and accommodate safe, environmentally-sound access.
- Prior to construction of production facilities not specifically addressed in the APD, the operator shall submit a Sundry Notice to the BLM Authorized Officer for approval.
- If not already required prior to constructing and drilling the well location, the operator shall immediately upgrade the entire access road to BLM standards (including topsoiling, crowning, ditching, drainage culverts, surfacing, etc.) to ensure safe, environmentally-sound, year-round access. Waterbars shall be installed on all reclaimed pipeline corridors per the guidelines in D #11.

Seed Mix A¹

Temporary Disturbance (for berms, topsoil piles, pad margins)

Forbes Lbs

Yellow Sweetclover	2.0 lbs/acre
Ladak Alfalfa	2.0 lbs/acre
Cicer Milkvetch	1.0 lbs/acre
Palmer Penstemon	0.5 lbs/acre

Grasses Lbs

Crested Wheatgrass	2.0 lbs/acre
Great Basin Wildrye	2.0 lbs/acre
Intermediate Wheatgrass	2.0 lbs/acre

Total

11.5 lbs/acre

1 Seed mix A is designed for rapid establishment, soil holding ability, and nitrogen fixing capability.
C-4 EA, West Tavaputs Plateau Drilling Program

Seed Mix B

Final Reclamation (for buried pipe lines, abandoned pads, road, etc.)

Forbes Lbs

Palmer Penstemon	0.5 lbs/acre
Golden Cryptantha	0.25 lbs/acre
Utah Sweetvetch	0.5 lbs/acre
Yellow Sweetclover ¹	2.0 lbs/acre
Lewis Flax	1.0 lbs/acre

Grasses Lbs

Indian Ricegrass	1.0 lbs/acre
Needle & Thread Grass	1.0 lbs/acre
Intermediate Wheatgrass	2.0 lbs/acre
Blue Grama	0.5 lbs/acre
Galletta	0.5 lbs/acre
Great Basin Wildrye	2.0 lbs/acre

Woody Plants Lbs

Fourwing Saltbush	2.0 lbs/acre
Winterfat	0.5 lbs/acre
Wyoming Big Sage brush	0.25 lbs/acre
Utah Serviceberry	1.0 lbs/acre
Blue Elderberry (Raw Seeds)	1.0 lbs/acre

Total	16.0 lbs/acre
--------------	----------------------

1 Yellow Sweetclover is planted as a nurse crop to provide solar protection, soil binding and nitrogen fixing. It will normally be crowded out in 2 to 3 years.

TMC 1: Browse Hand Planting Tubeling Mixtures

One of the two browse species lists (checked below) are to be hand planted at the prescribed application rate and according to the following prescribed methods on areas that are undergoing long term reclamation. The would include all pipeline corridors, berm around edge of drill pads, miscellaneous disturbed areas associated with construction such as staging areas for equipment, sidecast on road cuts, along side upgraded or new roads up to and including borrow ditch and in the termination of redundant access roads being closed. This planting shall be completed in the first planting window following completion of construction and on all other disturbed areas upon final reclamation.

Planting Methods:

Planting shall be accomplished using a labor force with specific experience in landscape restoration,

hand planting methods and handling and care of browse tubling and or bareroot stock plants.

Browse plants to be utilized can be bareroot stock or tubling stock plants of 1 year old age class or greater.

Browse seedling protectors will be used to provide protection from browsing ungulates for two years. Seedling protectors will be of an open mesh rigid design that will break down when exposed to sunlight and that measures a minimum of 12 inches in length and 4 inches in diameter.

Planting shall be completed in the spring (March 1-April 1) and or fall (November 1-December 1) planting windows.

Browse plants shall be stored and handled in such a manner as to maintain viability, according to the type of browse stock being used.

Planting Species and Application Rate: ☐ Sagebrush-Grass ☒ Pinyon-Juniper

Species	Plants Per Acre	
	Sagebrush-Grass	Pinyon-Juniper
Wyoming Sagebrush (Gordon Creek)	100	50
Fourwing Saltbush (Utah seed source collected at or above 5,000 feet elevation)	100	50
True Mountain Mahogany (Utah seed source)	0	50
Antelope Bitterbrush (Utah seed source)	0	50
TOTAL	200	200
Suitable Substitutions:		
Utah Serviceberry	No	50
Winterfat	100	No

**DOWNHOLE PROGRAM
CONDITIONS OF APPROVAL (COAs)**

SITE SPECIFIC DOWNHOLE COAs:

- The proposed 3M BOP system is adequate for anticipated conditions. Installation, testing and operation of the system shall be in conformance with Onshore Oil and Gas Order No. 2.
- The proposal included a provision for using minor amounts of diesel in the drilling fluid system. Diesel may be added to the system only after cementing the surface casing into place.
- The proposal included options for using one of three different grades of production casing. Any of the three options may be used.
- A Cement Bond Log (CBL) shall be run in the production casing from the TD to the top of cement. A field copy of the CBL shall be submitted to the BLM Price Field Office for review.
- If logging reveals that the cementing objectives were not met, remedial cementing will be required.
- Locally, the Green River Formation is known to contain oil, gas, oil shale and tar sand deposits. However, the lateral occurrence, distribution and grade of the oil shale and tar sand deposits are not well defined. The operator shall pay particular attention to this section, and shall attempt to identify and describe any of these resources that may be penetrated. Any information obtained on these resources shall be included as part of the Well Completion Report.
- All other equipment for air/gas drilling shall meet specifications in Onshore Order #2, III. Requirements, E. Special Drilling Operations.

All provisions outlined in Onshore Oil & Gas Order #2 Drilling Operations shall be strictly adhered to. The following items are emphasized:

DRILLING/COMPLETION/PRODUCING OPERATING STANDARDS

- The spud date and time shall be reported orally to Price Field Office within 24 hours of spudding.
- Notify Price Field Office Petroleum Engineering Technician at least 24 hours in advance of casing cementing operations and BOPE & casing pressure tests.
- If air drilling operations are utilized, the requirements of Onshore Oil & Gas Order No. 2, Part III.E *Special Drilling Operations*, shall be implemented.
- Blowout prevention equipment (BOPE) shall remain in use until the well is completed or abandoned. Closing unit controls shall remain unobstructed and readily accessible at all times. Choke manifolds shall be located outside of the rig substructure.
- All BOPE components shall be inspected daily and those inspections shall be recorded in the daily drilling report. Components shall be operated and tested as required by Onshore Oil & Gas Order

No. 2 to insure good mechanical working order. All BOPE pressure tests shall be performed by a test pump with a chart recorder and **NOT** by the rig pumps. Test shall be reported in the driller's log.

- BOP drills shall be initially conducted by each drilling crew within 24 hours of drilling out from under the surface casing and weekly thereafter as specified in Onshore Oil & Gas Order No. 2.
- Casing pressure tests are required before drilling out from under all casing strings set and cemented in place.
- No aggressive/fresh hard-banded drill pipe shall be used within casing.
- **Cement baskets shall not be run on surface casing.**
- The operator must report all shows of water or water-bearing sands to the BLM. If flowing water is encountered it must be sampled, analyzed, and a copy of the analyses submitted to the BLM Price Field Office.
- The operator must report encounters of all non oil & gas mineral resources (such as Gilsonite, tar sands, oil shale, trona, etc.) to the Price Field Office, in writing, within 5 working days of each encounter. Each report shall include the well name/number, well location, date and depth (from KB or GL) of encounter, vertical footage of the encounter and, the name of the person making the report (along with a telephone number) should the BLM need to obtain additional information.
- A complete set of angular deviation and directional surveys of a directional well will be submitted to the Price BLM office engineer within 30 days of the completion of the well.
- While actively drilling, chronologic drilling progress reports shall be filed directly with the BLM, Price Field Office on a weekly basis in sundry, letter format or e-mail to the Petroleum Engineers until the well is completed.
- A cement bond log (CBL) will be run from the production casing shoe to the top of cement and shall be utilized to determine the bond quality for the production casing. Submit a field copy of the CBL to this office.
- The use of a flow conditioner in lieu of straightening vanes in the gas meter run cannot be approved with the information provided. This proposal is not consistent with the provisions of Onshore Oil & Gas Order No. 5, and as such, can only be considered for approval as a "variance" from Order No. 5. A written request for variance would identify the Order No. 5 requirement(s) from which the variance is being requested, and it would included supporting justification as to how the alternate method of measurement would meet or exceed the minimum standards established in Order No. 5. A variance request for the use of a flow conditioner would also include the make, model, dimensions, and description of use for the specific flow conditioner being proposed.
- **Please submit a copy of all other logs run on this well to the BLM Price Field Office.**
- There shall be no deviation from the proposed drilling, completion, and/or workover program as approved. Safe drilling and operating practices must be observed. Any changes in operation must have prior approval from the BLM Price Field Office.

OPERATING REQUIREMENT REMINDERS:

- All wells, whether drilling, producing, suspended, or abandoned, shall be identified in accordance with 43 CFR 3162.6. There shall be a sign or marker with the name of the operator, lease serial number, well number, and surveyed description of the well.
- In accordance with 43 CFR 3162.4-3, this well shall be reported on the "Monthly Report of Operations" (Oil and Gas Operations Report ((OGOR)) starting with the month in which operations commence and continue each month until the well is physically plugged and abandoned. This report shall be filed in duplicate, directly with the Minerals Management Service, P.O. Box 17110, Denver, Colorado 80217-0110, or call 1-800-525-7922 (303) 231-3650 for reporting information.
- Should the well be successfully completed for production, the BLM Price Field office must be notified when it is placed in a producing status. Such notification will be by written communication and must be received in this office by not later than the fifth business day following the date on which the well is placed on production. The notification shall provide, as a minimum, the following informational items:
 - Operator name, address, and telephone number.
 - Well name and number
 - Well location (¼¼, Sec., Twn, Rng, and P.M.).
 - Date well was placed in a producing status (date of first production for which royalty will be paid).
 - The nature of the well's production, (i.e., crude oil, or crude oil and casing head gas, or natural gas and entrained liquid hydrocarbons).
 - The Federal or Indian lease prefix and number on which the well is located; otherwise the non-Federal or non-Indian land category, i.e., State or private.
 - Unit agreement and/or participating area name and number, if applicable.
 - Communitization agreement number, if applicable.
- Any venting or flaring of gas shall be done in accordance with Notice to Lessees (NTL) 4A and needs prior approval from the BLM Price Field Office.
- All undesirable events (fires, accidents, blowouts, spills, discharges) as specified in NTL 3A will be reported to the BLM, Price Field Office. Major events, as defined in NTL3A, shall be reported verbally within 24 hours, followed by a written report within 15 days. "Other than Major Events" will be reported in writing within 15 days. "Minor Events" will be reported on the Monthly Report of Operations and Production.
- Whether the well is completed as a dry hole or as a producer, "Well Completion and Recompletion Report and Log" (BLM Form 3160-4) shall be submitted not later than 30 days after completion of the well or after completion of operations being performed, in accordance with 43 CFR 3162.4-1. Two copies of all logs run, core descriptions, and all other surveys or data obtained and compiled during the drilling, workover, and/or completion operations, shall be filed on BLM Form 3160-4. Submit with the well completion report a geologic report including, at a minimum, formation tops, and a summary and conclusions. Also include deviation surveys, sample descriptions, strip logs, core data, drill stem test data, and results of production tests if performed. Samples (cuttings, fluid, and/or gas) shall be submitted only when requested by the BLM, Price Field Office.
- All off-lease storage, off-lease measurement, or commingling on-lease or off-lease, shall have prior written approval from the BLM Price Field Office.
- Oil and gas meters shall be calibrated in place prior to any deliveries. The BLM Price Field Office Petroleum Engineers will be provided with a date and time for the initial meter calibration and all future meter proving schedules. A copy of the meter calibration reports shall be submitted to the BLM Price Field Office. All measurement facilities will conform to the API standards for liquid

hydrocarbons and the AGA standards for natural gas measurement. All measurement points shall be identified as the point of sale or allocation for royalty purposes.

- A schematic facilities diagram as required by Onshore Oil & Gas Order No. 3 shall be submitted to the BLM Price Field Office within 30 days of installation or first production, whichever occurs first. All site security regulations as specified in Onshore Oil & Gas Order No. 3 shall be adhered to. All product lines entering and leaving hydrocarbon storage tanks will be effectively sealed in accordance with Onshore Oil & Gas Order No. 3
- Any additional construction, reconstruction, or alterations of facilities, including roads, gathering lines, batteries, etc., which will result in the disturbance of new ground, shall require the filing of a suitable plan and need prior approval of the BLM Price Field Office. Emergency approval may be obtained orally, but such approval does not waive the written report requirement.
- No location shall be constructed or moved, no well shall be plugged, and no drilling or workover equipment shall be removed from a well to be placed in a suspended status without prior approval of the BLM Price Field Office. If operations are to be suspended for more than 30 days, prior approval of the BLM Price Field Office shall be obtained and notification given before resumption of operations.
- Pursuant to Onshore Oil & Gas Order No. 7, this is authorization for pit disposal of water produced from this well for a period of 90 days from the date of initial production. A permanent disposal method must be approved by this office and in operation prior to the end of this 90-day period. In order to meet this deadline, an application for the proposed permanent disposal method shall be submitted along with any necessary water analyses, as soon as possible, but no later than 45 days after the date of first production. Any method of disposal which has not been approved prior to the end of the authorized 90-day period will be considered as an Incident of Noncompliance and will be grounds for issuing a shut-in order until an acceptable manner for disposing of said water is provided and approved by this office.
- Unless the plugging is to take place immediately upon receipt of oral approval, the Field Office Petroleum Engineers must be notified at least 24 hours in advance of the plugging of the well, in order that a representative may witness plugging operations. If a well is suspended or abandoned, all pits must be fenced immediately until they are backfilled. The "Subsequent Report of Abandonment" (Form BLM 3160-5) must be submitted within 30 days after the actual plugging of the well bore, showing location of plugs, amount of cement in each, and amount of casing left in hole, and the current status of the surface restoration.

DIVISION OF OIL, GAS AND MINING

SPUDDING INFORMATION

Name of Company: Bill Barrett Corp

Well Name: PPU Fed 9-27D-12-16

API No: 43-007-31411 Lease Type: Federal

Section 27 Township 12S Range 16E County Carbon

Drilling Contractor AAA Drilling Rig # 4

SPUDDED:

Date 10-31-08

Time 12:00 PM

How Dry

Drilling will Commence: _____

Reported by Tracey Fallang

Telephone # 303-312-8134

Date 11-03-2008 Signed RM

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

CONFIDENTIAL

FORM 6

ENTITY ACTION FORM

Operator: Bill Barrett Corporation Operator Account Number: N 2165
Address: 1099 18th Street, Suite 2300
city Denver
state CO zip 80202 Phone Number: (303) 312-8134

Well 1

API Number	Well Name	QQ	Sec	Twp	Rng	County
4300731411	Peter's Point Unit Federal 9-27D-12-16	SESE	27	12S	16E	Carbon
Action Code	Current Entity Number	New Entity Number	Spud Date	Entity Assignment Effective Date		
<i>AB</i>	<i>99999</i>	<i>2470</i>	10/31/2008	<i>11/10/08</i>		
Comments: Spud by Triple A Rig #4 with conductor pipe at 12:00 pm. <i>WSMVD BHL = NESE</i>						

CONFIDENTIAL

Well 2

API Number	Well Name	QQ	Sec	Twp	Rng	County
4300731410	Peter's Point Unit Federal 15-27D-12-16	SESE	27	12S	16E	Carbon
Action Code	Current Entity Number	New Entity Number	Spud Date	Entity Assignment Effective Date		
<i>AB</i>	<i>99999</i>	<i>2470</i>	10/31/2008	<i>11/10/08</i>		
Comments: Spud by Triple A Rig #4 with conductor pipe at 12:00 pm. <i>WSMVD BHL = SWSE</i>						

CONFIDENTIAL

Well 3

API Number	Well Name	QQ	Sec	Twp	Rng	County
4300731319	Peter's Point Unit Federal 10-27D-12-16	SESE	27	12S	16E	Carbon
Action Code	Current Entity Number	New Entity Number	Spud Date	Entity Assignment Effective Date		
<i>AB</i>	<i>99999</i>	<i>2470</i>	10/31/2008	<i>11/10/08</i>		
Comments: Spud by Triple A Rig #4 with conductor pipe at 12:00 pm. <i>PRRV = MVRD = WSMVD BHL = NWSE</i>						

CONFIDENTIAL

ACTION CODES:

- A - Establish new entity for new well (single well only)
- B - Add new well to existing entity (group or unit well)
- C - Re-assign well from one existing entity to another existing entity
- D - Re-assign well from one existing entity to a new entity
- E - Other (Explain in 'comments' section)

Tracey Fallang

Name (Please Print)

Signature
Regulatory Analyst

11/3/2008

Title

Date

RECEIVED

NOV 03 2008

DIV. OF OIL, GAS & MINING

COPY tfallang
CONFIDENTIAL
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE – Other instructions on page 2.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Bill Barrett Corporation

3a. Address
1099 18th Street, Suite 2300
Denver, CO 80202

3b. Phone No. (include area code)
303-312-8134

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
SESE, 1050' FSL, 790' FEL
Sec. 27, T12S-R16E

5. Lease Serial No.
UTU-08107

6. If Indian, Allottee or Tribe Name
N/A

7. If Unit of CA/Agreement, Name and/or No.
Peter's Point/UTU-63014

8. Well Name and No.
Peter's Point Unit Federal 9-27D-12-16

9. API Well No.
43-007-31411

10. Field and Pool or Exploratory Area
Peter's Point/Wasatch-Mesaverde

11. Country or Parish, State
Carbon County, UT

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <u>Spud</u>
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

This sundy is being submitted as notification that this well was spud on 10/31/2008.

RECEIVED

NOV 10 2008

DIV. OF OIL, GAS & MINING

14. I hereby certify that the foregoing is true and correct.
Name (Printed/Typed)

Tracey Fallang

Title Regulatory Analyst

Signature

Tracey Fallang

Date 11/03/2008

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONFIDENTIAL

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
**Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.**

5. Lease Serial No.
UTU-08107

6. If Indian, Allottee or Tribe Name
N/A

SUBMIT IN TRIPLICATE – Other instructions on page 2.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Bill Barrett Corporation

3a. Address
1099 18th Street, Suite 2300
Denver, CO 80202

3b. Phone No. (include area code)
303-312-8134

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
SESE, 1050' FSL, 790' FEL
Sec. 27, T12S-R16E

7. If Unit of CA/Agreement, Name and/or No.
Peter's Point/UTU-63014

8. Well Name and No.
Peter's Point Unit Federal 9-27D-12-16

9. API Well No.
43-007-31411

10. Field and Pool or Exploratory Area
Peter's Point/Wasatch-Mesaverde

11. Country or Parish, State
Carbon County, UT

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <u>Weekly Activity</u>
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Report
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Weekly drilling activity from 11/13/08 - 11/21/08 (report #'s 1-4).

14. I hereby certify that the foregoing is true and correct.

Name (Printed/Typed)
Tracey Fallang

Title Regulatory Analyst

Signature

Tracey Fallang

Date 11/21/2008

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

RECEIVED

NOV 25 2008

DIV. OF OIL, GAS & MINING

REGULATORY DRILLING SUMMARY

WELLCORE

Well : Peter's Point #9-27D-12-16

Phase/Area : West Tavaputs

Operations Date : 11/19/2008

Bottom Hole Display	API #/License
NESE-27-12S-16E-W26M	43-007-31411

Report # : 2

Depth At 06:00 : 1000.00

Estimated Total Depth : 7673.00

Surface Location : SESE-27-12S-16E-W26M

Spud Date : Days From Spud : 0

Morning Operations : MOVE IN AND RIG UP

Remarks :

Time To	Description
6:00 AM	MOVE IN AND RIG UP

DAYS SINCE LAST LOST TIME ACCIDENT=124
DAILY SAFETY MEETING= MOVING RIG
BARRELS OF WATER USED DAILY=
BARRELS OF WATER USED TOTAL=
GALLONS OF DIESEL ON LOCATION=
GALLONS OF DIESEL USED DAILY=
GALLONS OF DIESEL USED TOTAL=
TUBULARS ON PETERS POINT 9-27 LOCATION
1-6 1/2" AKO MUD MOTER S/N= ?? HOURS=
1-6 1/2" AKO MUD MOTER S/N=?? HOURS=
1-6 1/2" AKO MUD MOTER S/N=?? HOURS=
342-JOINTS OF 4 1/2" DRILL PIPE
40- JOINTS OF 4 1/2" HEAVY WEIGHT DRILL PIPE
23-JOINTS OF 6 1/2" DRILL COLLARS

Well : Peter's Point #9-27D-12-16

Phase/Area : West Tavaputs

Operations Date : 11/18/2008

Bottom Hole Display	API #/License
NESE-27-12S-16E-W26M	43-007-31411

Report # : 1

Depth At 06:00 : 1000.00

Estimated Total Depth : 7673.00

Surface Location : SESE-27-12S-16E-W26M

Spud Date : Days From Spud : 0

Morning Operations : RIG DOWN AND MOVE OFF PRICKLY PEAR 5-21

Remarks :

Time To	Description
6:00 AM	RIG DOWN AND MOVE OFF PRICKLY PEAR 5-21

DAYS SINCE LAST LOST TIME ACCIDENT=123
DAILY SAFETY MEETING= MOVING RIG
BARRELS OF WATER USED DAILY=
BARRELS OF WATER USED TOTAL=
GALLONS OF DIESEL ON LOCATION=
GALLONS OF DIESEL USED DAILY=
GALLONS OF DIESEL USED TOTAL=
TUBULARS ON PETERS POINT 9-27 LOCATION
1-6 1/2" AKO MUD MOTER S/N= ?? HOURS=
1-6 1/2" AKO MUD MOTER S/N=?? HOURS=
1-6 1/2" AKO MUD MOTER S/N=?? HOURS=
342-JOINTS OF 4 1/2" DRILL PIPE
40- JOINTS OF 4 1/2" HEAVY WEIGHT DRILL PIPE
23-JOINTS OF 6 1/2" DRILL COLLARS

REGULATORY DRILLING SUMMARY

WELLCORE

Well : Peter's Point #9-27D-12-16

Phase/Area : West Tavaputs

Operations Date : 11/21/2008

Bottom Hole Display	API #/License
NESE-27-12S-16E-W26M	43-007-31411

Report # : 4

Depth At 06:00 : 1532.00

Estimated Total Depth : 7673.00

Surface Location : SESE-27-12S-16E-W26M

Spud Date : Days From Spud : 0

Morning Operations : DRILLING W/ BIT #1

Remarks :

DAYS SINCE LAST LOST TIME ACCIDENT=125
DAILY SAFETY MEETING= PRESS TESTING-PIPE IN V-DOOR-PU BHA
BARRELS OF WATER USED DAILY= 360 Bbl
BARRELS OF WATER USED TOTAL=6870 Bbl
GALLONS OF DIESEL ON LOCATION= 10530 GAL
GALLONS OF DIESEL USED DAILY= 881 GAL
GALLONS OF DIESEL USED TOTAL= 881 GAL
TUBULARS ON PETERS POINT 9-27 LOCATION
1-6 1/2" AKO MUD MOTER S/N 2072= 8.5 HOURS-
TOTAL= 8.5 HRS
1-6 1/2" AKO MUD MOTER S/N=?? HOURS=
1-6 1/2" AKO MUD MOTER S/N=?? HOURS=
342-JOINTS OF 4 1/2" DRILL PIPE
40- JOINTS OF 4 1/2" HEAVY WEIGHT DRILL PIPE
23-JOINTS OF 6 1/2" DRILL COLLARS
BLM REP RANDY KNIGHT NOTIFIED OF START WELL-
BOP TEST @10:00 AM 11/20/08 BY PHONE

Time To	Description
7:30 AM	RU & PREPARE FOR BOP TEST
11:30 AM	PRESSURE TEST: PIPE RAMS-BLIND RAMS-CHOKE LINE-INSIDE KILL-INSIDE CHOKE-UPPER KELLEY-LOWER KELLEY-TIW VALVE-HCR VALVE-OUTSIDE KILL-CHOKE LINE-KILL LINE-CHOKE MANIFOLD AT 250 PSI LO-PRESS FOR 5 MIN & 3000 PSI HI-PRESS FOR 10 MIN EA TEST- TEST HYDRIL 250# LO & 1500# HI for 10 Min- TEST CASING TO 1500# & HELD 30 MIN & OKTEST ACCUMULATOR-NITROGEN-AIR PUMP-ELECTRIC TRIPLEX PMPREMOTE-3000# ACCUMULATOR PRESS- 1500# MANIFOLD PRESS-1000# ANNULAR PRESS-Filled Manifold W/ Methonal- INSTALL WEAR BUSHING
12:00 PM	RIG SERVICE & FILL COMPOUND
1:30 PM	RU FLOOR & REPLACE BREAK-OUT LINE
3:30 PM	PU 8 3/4" BIT #1 & DRLG MOTOR, SET MOTOR- MU MWD & ORIENT TOOL FACE-
6:30 PM	TIH PU SWDP, TAG CMT @ 946 FT
9:30 PM	KELLEY UP-INSTALL ROTATING RUBBER, BREAK CIRC- DRILL CMT, PLUG, Float Collar-CMT & FLOAT SHOE @1050 FT
6:00 AM	SPUD @9:30 PM on 11/20/08 & DRILL FORMATION F/ 1050 Ft to 1532 Ft W/ MWD Surveys & SLIDE & ROTATING

Well : Peter's Point #9-27D-12-16

Phase/Area : West Tavaputs

Operations Date : 11/20/2008

Bottom Hole Display	API #/License
NESE-27-12S-16E-W26M	43-007-31411

Report # : 3

Depth At 06:00 : 1031.00

Estimated Total Depth : 7673.00

Surface Location : SESE-27-12S-16E-W26M

Spud Date : Days From Spud : 0

Morning Operations : PREPARE FOR BOP TEST

Remarks :

DAYS SINCE LAST LOST TIME ACCIDENT=124
DAILY SAFETY MEETING= MOVING RIG
BARRELS OF WATER USED DAILY=5070
BARRELS OF WATER USED TOTAL=5070
GALLONS OF DIESEL ON LOCATION=
GALLONS OF DIESEL USED DAILY=
GALLONS OF DIESEL USED TOTAL=
TUBULARS ON PETERS POINT 9-27 LOCATION
1-6 1/2" AKO MUD MOTER S/N= ?? HOURS=
1-6 1/2" AKO MUD MOTER S/N=?? HOURS=
1-6 1/2" AKO MUD MOTER S/N=?? HOURS=
342-JOINTS OF 4 1/2" DRILL PIPE
40- JOINTS OF 4 1/2" HEAVY WEIGHT DRILL PIPE
23-JOINTS OF 6 1/2" DRILL COLLARS

Time To	Description
4:00 PM	MOVE IN TRUCKS FINISHED @ 16:00 HOURS
6:00 AM	RIG UP PREPARE FOR TEST

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.

UTU-08107

6. If Indian, Allottee or Tribe Name

N/A

SUBMIT IN TRIPLICATE - Other instructions on page 2.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Bill Barrett Corporation

3a. Address

1099 18th Street, Suite 2300
Denver, CO 80202

3b. Phone No. (include area code)

303-312-8134

7. If Unit of CA/Agreement, Name and/or No.

Peter's Point/UTU-63014

8. Well Name and No.

Peter's Point Unit Federal 9-27D-12-16

9. API Well No.

43-007-31411

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

SESE, 1050' FSL, 790' FEL
Sec. 27, T12S-R16E

10. Field and Pool or Exploratory Area

Peter's Point/Wasatch-Mesaverde

11. Country or Parish, State

Carbon County, UT

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <u>Weekly Activity</u>
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	<u>Report</u>
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Weekly drilling activity from 11/22/08 - 12/04/08 (report #'s 5-12). Final drilling report, no further reports until completion operations begin (2009).

14. I hereby certify that the foregoing is true and correct.

Name (Printed/Typed)

Tracey Fallang

Title Regulatory Analyst

Signature

Tracey Fallang

Date 12/04/2008

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

RECEIVED

DEC 08 2008

DIV. OF OIL, GAS & MINING

REGULATORY DRILLING SUMMARY

WELLCORE

Well : Peter's Point #9-27D-12-16

Phase/Area : West Tavaputs

Operations Date : 11/22/2008

Bottom Hole Display	API #/License
NESE-27-12S-16E-W26M	43-007-31411

Report # : 5

Depth At 06:00 : 2943.00

Estimated Total Depth : 7673.00

Surface Location : SESE-27-12S-16E-W26M

Spud Date : 11/5/2008

Days From Spud : 17

Morning Operations : DRILLING

Time To	Description
11:00 AM	DRILL 1532 Ft to 1918 Ft W/ MWD SURVEYS- ROTATING & SLIDING FOR CONTROL
11:30 AM	RIG SERVICE- BOP DRILL= 60 SEC- FCT PIPE RAMS & ANNULAR
6:00 AM	DRILL 1918 Ft to 2943 Ft W/ MWD SURVEYS, ROTATION & SLIDING AS NEEDED

Remarks :

DAYS SINCE LAST LOST TIME ACCIDENT=128
DAILY SAFETY MEETING= WELDER'S HELPER-HAND
AWARENESS- BOP DRILL DAYS= 1 MIN- S.MTG NITE=
POWER WASHING- BOP DRILL NITE= 62 MIN
BARRELS OF WATER USED DAILY= 0 Bbl
BARRELS OF WATER USED TOTAL=6870 Bbl
GALLONS OF DIESEL ON LOCATION= 9564 GAL
GALLONS OF DIESEL USED DAILY= 966 GAL
GALLONS OF DIESEL USED TOTAL= 1847 GAL
TUBULARS ON PETERS POINT 9-27 LOCATION
1-6 1/2" AKO MUD MOTER S/N 2072= 23.5 HOURS-
TOTAL= 32.0 HRS
1-6 1/2" AKO MUD MOTER S/N=?? HOURS=
1-6 1/2" AKO MUD MOTER S/N=?? HOURS=
342-JOINTS OF 4 1/2" DRILL PIPE
40- JOINTS OF 4 1/2" HEAVY WEIGHT DRILL PIPE
23-JOINTS OF 6 1/2" DRILL COLLARS

REGULATORY DRILLING SUMMARY

WELLCORE

Well : Peter's Point #9-27D-12-16

Phase/Area : West Tavaputs

Operations Date : 11/24/2008

Bottom Hole Display	API #/License
NESE-27-12S-16E-W26M	43-007-31411

Report # : 7

Depth At 06:00 : 5569.00

Estimated Total Depth : 7673.00

Surface Location : SESE-27-12S-16E-W26M

Spud Date : 11/5/2008

Days From Spud : 19

Morning Operations : DRILLING 8 3/4" HOLE W/ BIT #1

Time To	Description
6:00 AM	DRILL 4704 Ft to 5569 Ft W/ MWD SURVEYS, ROTATION & SLIDING AS NEEDED
1:30 PM	DRILL 4288 Ft to 4704 Ft W/ MWD SURVEYS- ROTATING & SLIDING FOR CONTROL
2:00 PM	RIG SERVICE- BOP DRILL= 56 SEC- FUNCTION TEST PIPE RAMS & ANNULAR

Remarks :

DAYS SINCE LAST LOST TIME ACCIDENT=130 DAYS
DAILY SAFETY MEETING= Changing Oil- Placing Pipe in V-Door- BOP DRILL DAYS= 56 Sec- S.MTG NITE= Methanol in Air System- BOP DRILL NITE= 65 SEC @5279'
BARRELS OF WATER USED DAILY= 0 Bbl
BARRELS OF WATER USED TOTAL=7210 Bbl
GALLONS OF DIESEL ON LOCATION= 7245 GAL
GALLONS OF DIESEL USED DAILY= 1248 GAL
GALLONS OF DIESEL USED TOTAL= 4186 GAL
TUBULARS ON PETERS POINT 9-27 LOCATION
1-6 1/2" AKO MUD MOTER S/N 2072= 23.5 HOURS- TOTAL= 79.0 HRS
1-6 1/2" AKO MUD MOTER S/N 6174= 0 HOURS=
1-6 1/2" AKO MUD MOTER S/N 6413= 0 HOURS=
342-JOINTS OF 4 1/2" DRILL PIPE
40- JOINTS OF 4 1/2" HEAVY WEIGHT DRILL PIPE
23-JOINTS OF 6 1/2" DRILL COLLARS
8 Jts 4.5"-11.6#-I-80-LTC PROD CSG
4 Jts 9 5/8"- 36#- J-55- STC SURF CSG

Well : Peter's Point #9-27D-12-16

Phase/Area : West Tavaputs

Operations Date : 11/23/2008

Bottom Hole Display	API #/License
NESE-27-12S-16E-W26M	43-007-31411

Report # : 6

Depth At 06:00 : 4288.00

Estimated Total Depth : 7673.00

Surface Location : SESE-27-12S-16E-W26M

Spud Date : 11/5/2008

Days From Spud : 18

Morning Operations : DRILLING 8 3/4" HOLE W/ BIT #1

Time To	Description
6:00 AM	DRILL 3456 Ft to 4288 Ft W/ MWD SURVEYS, ROTATION & SLIDING AS NEEDED
2:00 PM	DRILL 2943 Ft to 3456 Ft W/ MWD SURVEYS- ROTATING & SLIDING FOR CONTROL
2:30 PM	RIG SERVICE- BOP DRILL= 57 SEC- FUNCTION TEST PIPE RAMS & ANNULAR

Remarks :

DAYS SINCE LAST LOST TIME ACCIDENT=129
DAILY SAFETY MEETING= BOP PROCEDURES, Pressure Washing- BOP DRILL DAYS= 57 Sec- S.MTG NITE= BOP Procedures While Drilling- BOP DRILL NITE= @4096'= 1 MIN- 30 SEC
BARRELS OF WATER USED DAILY= 340 Bbl
BARRELS OF WATER USED TOTAL=7210 Bbl
GALLONS OF DIESEL ON LOCATION= 8493 GAL
GALLONS OF DIESEL USED DAILY= 1091 GAL
GALLONS OF DIESEL USED TOTAL= 2938 GAL
TUBULARS ON PETERS POINT 9-27 LOCATION
1-6 1/2" AKO MUD MOTER S/N 2072= 23.5 HOURS- TOTAL= 55.5 HRS
1-6 1/2" AKO MUD MOTER S/N 6174= 0 HOURS=
1-6 1/2" AKO MUD MOTER S/N 6413= 0 HOURS=
342-JOINTS OF 4 1/2" DRILL PIPE
40- JOINTS OF 4 1/2" HEAVY WEIGHT DRILL PIPE
23-JOINTS OF 6 1/2" DRILL COLLARS
8 Jts 4.5"-11.6#-I-80-LTC PROD CSG
4 Jts 9 5/8"- 36#- J-55- STC SURF CSG

REGULATORY DRILLING SUMMARY

WELLCORE

Well : Peter's Point #9-27D-12-16

Phase/Area : West Tavaputs

Operations Date : 11/25/2008

Bottom Hole Display	API #/License
NESE-27-12S-16E-W26M	43-007-31411

Report # : 8

Depth At 06:00 : 6434.00

Estimated Total Depth : 7673.00

Surface Location : SESE-27-12S-16E-W26M

Spud Date : 11/5/2008

Days From Spud : 20

Morning Operations : DRILLING 8 3/4" HOLE W/ BIT #1

Remarks :

Time To	Description
6:00 AM	DRILL 5857 Ft to 6434 Ft W/ MWD SURVEYS, ROTATION & SLIDING AS NEEDED
1:30 PM	DRILL 5569 Ft to 5857 Ft W/ MWD SURVEYS- ROTATING & SLIDING FOR CONTROL
2:00 PM	RIG SERVICE- BOP DRILL= 54 SEC- FUNCTION TEST PIPE RAMS & ANNULAR

DAYS SINCE LAST LOST TIME ACCIDENT=131 DAYS
DAILY SAFETY MEETING= UNLOADING
CASING-Methanol in Air System- BOP DRILL DAYS= 54
Sec- S.MTG NITE= OFLOADING CSG- MOVING DP W/
FORKLIFT- BOP DRILL NITE= 59 SEC @6274'
BARRELS OF WATER USED DAILY= 260 Bbl
BARRELS OF WATER USED TOTAL=7470 Bbl
GALLONS OF DIESEL ON LOCATION= 5973 GAL
GALLONS OF DIESEL USED DAILY= 1272 GAL
GALLONS OF DIESEL USED TOTAL= 5458 GAL
TUBULARS ON PETERS POINT 9-27 LOCATION
1-6 1/2" AKO MUD MOTER S/N 2072= 23.5 HOURS-
TOTAL= 102.5 HRS
1-6 1/2" AKO MUD MOTER S/N 6174= 0 HOURS=
1-6 1/2" AKO MUD MOTER S/N 6413= 0 HOURS=
342-JOINTS OF 4 1/2" DRILL PIPE
40- JOINTS OF 4 1/2" HEAVY WEIGHT DRILL PIPE
23-JOINTS OF 6 1/2" DRILL COLLARS
8 Jts 4.5"-11.6#-I-80-LTC PROD CSG
4 Jts 9 5/8"- 36#- J-55- STC SURF CSG
Recived 184 Jts P.CSG-4 1/2"-11.6#-I-100-LTC + 2 x Short
Mkr Jts P.CSG

REGULATORY DRILLING SUMMARY

WELLCORE

Well : Peter's Point #9-27D-12-16

Phase/Area : West Tavaputs

Operations Date : 11/26/2008

Bottom Hole Display	API #/License
NESE-27-12S-16E-W26M	43-007-31411

Report # : 9

Depth At 06:00 : 7008.00

Estimated Total Depth : 7673.00

Surface Location : SESE-27-12S-16E-W26M

Spud Date : 11/5/2008

Days From Spud : 21

Morning Operations : TRIPPING IN HOLE W/ BIT #2

Remarks :

Time To	Description
1:30 AM	DRILL 6623 Ft to 7008 Ft W/ MWD SURVEYS, ROTATION FOR LAST 3500 FT
12:00 PM	DRILL 6434 Ft to 6623 Ft W/ MWD SURVEYS- ROTATING fo Last 2200'- Dropping Angle Rot
12:30 PM	RIG SERVICE- BOP DRILL= 54 SEC- FUNCTION TEST PIPE RAMS & ANNULAR
5:30 AM	SLUG PIPE- TOH LD BIT #1 & MOTOR #1 & DIRECTIONAL TOOLS
6:00 AM	PU 7 7/8" BIT #2 & NEW Drlg MOTOR & TIH

DAYS SINCE LAST LOST TIME ACCIDENT=132 DAYS
DAILY SAFETY MEETING= Crew Chg, Driving To & From
LOC-Separating Pipe W/Forklift- BOP DRILL DAYS= 54
Sec- S.MTG NITE= Driving to & From Loc- Tripping- BOP
DRILL NITE= 58 SEC @6997"
BARRELS OF WATER USED DAILY= 0 Bbl
BARRELS OF WATER USED TOTAL=7470 Bbl
GALLONS OF DIESEL ON LOCATION= 4280 GAL
GALLONS OF DIESEL USED DAILY= 1693 GAL
GALLONS OF DIESEL USED TOTAL= 7151 GAL
TUBULARS ON PETERS POINT 9-27 LOCATION
1-6 1/2" AKO MUD MOTER S/N 2072= 19.0 hrs- Ttl= 121.5
hrs-out @7008'
1-6 1/2" AKO MUD MOTER S/N 6174= 0 HOURS=
1-6 1/2" AKO MUD MOTER S/N 6413= 0 HOURS=
342-JOINTS OF 4 1/2" DRILL PIPE
40- JOINTS OF 4 1/2" HEAVY WEIGHT DRILL PIPE
23-JOINTS OF 6 1/2" DRILL COLLARS
8 Jts 4.5"-11.6#-I-80-LTC PROD CSG
4 Jts 9 5/8"- 36#- J-55- STC SURF CSG
184 Jts P.CSG-4 1/2"-11.6#-I-100-LTC + 2 x Short Mkr Jts
P.CSG

REGULATORY DRILLING SUMMARY

WELLCORE

Well : Peter's Point #9-27D-12-16

Phase/Area : West Tavaputs

Operations Date : 11/27/2008

Bottom Hole Display	API #/License
NESE-27-12S-16E-W26M	43-007-31411

Report # : 10

Depth At 06:00 : 7697.00

Estimated Total Depth : 7673.00

Surface Location : SESE-27-12S-16E-W26M

Spud Date : 11/5/2008

Days From Spud : 22

Morning Operations : DRILLING TD HOLE @ 6:00 AM on 11/27/2008 @7697 FT

Remarks :

Time To	Description
9:00 AM	TIH W/ Bit #2, BREAK CIRC @4600' & 6945'
9:30 AM	WASH & REAM 6945' to 7008'
10:30 AM	PUMP SWEEP & CIRC BOTTEMS-UP, WASH BIT PIECES OFF BTM
12:30 PM	DRILL W/7 7/8" BIT #2 F/ 7008 Ft to 7074 Ft
1:00 PM	RIG SERVICE- BOP Drill= 53 Sec- Function Pipe Rams & Annular Preventer
6:00 AM	DRILL 7 7/8" Hole W/ BIT #2 F/ 7074 Ft TD @7697 Ft @6:00 AM on 11/27/08

DAYS SINCE LAST LOST TIME ACCIDENT=133 DAYS
DAILY SAFETY MEETING= TRIPPING- Hearing Prot- BOP
DRILL DAYS= 53 Sec- S.MTG NITE= Pipe In V-Door- Set
Kelley Back- BOP DRILL NITE= 67 SEC
BARRELS OF WATER USED DAILY= 160 Bbl
BARRELS OF WATER USED TOTAL=7630 Bbl
GALLONS OF DIESEL ON LOCATION= 10,050 GAL
GALLONS OF DIESEL USED DAILY= 2230 GAL
GALLONS OF DIESEL USED TOTAL= 9381 GAL
TUBULARS ON PETERS POINT 9-27 LOCATION
1-6 1/2" AKO MUD MOTER S/N 2072= 19.0 hrs- Ttl= 121.5
hrs-out @7008'
1-6 1/2" AKO MUD MOTER S/N 6174= 0 HOURS=
1-6 1/2" AKO MUD MOTER S/N 6413= 19 HOURS TOTAL/
TD @7697 FT @6:AM 11/27/08
342-JOINTS OF 4 1/2" DRILL PIPE
40- JOINTS OF 4 1/2" HEAVY WEIGHT DRILL PIPE
23-JOINTS OF 6 1/2" DRILL COLLARS
8 Jts 4.5"-11.6#-I-80-LTC PROD CSG
4 Jts 9 5/8"- 36#- J-55- STC SURF CSG
184 Jts P.CSG-4 1/2"-11.6#-I-100-LTC + 2 x Short Mkr Jts
P.CSG

REGULATORY DRILLING SUMMARY

WELLCORE

Well : Peter's Point #9-27D-12-16

Phase/Area : West Tavaputs

Operations Date : 11/28/2008

Bottom Hole Display	API #/License
NESE-27-12S-16E-W26M	43-007-31411

Report # : 11

Depth At 06:00 : 7697.00

Estimated Total Depth : 7673.00

Surface Location : SESE-27-12S-16E-W26M

Spud Date : 11/5/2008

Days From Spud : 23

Morning Operations : TOH LD DRILL STRING

Time To	Description
7:00 AM	CIRC BOTTEMS-UP For Short Trip
8:00 AM	SHORT TRIP 10 STANDS TO 6707 FT
9:00 AM	CIRC & Cond @TD For TOH FOR LOG O.H.
12:30 PM	TOH FOR LOGS- Function Blind Rams
6:30 PM	S.MTG, RU HALCO LOGGERS/ RUN TRIPLE COMBO LOG FROM WL DEPTH 7684 FT TO SURF CSG @1046 FT-1st Run Was Mis-Run, Tools Quit Working @ 7300 Ft- POH Re-Placed TOOL & LOGED WELL ON 2nd Run- RD Halco
7:00 PM	PULL WEAR BUSHING
10:30 PM	TIH W/ USED 7 7/8" RR TRI-CONE BIT #3 & BS
11:00 PM	WASH 30 FT TO BTM, 10' FILL
12:30 AM	CIRC & COND @TD 7697 FT-RU LD equipt
6:00 AM	TOH LD DP, HAD Pump-out 15 SINGLES- STAND BACK 7 STDS SWDP

Remarks :

DAYS SINCE LAST LOST TIME ACCIDENT=134 DAYS
DAILY SAFETY MEETING= TRIPPING- LOGGING OH-
BOP DRILL DAYS= 53 Sec- S.MTG NITE= TRIPPING-
LDDP- BOP DRILL NITE= 67 SEC
BARRELS OF WATER USED DAILY= 0 Bbl
BARRELS OF WATER USED TOTAL=7630 Bbl
GALLONS OF DIESEL ON LOCATION= 9473 GAL
GALLONS OF DIESEL USED DAILY= 577 GAL
GALLONS OF DIESEL USED TOTAL= 9958 GAL
TUBULARS ON PETERS POINT 9-27 LOCATION
1-6 1/2" AKO MUD MOTER S/N 2072= 19.0 hrs- Ttl= 121.5
hrs-out @7008'
1-6 1/2" AKO MUD MOTER S/N 6174= 0 HOURS=
1-6 1/2" AKO MUD MOTER S/N 6413= 19 HOURS TOTAL/
TD @7697 FT @6:AM 11/27/08
342-JOINTS OF 4 1/2" DRILL PIPE
40- JOINTS OF 4 1/2" HEAVY WEIGHT DRILL PIPE
23-JOINTS OF 6 1/2" DRILL COLLARS
8 Jts 4.5"-11.6#-I-80-LTC PROD CSG
4 Jts 9 5/8"- 36#- J-55- STC SURF CSG
184 Jts P.CSG-4 1/2"-11.6#-I-100-LTC + 2 x Short Mkr Jts
P.CSG
Note: Notify BLM Rep Randy Knight On His Cell Phone
@8:45 PM on 11/27/08 OF TD ThisB Well- Plans For Run
Csg & Cement & Est Skid Rig to Next Well- NU & Press
Test on SAT 11/29/08 on Peters Point U.F. 15-27D-12-16
-LEFT MESSAGE ON HIS VOICE MAIL OF THESE
ACTIONS

REGULATORY DRILLING SUMMARY

WELLCORE

Well : Peter's Point #9-27D-12-16

Phase/Area : West Tavaputs

Operations Date : 11/29/2008

Bottom Hole Display	API #/License
NESE-27-12S-16E-W26M	43-007-31411

Report # : 12

Depth At 06:00 : 7697.00

Estimated Total Depth : 7673.00

Surface Location : SESE-27-12S-16E-W26M

Spud Date : 11/5/2008

Days From Spud : 24

Morning Operations : PREP RIG FOR SKID- RELEASE RIG TO SKID @6:00 AM on 11/29/08

Remarks :

DAYS SINCE LAST LOST TIME ACCIDENT=134 DAYS
DAILY SAFETY MEETING= LAY DOWN DRLG STRING-
RUN CSG- CEMENT- ND BOP'S- COLD WEATHER- BOP
DRILL DAYS= 53 Sec- S.MTG NITE= TRIPPING- LDDP-
BOP DRILL NITE= 67 SEC
BARRELS OF WATER USED DAILY= 0 Bbl
BARRELS OF WATER USED TOTAL=7,630 Bbl
GALLONS OF DIESEL ON LOCACATION= 8855 GAL
GALLONS OF DIESEL USED DAILY= 618 GAL
GALLONS OF DIESEL USED TOTAL= 10,576 GAL
TUBULARS ON PETERS POINT 9-27 LOCATION
1-6 1/2" AKO MUD MOTER S/N 2072= 19.0 hrs- Ttl= 121.5
hrs-out @7008'
1-6 1/2" AKO MUD MOTER S/N 6174= 0 HOURS=
1-6 1/2" AKO MUD MOTER S/N 6413= 19 HOURS TOTAL/
TD @7697 FT @6:AM 11/27/08
342-JOINTS OF 4 1/2" DRILL PIPE
40- JOINTS OF 4 1/2" HEAVY WEIGHT DRILL PIPE
23-JOINTS OF 6 1/2" DRILL COLLARS
8 Jts 4.5"-11.6#-I-80-LTC PROD CSG
4 Jts 9 5/8"- 36#- J-55- STC SURF CSG
2 Jts P.CSG-4 1/2"-11.6#-I-100-LTC Jts P.CSG
Note: Notify BLM Rep Randy Knight On His Cell Phone
@8:45 PM on 11/27/08 OF TD ThisB Well- Plans For Run
Csg & Cement & Est Skid Rig to Next Well- NU & Press
Test on SAT 11/29/08 on Peters Point U.F. 15-27D-12-16
-Randy Knight Called Me @7:00 AM- 11/28/08 & we
Discussed These Actions. Said He will Proibly See Me
Monday.

Time To	Description
8:00 AM	FIN TOH LD DP-STAND BACK 7 STND's SWDP
1:00 PM	S.MTG W/ Casers-RU & RUN 184 Jts 4.5"- 11.6#- I-100- LT&C Prod w/ F.Shoe- Float Coll- 40 Centralizers- 2 Short Marker Jts- Land Csg @ 7687 Ft KBM- RD CSG RUN EQUIPTMENT
3:00 PM	CIRC & COND & WASH DOWN LAST JT CSG & CIRC CSG @7687 FT & RD PU Machine
6:30 PM	Safety Mtg w/ HALCO- RU HES- Test Lines- Pump 10 Bbl Water- 20 Bbl Super Flush @10#/gal-10 Bbl Water Spacers Ahead- Mix & Pump 1665 Sks 50/50 POZ Premium SBM Cement W/ 1.48 Yield- 6.99 Gps/H2O- @ AVG 13.4 Ppg w/ 2% Gel- 3% KCL- .75% Halad(R)-322- 2% FWCA- 3 #/Sk Silicalite- 0.125 lb/sk Poly- Flake- 1 lb/sk Granulite TR-1/4- (Total of 439 Bbl 13.4 lb/gal Slurry)- Drop Plug & Displace w/ 119 Bbl H2O w/ MA-844 additive- Bump Plug @2.5 bpm spr @2100 psi- Press up to 2772 Psi @5:49 PM on 11/28/08- Good Returns thru-out job- REL PRESS & Floats Held- RD HALLIBURTON
10:00 PM	ND BOP- SET 4.5" Slips @ 105 K , 10 K OVER STRING WT- CLEANING MUD PITS, CUT-OFF & LD CUT-OFF JT
6:00 AM	RD W/ CREWS, PREPARE FOR SKID- WINTERIZE PUMPS & RIG EQUIPT- SLIP & CUT DRILL LINE- (NOTE: RELEASE RIG @ 6:00 AM ON 11/29/2008)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

tfallang
CONFIDENTIAL
CONFIDENTIAL

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.
U-08107

6. If Indian, Allottee or Tribe Name
N/A

SUBMIT IN TRIPLICATE - Other instructions on page 2.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Bill Barrett Corporation

3a. Address
1099 18th Street, Suite 2300
Denver, CO 80202

3b. Phone No. (include area code)
303-312-8134

7. If Unit of CA/Agreement, Name and/or No.
Peter's Point/UTU-63014

8. Well Name and No.
Peter's Point Unit Federal 9-27D-12-16

9. API Well No.
43-007-31411

10. Field and Pool or Exploratory Area
Peter's Point/Wasatch-Mesaverde

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
SESE, 1050' FSL, 790' FEL
Sec. 27, T12S-R16E

11. Country or Parish, State
Carbon County, UT

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <u>Weekly Activity</u>
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	<u>Report</u>
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

No activity, waiting on completion.

STATE ONLY

RECEIVED
JAN 20 2009


DIV. OF OIL, GAS & MINING

14. I hereby certify that the foregoing is true and correct.
Name (Printed/Typed)

Tracey Fallang

Title Regulatory Analyst

Signature



Date 01/12/2009

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

WELL NAME	FIELD	COUNTY	QTR/QTR	SEC	TWN-RNG	FOOTAGE	CALLS	LEASE #	# OF TANKS
PETERS POINT U FED 3-36-12-16	PETER'S POINT	CARBON	NENW	36	12S-16E	572	N 2184 W	UTU-04049	(2) Multiple Well Prod Tank (1) Prod Tank (15-25D) (1) Test Tank (1) Blowdown Tank
PETERS POINT U FED 4-36D-12-16	PETER'S POINT	CARBON	NENW	36	12S-16E	617	N 2202 W	UTU-04049	
PETERS POINT U FED 15-25D-12-16	PETER'S POINT	CARBON	NENW	36	12S-16E	602	N 2195 W	UTU-0681	
PETERS POINT U FED 13-25D-12-16	PETER'S POINT	CARBON	NENW	36	12S-16E	588	N 2189 W	UTU-0681	(4) Multiple Well Prod Tanks (1) Test Tank (1) Blowdown Tank
PETERS POINT U FED 14-26D-12-16	PETER'S POINT	CARBON	SESW	26	12S-16E	225	S 1522 W	UTU-0681	
PETERS POINT U FED 3-35D-12-16	PETER'S POINT	CARBON	SESW	26	12S-16E	208	S 1527 W	JTSL-07159	
PETERS POINT U FED 15-26D-12-16	PETER'S POINT	CARBON	SESW	26	12S-16E	239	S 1518 W	UTU-0681	
PETERS POINT U FED 13-26D-12-16	PETER'S POINT	CARBON	SESW	26	12S-16E	254	S 1514 W	UTU-0681	
PETERS POINT U FED 10-26D-12-16	PETER'S POINT	CARBON	SESW	26	12S-16E	270	S 1510 W	UTU-0681	
PETERS POINT U FED 11-26D-12-16	PETER'S POINT	CARBON	SESW	26	12S-16E	285	S 1506 W	UTU-0681	
PETERS POINT U FED 12-26D-12-16	PETER'S POINT	CARBON	SESW	26	12S-16E	301	S 1502 W	UTU-0681	(3) Multiple Well Prod Tanks (1) Test Tank (1) Blowdown Tank
PETERS POINT U FED 6-35D-12-16	PETER'S POINT	CARBON	SESW	26	12S-16E	301	S 1502 W	UTU-0681	
PETERS POINT U FED 6-35D-12-16	PETER'S POINT	CARBON	SESW	26	12S-16E	301	S 1502 W	UTU-0681	
PETERS POINT U FED 2-35D-12-16	PETER'S POINT	CARBON	SESW	26	12S-16E	301	S 1502 W	UTU-0681	
PETERS POINT U FED 1-35D-12-16	PETER'S POINT	CARBON	SESW	26	12S-16E	301	S 1502 W	UTU-0681	
PETERS POINT U FED 7-35D-12-16	PETER'S POINT	CARBON	SESW	26	12S-16E	301	S 1502 W	UTU-0681	(2) Multiple Well Prod Tanks (1) Prod Tank (11-27D) (1) Test Tank (1) Blowdown Tank
PETERS POINT U FED 4-35D-12-16	PETER'S POINT	CARBON	SESW	26	12S-16E	301	S 1502 W	UTU-0681	
PETER'S POINT U FED 16-27-12-16	PETER'S POINT	CARBON	SESE	27	12S-16E	1049	S 813 E	UTU-08107	
PETER'S POINT U FED 9-27D-12-16	PETER'S POINT	CARBON	SESE	27	12S-16E	1050	S 790 E	UTU-08107	
PETER'S POINT U FED 15-27D-12-16	PETER'S POINT	CARBON	SESE	27	12S-16E	1063	S 799 E	UTU-08107	
PETER'S POINT U FED 11-27D-12-16	PETER'S POINT	CARBON	SESE	27	12S-16E	1075	S 809 E	UTU-08107	(2) Multiple Well Prod Tanks (1) Prod Tank (11-27D) (1) Test Tank (1) Blowdown Tank
PETER'S POINT U FED 10-27D-12-16	PETER'S POINT	CARBON	SESE	27	12S-16E	1088	S 819 E	UTU-08107	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

trialang
CONFIDENTIAL

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
**Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.**

COPY

SUBMIT IN TRIPLICATE – Other instructions on page 2.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Bill Barrett Corporation

3a. Address
1099 18th Street, Suite 2300
Denver, CO 80202

3b. Phone No. (include area code)
303-312-8134

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
see attached 12S 16E 27

5. Lease Serial No.
see attached

6. If Indian, Allottee or Tribe Name
N/A

7. If Unit of CA/Agreement, Name and/or No.
Peter's Point/UTU-63014

8. Well Name and No.
see attached PPU Fed 9-27D-12-16

9. API Well No.
43 007 31411

10. Field and Pool or Exploratory Area
Peter's Point/Wasatch-Mesaverde

11. Country or Parish, State
Carbon County, UT

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☒ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☐ Acidize

☐ Alter Casing

☐ Casing Repair

☐ Change Plans

☐ Convert to Injection

☐ Deepen

☐ Fracture Treat

☐ New Construction

☐ Plug and Abandon

☐ Plug Back

☐ Production (Start/Resume)

☐ Reclamation

☐ Recomplete

☐ Temporarily Abandon

☐ Water Disposal

☐ Water Shut-Off

☐ Well Integrity

☒ Other Revised layout
and measurement

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

This sundy is being submitted as a follow up to clarify testing/allocation methods for the attached wells.

Initial testing would occur (or has occurred) as soon as possible after production is established and would be a 1-3 day test to get a baseline for allocation. After the initial test is performed, BBC would move to quarterly testing, testing each well for 7-10 days and rotating through the wells without any downtime between tests. Revised site security diagrams will be submitted as wells are completed.

COPY SENT TO OPERATOR

Date: 2.24.2009

Initials: KS

14. I hereby certify that the foregoing is true and correct.

Name (Printed/Typed)

Tracey Fallang

Title Regulatory Analyst

Signature

Tracey Fallang

Date 02/10/2009

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

[Signature]

Title

Pet. Eng.

Date

2/17/09

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

DOGm

Federal Approval Of This
Action Is Necessary

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

RECEIVED
FEB 12 2009
DIV. OF OIL, GAS & MINING

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

tfallang
CONFIDENTIAL

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
**Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.**

5. Lease Serial No.
UTU-08107

6. If Indian, Allottee or Tribe Name
N/A

SUBMIT IN TRIPLICATE – Other instructions on page 2.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Bill Barrett Corporation

3a. Address
1099 18th Street, Suite 2300
Denver, CO 80202

3b. Phone No. (include area code)
303-312-8134

7. If Unit of CA/Agreement, Name and/or No.
Peter's Point/UTU-63014

8. Well Name and No.
Peter's Point Unit Federal 9-27D-12-16

9. API Well No.
43-007-31411

10. Field and Pool or Exploratory Area
Peter's Point/Wasatch-Mesaverde

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
SESE, 1050' FSL, 790' FEL
Sec. 27, T12S-R16E

11. Country or Parish, State
Carbon County, UT

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <u>Weekly Activity</u>
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Report
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

No activity, waiting on completion.

STATE ONLY

14. I hereby certify that the foregoing is true and correct.

Name (Printed/Typed)

Tracey Fallang

Title Regulatory Analyst

Signature

Tracey Fallang

Date 02/10/2009

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

RECEIVED

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

FEB 17 2009
DIV. OF OIL, GAS & MINING

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONFIDENTIAL

FORM APPROVED
OMB No. 1004-0127
Expires July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.
UTU-08107

6. If Indian, Allottee or Tribe Name
N/A

SUBMIT IN TRIPLICATE - Other instructions on page 2.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Bill Barrett Corporation

3a. Address
1099 18th Street, Suite 2300
Denver, CO 80202

3b. Phone No. (include area code)
303-312-8134

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
SESE, 1050' FSL, 790' FEL
Sec. 27, T12S-R16E

7. If Unit of CA/Agreement, Name and/or No.
Peter's Point/UTU-63014

8. Well Name and No.
Peter's Point Unit Federal 9-27D-12-16

9. API Well No.
43-007-31411

10. Field and Pool or Exploratory Area
Peter's Point/Wasatch-Mesaverde

11. Country or Parish, State
Carbon County, UT

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <u>Weekly Activity</u>
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Report
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Weekly completion activity report from 2/11/09 through 2/18/09 (report #'s 2-3).

14. I hereby certify that the foregoing is true and correct.

Name (Printed/Typed)
Tracey Fallang

Title Regulatory Analyst

Signature

Tracey Fallang

Date 02/18/2009

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

RECEIVED

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FEB 23 2009

(Instructions on page 2)

DIV. OF OIL, GAS & MINING

REGULATORY COMPLETION SUMMARY

WELLCORE

Well Name : Peter's Point #9-27D-12-16

Phase/Area

West Tavaputs

Bottom Hole Display	API #/License
NESE-27-12S-16E-W26M	43-007-31411

Ops Date : 2/12/2009

Report # : 3

AFE # : 15169D

Summary : Rig HES EL Truck up. Pick up Radial CBL Tool. RIH to PBD @ 7564'. Log up to 540'. With 1000 PSI on CSG. CMT @ 1250'. LD CBL tool. RD SWI.

End Time

Description

10:30 AM

SI

2:30 PM

Rig up HES EL Truck. Pick up Radial CBL & 3.65" gauge ring. RIH to PBD @ 7564'. Pressure CSG up to 1000 PSI. Log to 540'. CMT @ 1250'. LD CBL. RD. SWI

11:59 PM

SI

Well Name : Peter's Point #9-27D-12-16

Phase/Area

West Tavaputs

Bottom Hole Display	API #/License
NESE-27-12S-16E-W26M	43-007-31411

Ops Date : 2/11/2009

Report # : 2

AFE # : 15169D

Summary : Move HES, RU. Pick up Gyro/ Data tool up. RIH recording Data every 100'. POOH LD Tool.

End Time

Description

3:00 AM

SI

4:00 AM

MI HES EL Truck, Rig up.

8:00 AM

Pick up Gyro/ Data tool. RIH Recording DATA every 100'. POOH, Lay tool down.

11:59 PM

SI

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

tfallang
CONFIDENTIAL

FORM APPROVED
OMB No. 1004-0137
Expires July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.
UTU-08107

6. If Indian, Allottee or Trust Name
N/A

COPY

SUBMIT IN TRIPLICATE – Other instructions on page 2.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Bill Barrett Corporation

3a. Address
1099 18th Street, Suite 2300
Denver, CO 80202

3b. Phone No. (include area code)
303-312-8134

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
SESE, 1050' FSL, 790' FEL
Sec. 27, T12S-R16E

7. If Unit of CA/Agreement, Name and/or No.
Peter's Point/UTU-63014

8. Well Name and No.
Peter's Point Unit Federal 9-27D-12-16

9. API Well No.
43-007-31411

10. Field and Pool or Exploratory Area
Peter's Point/Wasatch-Mesaverde

11. Country or Parish, State
Carbon County, UT

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other Weekly Activity
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Report
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

No weekly completion activity from 02/19/09 through 3/19/09.

14. I hereby certify that the foregoing is true and correct.

Name (Printed/Typed)
Tracey Fallang

Title Regulatory Analyst

Signature

Tracey Fallang

Date 03/19/2009

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

RECEIVED

MAR 25 2009

DIV. OF OIL, GAS & MINING

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

~~CONFIDENTIAL~~

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.
UTU-08107

6. If Indian, Allottee or Tribe Name
N/A

SUBMIT IN TRIPLICATE – Other instructions on page 2.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Bill Barrett Corporation

7. If Unit of CA/Agreement, Name and/or No.
Peter's Point/UTU-63014

8. Well Name and No.
Peter's Point Unit Federal 9-27D-12-16

3a. Address
1099 18th Street, Suite 2300
Denver, CO 80202

3b. Phone No. (include area code)
303-312-8134

9. API Well No.
43-007-31411

10. Field and Pool or Exploratory Area
Peter's Point/Wasatch-Mesaverde

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
SESE, 1050' FSL, 790' FEL
Sec. 27, T12S-R16E

11. Country or Parish, State
Carbon County, UT

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <u>Weekly Activity</u>
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	<u>Report</u>
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

No activity, waiting on completion.

**** STATE ONLY ****

14. I hereby certify that the foregoing is true and correct.
Name (Printed/Typed)

Tracey Fallang

Title Regulatory Analyst

Signature

Tracey Fallang

Date 04/15/2009

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

RECEIVED

APR 20 2009

DIV. OF OIL, GAS & MINING

tfallang
CONFIDENTIAL

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.
UTU-08107

6. If Indian, Allottee or Tribe Name
N/A

SUBMIT IN TRIPLICATE – Other instructions on page 2.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Bill Barrett Corporation

3a. Address
1099 18th Street, Suite 2300
Denver, CO 80202

3b. Phone No. (include area code)
303-312-8134

7. If Unit of CA/Agreement, Name and/or No.
Peter's Point/UTU-63014

8. Well Name and No.
Peter's Point Unit Federal 9-27D-12-16

9. API Well No.
43-007-31411

10. Field and Pool or Exploratory Area
Peter's Point/Wasatch-Mesaverde

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
SESE, 1050' FSL, 790' FEL
Sec. 27, T12S-R16E

11. Country or Parish, State
Carbon County, UT

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <u>Weekly Activity</u>
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	<u>Report</u>
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

No activity, waiting on completion.

**** STATE ONLY ****

14. I hereby certify that the foregoing is true and correct.

Name (Printed/Typed)
Tracey Fallang

Title Regulatory Analyst

Signature

Tracey Fallang

Date 05/14/2009

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.


RECEIVED

(Instructions on page 2)

MAY 18 2009

DIV. OF OIL, GAS & MINING

<div>STATE OF UTAH</div> <div>DEPARTMENT OF NATURAL RESOURCES</div> <div>DIVISION OF OIL, GAS, AND MINING</div>		<div>FORM 9</div> <div>5.LEASE DESIGNATION AND SERIAL NUMBER: UTU-08107</div>	
<div>SUNDRY NOTICES AND REPORTS ON WELLS</div> <div>Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.</div>		<div>6. IF INDIAN, ALLOTTEE OR TRIBE NAME:</div> <div>7.UNIT or CA AGREEMENT NAME: PETERS POINT</div>	
<div>1. TYPE OF WELL</div> <div>Gas Well</div>		<div>8. WELL NAME and NUMBER:</div> <div>PPU FED 9-27D-12-16</div>	
<div>2. NAME OF OPERATOR:</div> <div>BILL BARRETT CORP</div>		<div>9. API NUMBER:</div> <div>43007314110000</div>	
<div>3. ADDRESS OF OPERATOR:</div> <div>1099 18th Street Ste 2300 , Denver, CO, 80202</div>		<div>PHONE NUMBER:</div> <div>303 312-8128 Ext</div>	
<div>4. LOCATION OF WELL</div> <div>FOOTAGES AT SURFACE: 1050 FSL 0790 FEL</div> <div>QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SESE Section: 27 Township: 12.0S Range: 16.0E Meridian: S</div>		<div>9. FIELD and POOL or WILDCAT:</div> <div>PETER'S POINT</div>	
		<div>COUNTY:</div> <div>CARBON</div>	
		<div>STATE:</div> <div>UTAH</div>	
<div>11.</div> <div>CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA</div>			
<div>TYPE OF SUBMISSION</div>		<div>TYPE OF ACTION</div>	
<div><input type="checkbox"/> NOTICE OF INTENT</div> <div>Approximate date work will start:</div> <div><input type="checkbox"/> SUBSEQUENT REPORT</div> <div>Date of Work Completion:</div> <div><input type="checkbox"/> SPUD REPORT</div> <div>Date of Spud:</div> <div><input checked="" type="checkbox"/> DRILLING REPORT</div> <div>Report Date: 5/28/2009</div>		<div><input type="checkbox"/> ACIDIZE</div> <div><input type="checkbox"/> CHANGE TO PREVIOUS PLANS</div> <div><input type="checkbox"/> CHANGE WELL STATUS</div> <div><input type="checkbox"/> DEEPEN</div> <div><input type="checkbox"/> OPERATOR CHANGE</div> <div><input type="checkbox"/> PRODUCTION START OR RESUME</div> <div><input type="checkbox"/> REPERFORATE CURRENT FORMATION</div> <div><input type="checkbox"/> TUBING REPAIR</div> <div><input type="checkbox"/> WATER SHUTOFF</div> <div><input type="checkbox"/> WILDCAT WELL DETERMINATION</div> <div><input type="checkbox"/> ALTER CASING</div> <div><input type="checkbox"/> CHANGE TUBING</div> <div><input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS</div> <div><input type="checkbox"/> FRACTURE TREAT</div> <div><input type="checkbox"/> PLUG AND ABANDON</div> <div><input type="checkbox"/> RECLAMATION OF WELL SITE</div> <div><input type="checkbox"/> SIDETRACK TO REPAIR WELL</div> <div><input type="checkbox"/> VENT OR FLARE</div> <div><input type="checkbox"/> SI TA STATUS EXTENSION</div> <div><input type="checkbox"/> OTHER</div> <div><input type="checkbox"/> CASING REPAIR</div> <div><input type="checkbox"/> CHANGE WELL NAME</div> <div><input type="checkbox"/> CONVERT WELL TYPE</div> <div><input type="checkbox"/> NEW CONSTRUCTION</div> <div><input type="checkbox"/> PLUG BACK</div> <div><input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION</div> <div><input type="checkbox"/> TEMPORARY ABANDON</div> <div><input type="checkbox"/> WATER DISPOSAL</div> <div><input type="checkbox"/> APD EXTENSION</div> <div>OTHER: </div>	
<div>12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.</div> <div>Completion activity report, 5/21/09-5/28/09, no activity from 3/20-5/20.</div> <div>Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY May 28, 2009</div>			
<div>NAME (PLEASE PRINT)</div> <div>Tracey Fallang</div>		<div>PHONE NUMBER</div> <div>303 312-8134</div>	
<div>SIGNATURE</div> <div>N/A</div>		<div>TITLE</div> <div>Regulatory Analyst</div>	
		<div>DATE</div> <div>5/28/2009</div>	

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING		FORM 9			
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.		5. LEASE DESIGNATION AND SERIAL NUMBER: UTU-08107			
1. TYPE OF WELL Gas Well		6. IF INDIAN, ALLOTTEE OR TRIBE NAME:			
2. NAME OF OPERATOR: BILL BARRETT CORP		7. UNIT or CA AGREEMENT NAME: PETERS POINT			
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300 , Denver, CO, 80202		8. WELL NAME and NUMBER: PPU FED 9-27D-12-16			
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1050 FSL 0790 FEL QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SESE Section: 27 Township: 12.0S Range: 16.0E Meridian: S		9. API NUMBER: 43007314110000			
PHONE NUMBER: 303 312-8128 Ext		9. FIELD and POOL or WILDCAT: PETER'S POINT			
COUNTY: CARBON		STATE: UTAH			
11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA					
TYPE OF SUBMISSION	TYPE OF ACTION				
<input checked="" type="checkbox"/> NOTICE OF INTENT Approximate date work will start: 5/30/2009 <input type="checkbox"/> SUBSEQUENT REPORT Date of Work Completion: <input type="checkbox"/> SPUD REPORT Date of Spud: <input type="checkbox"/> DRILLING REPORT Report Date:	<table style="width: 100%; border: none;"> <tr> <td style="width: 33%; vertical-align: top;"> <input type="checkbox"/> ACIDIZE <input type="checkbox"/> CHANGE TO PREVIOUS PLANS <input type="checkbox"/> CHANGE WELL STATUS <input type="checkbox"/> DEEPEN <input type="checkbox"/> OPERATOR CHANGE <input type="checkbox"/> PRODUCTION START OR RESUME <input type="checkbox"/> REPERFORATE CURRENT FORMATION <input type="checkbox"/> TUBING REPAIR <input type="checkbox"/> WATER SHUTOFF <input type="checkbox"/> WILDCAT WELL DETERMINATION </td> <td style="width: 33%; vertical-align: top;"> <input type="checkbox"/> ALTER CASING <input type="checkbox"/> CHANGE TUBING <input checked="" type="checkbox"/> COMMINGLE PRODUCING FORMATIONS <input type="checkbox"/> FRACTURE TREAT <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> RECLAMATION OF WELL SITE <input type="checkbox"/> SIDETRACK TO REPAIR WELL <input type="checkbox"/> VENT OR FLARE <input type="checkbox"/> SI TA STATUS EXTENSION <input type="checkbox"/> OTHER </td> <td style="width: 33%; vertical-align: top;"> <input type="checkbox"/> CASING REPAIR <input type="checkbox"/> CHANGE WELL NAME <input type="checkbox"/> CONVERT WELL TYPE <input type="checkbox"/> NEW CONSTRUCTION <input type="checkbox"/> PLUG BACK <input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION <input type="checkbox"/> TEMPORARY ABANDON <input type="checkbox"/> WATER DISPOSAL <input type="checkbox"/> APD EXTENSION OTHER: </td> </tr> </table>		<input type="checkbox"/> ACIDIZE <input type="checkbox"/> CHANGE TO PREVIOUS PLANS <input type="checkbox"/> CHANGE WELL STATUS <input type="checkbox"/> DEEPEN <input type="checkbox"/> OPERATOR CHANGE <input type="checkbox"/> PRODUCTION START OR RESUME <input type="checkbox"/> REPERFORATE CURRENT FORMATION <input type="checkbox"/> TUBING REPAIR <input type="checkbox"/> WATER SHUTOFF <input type="checkbox"/> WILDCAT WELL DETERMINATION	<input type="checkbox"/> ALTER CASING <input type="checkbox"/> CHANGE TUBING <input checked="" type="checkbox"/> COMMINGLE PRODUCING FORMATIONS <input type="checkbox"/> FRACTURE TREAT <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> RECLAMATION OF WELL SITE <input type="checkbox"/> SIDETRACK TO REPAIR WELL <input type="checkbox"/> VENT OR FLARE <input type="checkbox"/> SI TA STATUS EXTENSION <input type="checkbox"/> OTHER	<input type="checkbox"/> CASING REPAIR <input type="checkbox"/> CHANGE WELL NAME <input type="checkbox"/> CONVERT WELL TYPE <input type="checkbox"/> NEW CONSTRUCTION <input type="checkbox"/> PLUG BACK <input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION <input type="checkbox"/> TEMPORARY ABANDON <input type="checkbox"/> WATER DISPOSAL <input type="checkbox"/> APD EXTENSION OTHER:
<input type="checkbox"/> ACIDIZE <input type="checkbox"/> CHANGE TO PREVIOUS PLANS <input type="checkbox"/> CHANGE WELL STATUS <input type="checkbox"/> DEEPEN <input type="checkbox"/> OPERATOR CHANGE <input type="checkbox"/> PRODUCTION START OR RESUME <input type="checkbox"/> REPERFORATE CURRENT FORMATION <input type="checkbox"/> TUBING REPAIR <input type="checkbox"/> WATER SHUTOFF <input type="checkbox"/> WILDCAT WELL DETERMINATION	<input type="checkbox"/> ALTER CASING <input type="checkbox"/> CHANGE TUBING <input checked="" type="checkbox"/> COMMINGLE PRODUCING FORMATIONS <input type="checkbox"/> FRACTURE TREAT <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> RECLAMATION OF WELL SITE <input type="checkbox"/> SIDETRACK TO REPAIR WELL <input type="checkbox"/> VENT OR FLARE <input type="checkbox"/> SI TA STATUS EXTENSION <input type="checkbox"/> OTHER	<input type="checkbox"/> CASING REPAIR <input type="checkbox"/> CHANGE WELL NAME <input type="checkbox"/> CONVERT WELL TYPE <input type="checkbox"/> NEW CONSTRUCTION <input type="checkbox"/> PLUG BACK <input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION <input type="checkbox"/> TEMPORARY ABANDON <input type="checkbox"/> WATER DISPOSAL <input type="checkbox"/> APD EXTENSION OTHER:			
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. In accordance with Utah Division of Oil, Gas, and Mining's Rule 649-3-22, Completion Into Two or More Pools, BBC is submitting this sundry to request commingling approval for the Wasatch and Mesaverde formations. Gas composition is similar across all formations. The pressure profile across the formations is similar and BBC does not anticipate any cross flow. Production is considered to be from one pool. In the event that allocation by zone or interval is required, BBC would use representative sampling obtained from production logs and allocate on a percentage basis by zone or interval. A letter and affidavit of notice is attached.					
Accepted by the Utah Division of Oil, Gas and Mining Date: June 22, 2009 By: 					
NAME (PLEASE PRINT) Tracey Fallang	PHONE NUMBER 303 312-8134	TITLE Regulatory Analyst			
SIGNATURE N/A	DATE 6/1/2009				

AFFIDAVIT

Affiant on oath swears that the following statements are true:


My Name is Douglas W. G. Gundry-White. I am a Senior Landman with Bill Barrett Corporation (BBC). BBC has submitted Sundry Notices to commingle production from the Wasatch and Mesaverde Formations in the Peters Point Unit Federal 9-27D-12-16 well, which is located in the NESE of Section 27, Township 12 South, Range 16 East. In compliance with the Utah OGM regulation R649-3-22, I have provided a copy of the Sundry Notices, by certified mail, to the owners as listed below of all contiguous oil and gas leases or drilling units overlying the pool.


State of Utah
School and Institutional Trust Lands Administration
675 East 500 South, Suite 500
Salt Lake City, UT 84102

Bureau of Land Management
440 W. 200 S., Suite 500
Salt Lake City, Utah 84101

Date: 10/11/2009

Affiant


Douglas W. G. Gundry-White



Bill Barrett Corporation

Well Location, Peters Point #9-27D
 Located as shown in the NWSE 1/4
 of Section 27, T12S-R16E Carbon County, Utah

Wells

- GAS
- 1/2 Mile Well Buffer

Surface

- FEDERAL SURFACE
- STATE SURFACE

Leased

- BILL BARRETT CORP.
- BILL BARRETT CORP (PENDING)
- EOG-75% / GASCO-25%





Bill Barrett Corporation

June 1, 2009

Utah Division of Oil, Gas & Mining
1594 W. North Temple, Suite 1210
Salt Lake City, UT 84116
Attention: Dustin Doucet

RE: Sundry Notices
Peter's Point Unit Federal 9-27D-12-16
NESE 27, T 13 S, R 16 E (BHL)
Carbon Co., UT

Dear Mr. Doucet:

Bill Barrett Corporation has submitted Sundry Notices to commingle production from the Wasatch and Mesaverde Formations in the Peters Point UF 9-27D well. We have enclosed herewith a copy of the Sundry Notices together with a plat showing the leases and wells in the area and affidavit confirming notice pursuant to the Utah OGM regulations.

Should you require additional information in this regard, please feel free to contact me at 303-312-8129. Your earliest attention to this matter is most appreciated.

BILL BARRETT CORPORATION

Doug Gundry-White
Senior Landman

Enclosures

1099 18TH STREET
SUITE 2300
DENVER, CO 80202
P 303.293.9100
F 303 291 0420



June 1, 2009

Bureau of Land Management
440 West 200 South, Suite 500
Salt Lake City, Utah 84101

Certified Mail 7008 1830 0000 5160 8478

RE: Sundry Notices
Peters Point Unit Federal 9-27D-12-16
NESE 27 T12S R16E
Carbon Co., UT

Gentlemen:

Bill Barrett Corporation has submitted Sundry Notices to commingle production from the Wasatch and Mesaverde Formations in the Peters Point UF 9-27D well. As required by the Utah OGM regulations R649-3-22, BBC has enclosed copies of the completed Sundry Notices.

Should you require additional information in this regard, please feel free to contact me at 303-312-8129.

BILL BARRETT CORPORATION



Doug Gundry-White
Senior Landman

Enclosures

1099 18TH STREET
SUITE 2300
DENVER, CO 80202
P 303 293.9100
F 303.291 0420



Bill Barrett Corporation

June 1, 2009

State of Utah
School and Institutional Trust Lands Administration
675 East 500 South, Suite 500
Salt Lake City, UT 84102

Certified Mail 7008 1830 0000 5160 8485


RE: Sundry Notices
Peters Point Unit Federal 9-27D-12-16
NESE 27 T12S R16E
Carbon Co., UT

Gentlemen:

Bill Barrett Corporation has submitted Sundry Notices to commingle production from the Wasatch and Mesaverde Formations in the Peters Point UF 9-27D well. As required by the Utah OGM regulations R649-3-22, BBC has enclosed copies of the completed Sundry Notices.

Should you require additional information in this regard, please feel free to contact me at 303-312-8129.

BILL BARRETT CORPORATION



Doug Gundry-White
Senior Landman

Enclosures

1099 18TH STREET
SUITE 2300
DENVER, CO 80202
P 303.293.9100
F 303.291.0420

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING		FORM 9
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.		5. LEASE DESIGNATION AND SERIAL NUMBER: UTU-08107
1. TYPE OF WELL Gas Well		6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
2. NAME OF OPERATOR: BILL BARRETT CORP		7. UNIT or CA AGREEMENT NAME: PETERS POINT
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300 , Denver, CO, 80202		8. WELL NAME and NUMBER: PPU FED 9-27D-12-16
PHONE NUMBER: 303 312-8128 Ext		9. API NUMBER: 43007314110000
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1050 FSL 0790 FEL QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SESE Section: 27 Township: 12.0S Range: 16.0E Meridian: S		9. FIELD and POOL or WILDCAT: PETER'S POINT
		COUNTY: CARBON
		STATE: UTAH
11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION	
<input type="checkbox"/> NOTICE OF INTENT Approximate date work will start:	<input type="checkbox"/> ACIDIZE	
<input checked="" type="checkbox"/> SUBSEQUENT REPORT Date of Work Completion: 5/30/2009	<input type="checkbox"/> CHANGE TO PREVIOUS PLANS	<input type="checkbox"/> ALTER CASING
<input type="checkbox"/> SPUD REPORT Date of Spud:	<input type="checkbox"/> CHANGE WELL STATUS	<input type="checkbox"/> CHANGE TUBING
<input type="checkbox"/> DRILLING REPORT Report Date:	<input type="checkbox"/> DEEPEN	<input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS
	<input type="checkbox"/> OPERATOR CHANGE	<input type="checkbox"/> FRACTURE TREAT
	<input checked="" type="checkbox"/> PRODUCTION START OR RESUME	<input type="checkbox"/> PLUG AND ABANDON
	<input type="checkbox"/> REPERFORATE CURRENT FORMATION	<input type="checkbox"/> RECLAMATION OF WELL SITE
	<input type="checkbox"/> TUBING REPAIR	<input type="checkbox"/> SIDETRACK TO REPAIR WELL
	<input type="checkbox"/> WATER SHUTOFF	<input type="checkbox"/> VENT OR FLARE
	<input type="checkbox"/> WILDCAT WELL DETERMINATION	<input type="checkbox"/> SI TA STATUS EXTENSION
		<input type="checkbox"/> OTHER
		OTHER:
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. This sundry is being submitted as notice that this well had first sales on 5/30/2009. <div style="text-align: right;">Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY June 01, 2009</div>		
NAME (PLEASE PRINT) Tracey Fallang	PHONE NUMBER 303 312-8134	TITLE Regulatory Analyst
SIGNATURE N/A	DATE 6/1/2009	

<div>STATE OF UTAH</div> <div>DEPARTMENT OF NATURAL RESOURCES</div> <div>DIVISION OF OIL, GAS, AND MINING</div>		<div>FORM 9</div> <div>5.LEASE DESIGNATION AND SERIAL NUMBER: UTU-08107</div>	
<div>SUNDRY NOTICES AND REPORTS ON WELLS</div> <div>Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.</div>		<div>6. IF INDIAN, ALLOTTEE OR TRIBE NAME:</div> <div>7.UNIT or CA AGREEMENT NAME: PETERS POINT</div>	
<div>1. TYPE OF WELL</div> <div>Gas Well</div>		<div>8. WELL NAME and NUMBER:</div> <div>PPU FED 9-27D-12-16</div>	
<div>2. NAME OF OPERATOR:</div> <div>BILL BARRETT CORP</div>		<div>9. API NUMBER:</div> <div>43007314110000</div>	
<div>3. ADDRESS OF OPERATOR:</div> <div>1099 18th Street Ste 2300 , Denver, CO, 80202</div>		<div>PHONE NUMBER:</div> <div>303 312-8128 Ext</div>	
<div>4. LOCATION OF WELL</div> <div>FOOTAGES AT SURFACE: 1050 FSL 0790 FEL</div> <div>QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SESE Section: 27 Township: 12.0S Range: 16.0E Meridian: S</div>		<div>9. FIELD and POOL or WILDCAT:</div> <div>PETER'S POINT</div>	
		<div>COUNTY:</div> <div>CARBON</div>	
		<div>STATE:</div> <div>UTAH</div>	
<div>11.</div> <div>CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA</div>			
<div>TYPE OF SUBMISSION</div>		<div>TYPE OF ACTION</div>	
<div><input type="checkbox"/> NOTICE OF INTENT</div> <div>Approximate date work will start:</div> <div><input type="checkbox"/> SUBSEQUENT REPORT</div> <div>Date of Work Completion:</div> <div><input type="checkbox"/> SPUD REPORT</div> <div>Date of Spud:</div> <div><input checked="" type="checkbox"/> DRILLING REPORT</div> <div>Report Date: 6/4/2009</div>		<div><input type="checkbox"/> ACIDIZE</div> <div><input type="checkbox"/> CHANGE TO PREVIOUS PLANS</div> <div><input type="checkbox"/> CHANGE WELL STATUS</div> <div><input type="checkbox"/> DEEPEN</div> <div><input type="checkbox"/> OPERATOR CHANGE</div> <div><input type="checkbox"/> PRODUCTION START OR RESUME</div> <div><input type="checkbox"/> REPERFORATE CURRENT FORMATION</div> <div><input type="checkbox"/> TUBING REPAIR</div> <div><input type="checkbox"/> WATER SHUTOFF</div> <div><input type="checkbox"/> WILDCAT WELL DETERMINATION</div> <div><input type="checkbox"/> ALTER CASING</div> <div><input type="checkbox"/> CHANGE TUBING</div> <div><input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS</div> <div><input type="checkbox"/> FRACTURE TREAT</div> <div><input type="checkbox"/> PLUG AND ABANDON</div> <div><input type="checkbox"/> RECLAMATION OF WELL SITE</div> <div><input type="checkbox"/> SIDETRACK TO REPAIR WELL</div> <div><input type="checkbox"/> VENT OR FLARE</div> <div><input type="checkbox"/> SI TA STATUS EXTENSION</div> <div><input type="checkbox"/> OTHER</div> <div><input type="checkbox"/> CASING REPAIR</div> <div><input type="checkbox"/> CHANGE WELL NAME</div> <div><input type="checkbox"/> CONVERT WELL TYPE</div> <div><input type="checkbox"/> NEW CONSTRUCTION</div> <div><input type="checkbox"/> PLUG BACK</div> <div><input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION</div> <div><input type="checkbox"/> TEMPORARY ABANDON</div> <div><input type="checkbox"/> WATER DISPOSAL</div> <div><input type="checkbox"/> APD EXTENSION</div> <div>OTHER: </div>	
<div>12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.</div> <div>Completion activity, 5/29-6/4/09</div> <div>Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY</div> <div>June 09, 2009</div>			
<div>NAME (PLEASE PRINT)</div> <div>Tracey Fallang</div>		<div>PHONE NUMBER</div> <div>303 312-8134</div>	
<div>SIGNATURE</div> <div>N/A</div>		<div>TITLE</div> <div>Regulatory Analyst</div>	
		<div>DATE</div> <div>6/9/2009</div>	

REPORT DATE 5/29/2009

FROM (TIME)	TO (TIME)	HOURS	CODE	CATEGORY	COMMENT
06:00 AM	12:00 PM	6.00	LOCL	Lock Wellhead and Secure	Shut in 2500 psi.
12:00 PM	1:30 PM	1.50	PFRT	Perforating	Schlumberger EI stage 7 North Horn. PU HES CFP with 10 ft. perf guns RIH correlate to short jt. run to setting depth set CFP @ 6530 ft. PU pressure up casing 500 psi over SI. Perforate @ 6427-6437, 3 JSPF, 120 phasing, .340 holes. POOH turn well over to frac.
1:30 PM	2:30 PM	1.00	FRAC	Frac. Job	HES frac stage 7 North Horn 60Q foam frac. Load and Break @ 4033 PSI @ 14.5 BPM. Avg. Wellhead Rate:23.6 BPM. Avg. Slurry Rate:11.8 BPM. Avg. CO2 10.7 Rate: BPM. Avg. Pressure: 4,731 PSI. Max. Wellhead Rate: 25.4 BPM. Max. Slurry Rate: 13.9 BPM. Max. CO2 Rate: 16.1 BPM. Max. Pressure:5,104 PSI. Total Fluid Pumped: 15,429 Gal. Total Sand in Formation:48,000 lb. (20/40 White) Linde CO2 Downhole: 62 tons. CO2 Cooldown: 5 tons. ISIP:3,568 PSI. Frac Gradient:0.99 psi/ft. Successfully flushed wellbore with 50Q foam 50 bbl over flush with 500 gal. fluid cap.
2:30 PM	4:12 PM	1.70	PFRT	Perforating	Schlumberger EI stage 8 North Horn. PU HES CFP with 10 ft. perf guns. RIH correlate to short jt. run to setting depth set CFP @ 5660 ft. PU pressure up CSG. Perforate @ 5580-5590, 3 JSPF, 120 phasing, .340 holes. POOH turn well over to frac.
4:12 PM	5:09 PM	0.95	FRAC	Frac. Job	HES frac stage 8 North Horn 60Q foam frac. Load and Break @ 4,838 PSI @ 15 BPM. Avg. Wellhead Rate:23.8 BPM. Avg. Slurry Rate: 11.7 BPM. Avg. CO2 Rate: 10.9 BPM. Avg. Pressure:4,537 PSI. Max. Wellhead Rate:25.5 BPM. Max. Slurry Rate:14 BPM. Max. CO2 Rate:15.1 BPM. Max. Pressure: 5,426 PSI. Total Fluid Pumped: 16.848 Gal. Total Sand in Formation: 56,000 lb.(20/40 White) Linde CO2 Downhole:69 tons. CO2 Cooldown: 4 tons. ISIP:2,881 PSI. Frac Gradient: 0.95 psi/ft. Successfully flushed wellbore with 50Q foam 50 bbl over flush with 500 gal.fluid cap.
5:09	6:09	1.00	PFRT	Perforating	Schlumberger EL stage 9 North Horn. PU HES CFP with 10 ft. perf

PM	PM				guns.RIH correlate to short jt. run to setting depth set CFP @ 5410 ft. PU pressure up CSG. Perforate @ 5316-5326 3JSPF, 120 phasing, .340 holes. POOH turn well over to frac.
6:09 PM	7:09 PM	1.00	FRAC	Frac. Job	HES frac stage 9 North Horn. Load and Break @ 4,148 PSI @ 17 BPM. Avg. Wellhead Rate: 28.4 BPM. Avg. Slurry Rate: 13.7 BPM. Avg. CO2 Rate: 13.3 BPM. Avg. Pressure: 4,289 PSI. Max. Wellhead Rate: 30.4 BPM. Max. Slurry Rate: 16.6 BPM. Max. CO2 Rate: 20.6 BPM. Max. Pressure: 4,709 PSI. Total Fluid Pumped: 17,801 Gal. Total Sand in Formation: 60,000 lb. (20/40 White Sand) Linde CO2 Downhole: 79 tons. CO2 Cooldown: 4 tons. ISIP: 2,989 PSI. Frac Gradient: 1.00 psi/ft. Successfully flushed wellbore with 50Q foam 50 bbl over flush with 500 gal. fluid cap.
7:09 PM	8:09 PM	1.00	PFRT	Perforating	Schlumberger EL stage 10 M. Wasatch. PU HES CFP with 10 ft. perf guns. RIH correlate to short jt. run to setting depth set CFP @ 5200 ft. PU pressure up casing 500 psi over SI. Perforate @ 5113-5123, 3 JSPF, 120 phasing, .34 0 holes. POOH turn well over to frac.
8:09 PM	9:00 PM	0.85	FRAC	Frac. Job	HES frac stage 10 Middle Wasatch 60Q foam frac. Load and Break @ 3371 PSI @ 15 BPM. Avg. Wellhead Rate: 19.3 BPM. Avg. Slurry Rate: 9.4 BPM. Avg. CO2 Rate: 8.8 BPM. Avg. Pressure: 3,576 PSI. Max. Wellhead Rate: 21.5 BPM. Max Slurry Rate: 11.2 BPM Max. CO2 Rate: 12.8 BPM. Max. Pressure: 3,850 PSI. Total Fluid Pumped: 12,953 Gal. Total Sand in Formation: 44,000 lb. (20/40 White) Praxair CO2 Downhole: 55 tons. CO2 Cooldown: 6 tons. ISIP: 2,856 PSI. Frac Gradient: 0.99 psi/ft. Blender shut down at start of 4# sand stage. design was not in system treater did not input.pumped 4# sand Successfully flushed wellbore with 50Q foam 10 bbl over flush with 500 gal. fluid cap.
9:00 PM	06:00 AM	9.00	FBCK	Flowback Well	Shut in. Rig EL and HES iron off well. Move to 15-27D. Flow stages 1-10 through Opsco equipment

REPORT DATE 5/30/2009

FROM (TIME)	To (TIME)	HOURS	CODE	CATEGORY	COMMENT
06:00	12:00	6.00	FBCK	Flowback	Flow stages 1-10 through Opsco flow equipment. FCP: 1100 psi. on 42

AM	PM			Well	/64 ck. recovered 396 bbl in 14 hours avg. of 28.2 BPH. CO2 40%. Gas rate: 4,522 MMCFD.
12:00 PM	5:30 PM	5.50	FBCK	Flowback Well	Flow stages 1-10 FCP: 11200 psi on 42 ck. CO2 14% gas rate 6.966 MMCFD 1/4 bbl oil per hour
5:30 PM	06:00 AM	12.50	FBCK	Flowback Well	Flow stages 1-10 through Opsco

REPORT DATE 5/31/2009

FROM (TIME)	TO (TIME)	HOURS	CODE	CATEGORY	COMMENT
06:00 AM	12:00 PM	6.00	FBCK	Flowback Well	Flow stages 1-10 through Opsco flow equipment. FCP: 1180 psi on 38/64 ck. recovered 189 bbl in 24 hours avg. of 7.87 BPH. CO2 9% gas rate of 6.592 MMCFD trace of oil
12:00 PM	5:00 PM	5.00	FBCK	Flowback Well	flow stages 1-10. shut in rig for sales. recovered 26 bbl in 5 hours. FCP: 1165 psi on 38 ck.
5:00 PM	06:00 AM	13.00	FBCK	Flowback Well	turn well over to sales. 30 choke gas rate of 4.300 MMCFD

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

tfallang
CONFIDENTIAL

FORM APPROVED
OMB No. 1004-0137
Expires: July 21, 2010

COPY

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.
UTU-08107

6. If Indian, Allottee or Tribe Name
N/A

SUBMIT IN TRIPLICATE - Other instructions on page 2.

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Bill Barrett Corporation

3a. Address
1099 18th Street, Suite 2300
Denver, CO 80202

3b. Phone No. (include area code)
303-312-8134

7. If Unit of CA/Agreement, Name and/or No.
Peter's Point/UTU-63014

8. Well Name and No.
Peter's Point Unit Federal 9-27D-12-16

9. API Well No.
43-007-31411

10. Field and Pool or Exploratory Area
Peter's Point/Wasatch-Mesaverde

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
SESE, 1050' FSL, 790' FEL
Sec. 27, T12S-R16E

11. Country or Parish, State
Carbon County, UT

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <u>Weekly Activity</u>
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	<u>Report</u>
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Completion activity report from 6/5/09 through 6/26/2009.

RECEIVED

JUL 02 2009

DIV. OF OIL, GAS & MINING

14. I hereby certify that the foregoing is true and correct.
Name (Printed/Typed)

Tracey Fallang

Title Regulatory Analyst

Signature

Tracey Fallang

Date 06/26/2009

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

COMPLETION SUMMARY

LOCATION INFORMATION

Field West
: Tavaputs

Well Name Peter's Point #9-27D-12-
: 16

API/LICENSE #
43007314110000

**SURFACE LEGAL
LOCATION**
SESE-27-12S-
16E-W26M

REPORT INFORMATION

Report # : 14

Report Date : 06/14/2009

OPERATIONS

A.M. Ops :

Ops Forecast : Continue well to sales R/D Coil equip.

24hr. Summary : R/U CTS Coil equip. Clean out

Well Status :

FROM (TIME)	TO (TIME)	HOURS	CODE	CATEGORY	COMMENT
06:00 AM	1:00 PM	7.00	WTST	Well Test	Continue flow well to sales R/U Opsco flow back equip to all 4-wells ready equip for clean out
1:00 PM	4:30 PM	3.50	SRIG	Rig Up/Down	CTS Coil equip arrived spot equip Pre-ops safety Meeting. R/U Coil Tubing equip. P/U W/ford Jars, Motor and 3 7/8" Mill. Pull test to 25,000 lbs, Pressure test equip to 5000 psi. Cont flow well to sales
4:30 PM	03:30 AM	11.00	CTU	Clean Out	RIH to 5,202' tag CFP #1 Drill out all 9-plug and clean-out to 7,636' (61' off csg shoe 83' F/bottom perf) pump sweep POOH w/coil and R/D CTS Equip. Continue flow through Opsco equip untill clean
03:30 AM	04:30 AM	1.00	FBCK	Flowback Well	Continue flow well untill clean through Opsco
04:30 AM	06:00 AM	1.50	WTST	Well Test	Well down sales line
TOTAL HOURS :	24.00				

RECEIVED

JUL 02 2009

DIV. OF OIL, GAS & MINING

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTtfallang
CONFIDENTIALFORM APPROVED
OMB NO. 1004-0137
Expires: July 31, 2010

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

- 1a. Type of Well ☐ Oil Well ☒ Gas Well ☐ Dry ☐ Other
b. Type of Completion: ☒ New Well ☐ Work Over ☐ Deepen ☐ Plug Back ☐ Diff. Resvr.,
Other: _____

2. Name of Operator
Bill Barrett Corporation3. Address 1099 18th Street, Suite 2300
Denver, CO 802023a. Phone No. (include area code)
303-312-8134

4. Location of Well (Report location clearly and in accordance with Federal requirements)*

At surface SESE, 1050' FSL, 790' FEL

At top prod. interval reported below NESE, 1902' FSL, 628' FEL, Sec. 27

At total depth NESE, 2035' FSL, 596' FEL, Sec. 27

14. Date Spudded
10/31/200815. Date T.D. Reached
11/27/200816. Date Completed 05/30/2009
☐ D & A ☒ Ready to Prod.17. Elevations (DF, RKB, RT, GL)*
7213' RKB18. Total Depth: MD 7697'
TVD 7556'19. Plug Back T.D.: MD 7516'
TVD 7375'20. Depth Bridge Plug Set: MD N/A
TVD21. Type Electric & Other Mechanical Logs Run (Submit copy of each)
Halliburton Triple Combo and Radial Sector Bond Log; Mudlog22. Was well cored? ☒ No ☐ Yes (Submit analysis)
Was DST run? ☒ No ☐ Yes (Submit report)
Directional Survey? ☐ No ☒ Yes (Submit copy)

23. Casing and Liner Record (Report all strings set in well)

Hole Size	Size/Grade	Wt. (#/ft.)	Top (MD)	Bottom (MD)	Stage Cement Depth	No. of Sks. & Type of Cement	Slurry Vol. (BBL)	Cement Top*	Amount Pulled
20"	16" H40	65#	0	40'		grout cement		Surface	0 lbs
12 1/4"	9 5/8" J-55	36#	0	1031'		450 Prem	92 bbls	Surface	
8 3/4" & 7 7/8"	4 1/2" I-80	11.6#	0	7560'		1665 50/50 Poz	442 bbls	1080'	10,000 lbs

24. Tubing Record

Size	Depth Set (MD)	Packer Depth (MD)	Size	Depth Set (MD)	Packer Depth (MD)	Size	Depth Set (MD)	Packer Depth (MD)

25. Producing Intervals

Formation	Top	Bottom	Perforated Interval	Size	No. Holes	Perf. Status
A) Mesaverde	6894'	7523'	7513' - 7523'	0.34"	30	Open
B) Wasatch	5113'	6880'	7240' - 7270'	0.56"	30	Open
C)			7032' - 7072'	0.56"	30	Open
D)			6870' - 6914'	0.56"	30	Open

27. Acid, Fracture, Treatment, Cement Squeeze, etc.

Depth Interval	Amount and Type of Material
7513' - 7523'	Stage 1: 70% CO2 foam frac: 48 tons CO2; 222 bbls fluid; 25,974# 20/40 White sand
7240' - 7270'	Stage 2: 70% CO2 foam frac: 71 tons CO2; 316 bbls fluid; 17,400# 20/40 White sand
7032' - 7072'	Stage 3: 70% CO2 foam frac: 154 tons CO2; 583 bbls fluid; 107,900# 20/40 White sand
6870' - 6914'	Stage 4: 70% CO2 foam frac: 195 tons CO2; 710 bbls fluid; 139,400# 20/40 White sand

28. Production - Interval A

Date First Produced	Test Date	Hours Tested	Test Production	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method
05/28/09	5/29/09	24	→	0	3,171	293			Flowing
Choke Size	Tbg. Press. Flwg. SI	Csg. Press.	24 Hr. Rate	Oil BBL	Gas MCF	Water BBL	Gas/Oil Ratio	Well Status	
38/64		1210	→	0	3,171	293		Producing	

28a. Production - Interval B

Date First Produced	Test Date	Hours Tested	Test Production	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method
			→						
Choke Size	Tbg. Press. Flwg. SI	Csg. Press.	24 Hr. Rate	Oil BBL	Gas MCF	Water BBL	Gas/Oil Ratio	Well Status	
			→						

*(See instructions and spaces for additional data on page 2)

RECEIVED
JUL 13 2009

DIV. OF OIL, GAS & MINING

28b. Production - Interval C

Date First Produced	Test Date	Hours Tested	Test Production →	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method
Choke Size	Tbg. Press. Flwg. SI	Csg. Press.	24 Hr. Rate →	Oil BBL	Gas MCF	Water BBL	Gas/Oil Ratio	Well Status	

28c. Production - Interval D

Date First Produced	Test Date	Hours Tested	Test Production →	Oil BBL	Gas MCF	Water BBL	Oil Gravity Corr. API	Gas Gravity	Production Method
Choke Size	Tbg. Press. Flwg. SI	Csg. Press.	24 Hr. Rate →	Oil BBL	Gas MCF	Water BBL	Gas/Oil Ratio	Well Status	

29. Disposition of Gas (Solid, used for fuel, vented, etc.)

Sold

30. Summary of Porous Zones (Include Aquifers):

Show all important zones of porosity and contents thereof. Cored intervals and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures and recoveries.

31. Formation (Log) Markers

Formation	Top	Bottom	Descriptions, Contents, etc.	Name	Top
					Meas. Depth
				Wasatch North Horn	3293' 5281'
				Dark Canyon Price River	6887' 7087'
				TD	7697'

32. Additional remarks (include plugging procedure):

Copies of logs previously submitted under separate cover. In the event log copies were not received, please contact Jim Kinser at 303-312-8163.

7 7/8" hole size started at 7008'.

33. Indicate which items have been attached by placing a check in the appropriate boxes:

- ☐ Electrical/Mechanical Logs (1 full set req'd.)
 ☐ Geologic Report
 ☐ DST Report
 ☒ Directional Survey
- ☐ Sundry Notice for plugging and cement verification
 ☐ Core Analysis
 ☐ Other:

34. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records (see attached instructions)*

Name (please print) Tracey Fallang

Title Regulatory Analyst

Signature

Date

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 3)

(Form 3160-4, page 2)

Peter's Point Unit Federal #9-27D-12-16 Report Continued

26. PERFORATION RECORD (cont.)					27. ACID, FRACTURE, TREATMENT, CEMENT SQUEEZE, ETC. (cont.)							
INTERVAL (Top/Bot-MD)		SIZE	NO. HOLES	PERFORATION STATUS	AMOUNT AND TYPE OF MATERIAL							
6733'	6743'	0.34"	30	Open	Stg 5	70% CO2 foam frac	80	tons CO2	444	bbls total fluid	64,000#	20/40 White Sand
6607'	6656'	0.34"	30	Open	Stg 6	60% CO2 foam frac	69	tons CO2	404	bbls total fluid	52,000#	20/40 White Sand
6427'	6437'	0.34"	30	Open	Stg 7	60% CO2 foam frac	62	tons CO2	367	bbls total fluid	48,000#	20/40 White Sand
5580'	5590'	0.34"	30	Open	Stg 8	60% CO2 foam frac	69	tons CO2	401	bbls total fluid	56,000#	20/40 White Sand
5316'	5326'	0.34"	30	Open	Stg 9	60% CO2 foam frac	79	tons CO2	424	bbls total fluid	60,000#	20/40 White Sand
5113'	5123'	0.34"	30	Open	Stg 10	60% CO2 foam frac	55	tons CO2	308	bbls total fluid	44,000#	20/40 White Sand

*Depth intervals for frac information same as perforation record intervals.



Well Name: Peter's Point #9-27D-12-16

API/UWI 43007314110000	Surface Legal Location SESE-27-12S-16E-W26M	Field Name West Tavaputs	State/Province UT	Well Configuration Type Deviated
Ground Elevation (ft) 7,196.00	KB Elevation (ft) 17.00	Spud Date 11/20/2008	Rig Release Date	

Wellbore Name Main Hole	Parent Wellbore	Kick Off Depth (ftKB)	Vertical Section Direction (°)
Date	Definitive? No	Description Survey	Proposed? No
MD Tie In (ftKB)	TVD Tie In (ftKB)	Inclination Tie In (°)	Azimuth Tie In (°)
		NSTie In (ft)	EW Tie In (ft)

Survey Data

Date	MD (ftKB)	Incl (°)	Azm (°)	TVD (ftKB)	VS (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Method	Survey Company
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		WEATHERFORD
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		GYRODATA
	100.00	0.21	75.14	100.00	0.08	0.05	0.18	0.00		WEATHERFORD
	100.00	0.21	75.14	100.00	0.08	0.05	0.18	0.00		WEATHERFORD
	200.00	0.26	76.80	200.00	0.25	0.15	0.58	0.00		WEATHERFORD
	200.00	0.26	76.80	200.00	0.25	0.15	0.58	0.00		GYRODATA
	300.00	0.28	87.28	300.00	0.41	0.21	1.04	0.00		WEATHERFORD
	300.00	0.28	87.28	300.00	0.41	0.21	1.04	0.00		GYRODATA
	400.00	0.43	64.49	400.00	0.69	0.38	1.62	0.00		WEATHERFORD
	400.00	0.43	64.49	400.00	0.69	0.38	1.62	0.00		GYRODATA
	500.00	0.50	62.41	499.99	1.19	0.75	2.35	0.00		WEATHERFORD
	500.00	0.50	62.41	499.99	1.19	0.75	2.35	0.00		GYRODATA
	600.00	0.50	83.69	599.99	1.59	1.00	3.17	0.00		GYRODATA
	600.00	0.50	83.69	599.99	1.59	1.00	3.17	0.00		WEATHERFORD
	700.00	0.46	73.89	699.99	1.91	1.16	3.99	0.00		GYRODATA
	700.00	0.46	73.89	699.99	1.91	1.16	3.99	0.00		WEATHERFORD
	800.00	0.46	87.51	799.98	2.18	1.28	4.77	0.00		WEATHERFORD
	800.00	0.46	87.51	799.98	2.18	1.28	4.77	0.00		GYRODATA
	900.00	0.35	94.17	899.98	2.32	1.28	5.48	0.00		GYRODATA
	900.00	0.35	94.17	899.99	0.33	-0.20	2.74	0.00		WEATHERFORD
	1,098.00	0.63	189.37	1,097.98	-0.68	-1.32	3.17	0.00		WEATHERFORD
	1,194.00	1.85	106.01	1,193.96	-1.34	-2.27	4.57	0.00		WEATHERFORD
	1,291.00	2.04	92.77	1,290.90	-1.22	-2.78	7.80	0.00		WEATHERFORD
	1,386.00	2.11	91.08	1,385.84	-0.67	-2.90	11.24	0.00		WEATHERFORD
	1,482.00	1.63	53.40	1,468.80	105.32	104.33	15.28	0.00		WEATHERFORD
	1,579.00	1.75	22.15	1,565.76	107.79	106.53	16.94	0.00		WEATHERFORD
	1,675.00	1.94	18.15	1,661.71	110.84	109.43	18.00	0.00		WEATHERFORD
	1,771.00	1.81	22.28	1,757.65	113.94	112.38	19.08	0.00		WEATHERFORD
	1,876.00	1.81	21.19	1,862.60	117.20	115.46	20.31	0.00		WEATHERFORD
	1,963.00	1.75	16.90	1,949.56	119.88	118.01	21.19	0.00		WEATHERFORD
	2,060.00	3.94	3.40	2,046.42	124.65	122.75	21.82	0.00		WEATHERFORD
	2,155.00	7.25	8.90	2,140.93	133.88	131.93	22.94	0.00		WEATHERFORD
	2,252.00	9.81	10.28	2,229.11	220.66	219.28	28.59	0.00		WEATHERFORD
	2,348.00	11.75	7.53	2,323.40	238.60	237.01	31.33	0.00		WEATHERFORD
	2,444.00	13.44	4.78	2,424.82	185.48	183.42	28.56	0.00		WEATHERFORD
	2,541.00	16.19	4.40	2,518.57	210.11	208.13	30.54	0.00		WEATHERFORD
	2,637.00	18.31	5.78	2,610.23	238.41	236.48	33.08	0.00		WEATHERFORD
	2,733.00	20.38	6.65	2,700.80	270.09	268.09	36.54	0.00		WEATHERFORD
	2,829.00	22.19	8.15	2,790.24	304.86	302.64	41.04	0.00		WEATHERFORD
	2,925.00	22.06	7.90	2,892.13	239.83	234.71	49.41	0.00		WEATHERFORD
	3,021.00	22.00	7.53	2,981.12	275.78	270.39	54.24	0.00		WEATHERFORD
	3,117.00	21.00	6.78	3,070.44	310.87	305.30	58.63	0.00		WEATHERFORD
	3,214.00	21.81	8.40	3,160.75	346.20	340.38	63.31	0.00		WEATHERFORD
	3,310.00	21.19	8.53	3,250.07	381.35	375.18	68.49	0.00		WEATHERFORD
	3,406.00	20.78	7.93	3,339.70	415.68	409.21	73.42	0.00		WEATHERFORD
	3,502.00	21.21	11.15	3,429.32	450.05	443.11	79.12	0.00		WEATHERFORD
	3,598.00	20.81	11.03	3,518.94	484.47	476.89	85.74	0.00		WEATHERFORD
	3,694.00	20.13	10.90	3,608.88	518.04	509.85	92.13	0.00		WEATHERFORD
	3,790.00	19.31	10.15	3,699.25	550.43	541.69	98.05	0.00		WEATHERFORD
	3,886.00	18.56	10.90	3,790.05	581.58	572.32	103.74	0.00		WEATHERFORD
	3,982.00	18.31	10.53	3,881.12	611.93	602.15	109.38	0.00		WEATHERFORD
	4,078.00	17.19	12.03	3,972.55	641.20	630.85	115.09	0.00		WEATHERFORD
	4,174.00	16.80	10.25	4,064.35	669.25	658.38	120.52	0.00		WEATHERFORD
	4,270.00	14.81	13.15	4,156.71	695.39	683.98	125.78	0.00		WEATHERFORD



Well Name: Peter's Point #9-27D-12-16

API/UWI 43007314110000	Surface Legal Location SESE-27-12S-16E-W26M	Field Name West Tavaputs	State/Province UT	Well Configuration Type Deviated
Ground Elevation (ft) 7,196.00	KB Elevation (ft) 17.00	Spud Date 11/20/2008	Rig Release Date	

Survey Data

Date	MD (ftKB)	Incl (°)	Azm (°)	TVD (ftKB)	VS (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Method	Survey Company
	4,366.00	13.94	11.78	4,249.70	719.21	707.24	130.93	0.00		WEATHERFORD
	4,462.00	13.38	12.15	4,342.99	741.88	729.42	135.63	0.00		WEATHERFORD
	4,558.00	13.00	12.15	4,436.45	763.78	750.84	140.24	0.00		WEATHERFORD
	4,654.00	12.33	11.55	4,530.12	784.83	771.43	144.57	0.00		WEATHERFORD
	4,750.00	11.25	12.53	4,624.09	804.44	790.62	148.65	0.00		WEATHERFORD
	4,846.00	10.56	12.15	4,718.35	822.60	808.36	152.53	0.00		WEATHERFORD
	4,943.00	9.81	12.53	4,813.82	839.75	825.12	156.20	0.00		WEATHERFORD
	5,039.00	9.25	13.53	4,908.49	855.63	840.60	159.78	0.00		WEATHERFORD
	5,135.00	8.56	13.28	5,003.34	870.48	855.06	163.22	0.00		WEATHERFORD
	5,231.00	7.94	13.40	5,098.34	884.24	868.46	166.40	0.00		WEATHERFORD
	5,327.00	7.25	13.53	5,193.50	896.92	880.80	169.35	0.00		WEATHERFORD
	5,423.00	6.69	12.03	5,288.79	908.57	892.16	171.94	0.00		WEATHERFORD
	5,519.00	5.94	12.78	5,384.20	919.12	902.47	174.20	0.00		WEATHERFORD
	5,615.00	5.19	13.65	5,479.75	928.43	911.53	176.32	0.00		WEATHERFORD
	5,712.00	4.75	13.03	5,576.38	936.82	919.71	178.27	0.00		WEATHERFORD
	5,807.00	4.39	12.44	5,671.08	944.39	927.09	179.94	0.00		WEATHERFORD
	5,904.00	3.81	12.03	5,767.83	951.32	933.87	181.41	0.00		WEATHERFORD
	6,000.00	3.44	13.40	5,863.64	957.39	939.79	182.74	0.00		WEATHERFORD
	6,096.00	3.38	12.90	5,959.47	963.10	945.35	184.04	0.00		WEATHERFORD
	6,192.00	3.25	14.40	6,055.31	968.64	950.75	185.35	0.00		WEATHERFORD
	6,288.00	2.88	14.53	6,151.17	973.77	955.72	186.63	0.00		WEATHERFORD
	6,384.00	2.56	14.78	6,247.06	978.31	960.12	187.78	0.00		WEATHERFORD
	6,479.00	2.25	16.65	6,341.98	982.29	963.96	188.86	0.00		WEATHERFORD
	6,573.00	2.13	20.16	6,435.91	985.85	967.37	189.99	0.00		WEATHERFORD
	6,669.00	2.00	20.40	6,531.85	989.26	970.61	191.19	0.00		WEATHERFORD
	6,765.00	1.69	21.40	6,627.80	992.31	973.50	192.29	0.00		WEATHERFORD
	6,861.00	1.25	14.53	6,723.76	994.75	975.83	193.07	0.00		WEATHERFORD
	6,958.00	0.81	9.11	6,820.75	996.49	977.54	193.44	0.00		WEATHERFORD
	7,009.00	0.58	6.26	6,871.74	997.11	978.15	193.52	0.00		WEATHERFORD
	7,697.00	0.58	6.26	7,559.71	1,004.05	985.07	194.28	0.00		WEATHERFORD

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING		FORM 9
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.		5. LEASE DESIGNATION AND SERIAL NUMBER: UTU-08107
1. TYPE OF WELL Gas Well		6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
2. NAME OF OPERATOR: BILL BARRETT CORP		7. UNIT or CA AGREEMENT NAME: PETERS POINT
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300 , Denver, CO, 80202		8. WELL NAME and NUMBER: PPU FED 9-27D-12-16
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1050 FSL 0790 FEL QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SESE Section: 27 Township: 12.0S Range: 16.0E Meridian: S		9. API NUMBER: 43007314110000
PHONE NUMBER: 303 312-8128 Ext		9. FIELD and POOL or WILDCAT: PETER'S POINT
COUNTY: CARBON		STATE: UTAH
11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION	
<input type="checkbox"/> NOTICE OF INTENT Approximate date work will start:	<input type="checkbox"/> ACIDIZE	
<input checked="" type="checkbox"/> SUBSEQUENT REPORT Date of Work Completion: 7/23/2009	<input type="checkbox"/> ALTER CASING	
<input type="checkbox"/> SPUD REPORT Date of Spud:	<input type="checkbox"/> CASING REPAIR	
<input type="checkbox"/> DRILLING REPORT Report Date:	<input type="checkbox"/> CHANGE TO PREVIOUS PLANS	
	<input type="checkbox"/> CHANGE TUBING	
	<input type="checkbox"/> CHANGE WELL STATUS	
	<input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS	
	<input type="checkbox"/> DEEPEN	
	<input type="checkbox"/> FRACTURE TREAT	
	<input type="checkbox"/> OPERATOR CHANGE	
	<input type="checkbox"/> PLUG AND ABANDON	
	<input type="checkbox"/> PRODUCTION START OR RESUME	
	<input type="checkbox"/> RECLAMATION OF WELL SITE	
	<input type="checkbox"/> REPERFORATE CURRENT FORMATION	
	<input type="checkbox"/> SIDETRACK TO REPAIR WELL	
	<input type="checkbox"/> TUBING REPAIR	
	<input type="checkbox"/> VENT OR FLARE	
	<input type="checkbox"/> WATER SHUTOFF	
	<input type="checkbox"/> SI TA STATUS EXTENSION	
	<input type="checkbox"/> WILDCAT WELL DETERMINATION	
	<input checked="" type="checkbox"/> OTHER	
	OTHER: <input type="text" value="Tubing Landed"/>	
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. 2 3/8" tubing was landed in this well at 7532'.		
Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY August 03, 2009		
NAME (PLEASE PRINT) Tracey Fallang	PHONE NUMBER 303 312-8134	TITLE Regulatory Analyst
SIGNATURE N/A	DATE 7/31/2009	

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE – Other instructions on page 2.

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
Bill Barrett Corporation

3a. Address
1099 18th Street, Suite 2300, Denver, CO 80202

3b. Phone No. (include area code)
303-312-8134

7. If Unit of CA/Agreement, Name and/or No.
Prickly Pear Unit/UTU-79487

8. Well Name and No.
See Attached

9. API Well No.

10. Field and Pool or Exploratory Area

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

11. Country or Parish, State
Carbon County, UT

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other Off-lease Water
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Treatment of Prickly
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	Pear Unit Water

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomple horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recomple in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Bill Barrett Corporation (BBC) is submitting this sundry in accordance with Onshore Order No. 7, III.B.2.b, Disposal of Produced Water on State or Privately Owned Lands. BBC will be taking produced water and flowback water from federal and state leases (a map and list of these wells is attached) within the Prickly Pear unit, hauling it to a temporary, "pilot" water treatment facility on SITLA lands in Sec. 16, T12S-R15E where it will be treated and reused for completion operations for approximately 16 state wells. This water treatment and recycling process will be in operation from January through July of 2010 and if successful, there is the potential of this being a permanent facility.

BBC has attached the SITLA submittal information for your records.

If you have further questions, please contact me at 303-312-8134.

COPY

COA: Once received, please provide a copy of SITLA's approval letter.

14. I hereby certify that the foregoing is true and correct.

Name (Printed/Typed)
Tracey Fallang

Title Regulatory Analyst

Signature

Tracey Fallang

Date 01/14/2010

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Manny Hendricks

Petroleum Engineer

Title

Date

JAN 14 2010

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

PRICE FIELD OFFICE

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

UDOGM

WEST TAVAPUTS PILOT WATER TREATMENT FACILITY NESW, SECTION 16, T12S-R15E

This is being submitted as notification that Bill Barrett Corporation (BBC) will be setting a temporary "pilot" water treatment facility within existing disturbance (no surface-laid lines are proposed) at the Prickly Pear Unit State 11-16 location. This facility will test the ability for BBC to reuse and recycle Prickly Pear unit water for approximately 16 state wells in Section 16 which are to be completed in 2010. It would also reduce truck traffic through Harmon Canyon associated with water hauling by approximately 16 trucks per day. Wells on Prickly Pear mesa generate approximately 1000 barrels of water per day (BWPD) and each well completion will take approximately 1300 BWPD. Any additional water needed for completion will come from currently approved water sources. This pilot facility will be in operation from January through July of 2010 and if successful, BBC will discuss the potential of making the facility permanent.


The process description is listed below and attachments to this proposal include proposed facility diagrams and maps and spreadsheets which indicate Prickly Pear wells involved with the water treatment process.

PROCESS DESCRIPTION


BBC will use an electro-coagulation (EC) process which transmits an electrical current through the water between iron plates. Iron hydroxyl-oxide (IHO) is formed by the electrical current in the form of a floc which then adsorbs compounds in the water. Compounds bound to the IHO create larger floc/solids known as hematite. The hematite is then skimmed off and placed into a tank to be hauled off of to a state approved disposal facility and a pH buffer is added to the water to lower the pH for re-use.

The EC system will treat approximately 1000-1200 BWPD (including flow-back water) and will be stored in clean tanks adjacent to the system. There will be ten 450-bbl holding tanks (two inlet water and eight treated water), three 450-bbl weir (skim) tanks and the actual EC system. There will also be a small generator to power a pump on location to assist in keeping the water flowing through the system. The tank battery will be bermed and the berms will be constructed to contain at a minimum 120 percent of the storage capacity of the largest tank within the berm. Any load lines and valves will be placed inside the berm.

After completion operations have ceased within Section 16, water will once again be diverted back to BBC's permitted saltwater disposal well in Sec. 24, T12S-R14E or a request for a permanent facility may be filed.



STATE
 Prickly Pear U ST 11-16 (1841' FSL & 1985' FWL)
 Prickly Pear U ST 13A-16D (1859' FSL & 2016' FWL)
 Prickly Pear U ST 12-16D (1864' FSL & 2023' FWL)
 Prickly Pear U ST 12A-16D (1868' FSL & 2030' FWL)
 Prickly Pear U ST 15A-16D (1872' FSL & 2037' FWL)
 Prickly Pear U ST 10-16D (1877' FSL & 2043' FWL)
 Prickly Pear U ST 11A-16D (1881' FSL & 2050' FWL)



*Only those access and utility corridors constructed and/or applied for in this APD, are shown.

LEGEND — ROAD — PIPE SURFACE — PIPE BURIED * WELL LOCATION * SHUT IN WELL LOCATION ■ WELL DISTURBANCE ■ SEPARATORS ■ TANKS ■ PIT

**Environmental
Industrial
Services**
 Environmental & Engineering Consulting

31 North Main Street
 Helper, Utah 84526
 (435) 472-3814
 fax (435) 472-8780
 eisecc@preciscom.net

Total Road Length - 1176 ft
 Ave. Road Disturbance Total Width - 38 ft
 Ave. Road Disturbance Running Width - 30 ft
 Total Road Disturbance - 1.0 Acres
 Total Pipeline Length - 1153 ft
 Total Pipeline Disturbance - 0 Acres
 Total Pad Disturbance - 3.5 Acres



As-Built
 Bill Barrett Corporation

NESW, Sec. 16, T12S, R15E, SLB&M
 Carbon County, Utah

UWI/API	Well	Status
430071604500	1-GOVT PCKRL	GAS
430071654200	SC 1-STONE CABIN	GAS
430073001400	1-11-ST CAB-FED	GAS
430071501600	33-1A-CLAYBANK SPRIN	GAS
430073052200	16-15 (12S-15E)	GAS
430073001800	2-B-27-ST CAB FED	GAS
430071654200	SC 1-ST CAB UNIT	GAS
430073101800	36-06-12-15	GAS
430073082500	13-4 (12S-14E)	GAS
430073082800	21-2-12-15	GAS
430073082300	10-4-12-14	GAS
430073095400	7-25-12-15	GAS
430073093300	13-16-12-15	GAS
430073100800	5-13-12-14	GAS
430073094300	5-16-12-15	GAS
430073094500	7-16-12-15	GAS
430073094400	11-16-12-15	GAS
430073119300	15-18-12-15	GAS
430073098500	7-33D-12-15	GAS
430073128900	7-17D-12-15	GAS
430073086000	5-19-12-15	GAS
430073107300	13-23-12-15	GAS
430073119600	10-27-12-15	GAS
430073120600	1-20-12-15	GAS
430073118300	15-17-12-15	GAS
430073119800	7-20-12-15	GAS
430073116400	15-21-12-15	GAS
430073116600	13-21D-12-15	GAS
430073116500	7-28D-12-15	GAS
430073112100	3-28D-12-15	GAS
430073107500	3-26D-12-15	GAS
430073107400	1-27D-12-15	GAS
430073107600	15-22D-12-15	GAS
430073118700	3-22-12-15	GAS
430073118600	7-22D-12-15	GAS
430073118800	5-22D-12-15	GAS
430073135800	13-15D-12-15	GAS
430073119200	9-18D-12-15	GAS
430073118400	11-17D-12-15	GAS
430073119700	9-20D-12-15	GAS
430073119400	16-27D-12-15	GAS
430073119500	12-27D-12-15	GAS
430073118900	11-15D-12-15	GAS
430073125900	4-25D-12-15	GAS
430073126000	12-25D-12-15	GAS
430073128300	2-35-12-15	GAS
430073128500	4-35D-12-15	GAS
430073128400	10-26D-12-15	GAS
430073125700	11-18D-12-15	GAS
430073125800	11-20D-12-15	GAS
430073122600	2-36-12-15	GAS
430073122700	4-36-12-15	GAS
430073123800	13-22-12-15	GAS

UWI/API	Well	Status
430073123900	3-27D-12-15	GAS
430073123700	4-27D-12-15	GAS
430073124300	1-28-12-15	GAS
430073124200	5-27D-12-15	GAS
430073124400	8-28D-12-15	GAS
430073124100	9-28D-12-15	GAS
430073128700	9-17-12-15	GAS
430073129500	7-18D-12-15	GAS
430073129400	1-18D-12-15	GAS
430073124000	9-16-12-15	GAS
430073124500	1-16-12-15	GAS
430073136200	2-28D-12-15	GAS
430073139900	11-22D-12-15	GAS
430073136000	4-22D-12-15	GAS
430073140000	14-22D-12-15	GAS
430073139800	12-22D-12-15	GAS
430073136100	6-22D-12-15	GAS
430073141300	6-21D-12-15	GAS
430073141200	11-21D-12-15	GAS
430073141400	12-21D-12-15	GAS
430073142100	2-20D-12-15	GAS
430073141900	8-20D-12-15	GAS
430073135900	14-15D-12-15	GAS
430073145600	12-16D-12-15	GAS
430073139400	10-18D-12-15	GAS
430073128200	14-26D-12-15	GAS
430073128800	1-17D-12-15	GAS
430073129600	5-17D-12-15	GAS
430073131400	3-18D-12-15	GAS
430073131600	5-18D-12-15	GAS
430073131000	13-17D-12-15	GAS
430073130900	12-17D-12-15	GAS
430073131100	14-17D-12-15	GAS
430073131200	16-18D-12-15	GAS
430073132800	3-21D-12-15	GAS
430073131500	4-18-12-15	GAS
430073130800	8-17D-12-15	GAS
430073130700	10-17D-12-15	GAS
430073131300	8-18D-12-15	GAS
430073131700	6-18D-12-15	GAS
430073145900	10-16D-12-15	GAS
430073132100	16-17D-12-15	GAS
430073132400	14-16D-12-15	GAS
430073132900	4-21D-12-15	GAS
430073136400	5A-27D-12-15	GAS
430073136800	1A-28D-12-15	GAS
430073136300	16X-21D-12-15	GAS
430073140100	4A-27D-12-15	GAS
430073139300	14A-18D-12-15	GAS
430073139500	15A-18D-12-15	GAS
430073139600	16A-18D-12-15	GAS
430073145800	15A-16D-12-15	GAS
430073146100	13A-16D-12-15	GAS
430073146000	11A-16D-12-15	GAS

UWI/API	Well	Status
430073148000	5A-16D-12-15	LOC
430073148500	9A-16D-12-15	LOC
430073147900	4A-16D-12-15	LOC
430073148100	3A-16D-12-15	LOC
430073147700	6A-16D-12-15	LOC
430073148400	16A-16D-12-15	LOC
430073151600	13B-16D-12-15	LOC
430073095300	12-24-12-14	SWD
430073142200	7A-16D-12-15	WOC
430073142500	3-16D-12-15	WOC
430073145500	8-16D-12-15	WOC
430073142300	6-16D-12-15	WOC
430073132300	16-16D-12-15	WOC
430073142400	10A-16D-12-15	WOC
430073151500	14B-16D-12-15	WOC
430073132200	15-16D-12-15	WOC
430073147800	4-16D-12-15	WOC
430073151400	16B-16D-12-15	DRL

Status Legend


DRL	Currently Drilling
GAS	Currently Producing
LOC	2010 Location
SWD	Salt Water Disposal
WOC	Waiting on Completion

Yellow indicates state wells that will be completed in 2010 using treated Prickly Pear Unit water. Water could come from any of these wells to be used in treatment process and reused for state well completions.


Inlet

Weir Tanks/Treatment

Treated Water



Pump



2010 STATE WELL COMPLETIONS



Bill Barrett Corporation

Uinta Basin

West Tavaputs


Prickly Pear Section 16




WELL SYMBOLS
Active Drilling Well
Location
Waiting on Completion

By JA

January 11, 2010 12:19 PM





UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on page 2.

7. If Unit of CA/Agreement, Name and/or No.

Prickly Pear Unit UTA-79487
Peter's Point Unit UTA-63014

8. Well Name and No.
See Attached

9. API Well No.

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
Bill Barrett Corporation

3a. Address
1099 18th Street, Suite 2300, Denver, CO 80202

3b. Phone No. (include area code)
303-312-8134

10. Field and Pool or Exploratory Area

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

11. Country or Parish, State
Carbon County, UT

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other Off-lease Water Treatment
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Bill Barrett Corporation (BBC) is submitting this as an update to the previously submitted sundry dated 05/14/2010. BBC will be also be treating produced water from Peter's Point unit, in addition to Prickly Pear unit, for re-use for the state water use. BBC is also submitting a list and map of Peter's Point unit wells is attached.

If you have further questions, please contact me at 303-312-8134.

Accepted by the
Utah Division of
Oil, Gas and Mining
FOR RECORD ONLY

RECEIVED
FEB 16 2010

DIV. OF OIL, GAS & MINING

COA: Approval is granted to take the water produced by Peter's Point Federal wells to be treated by the temporary water treatment facility located on SI TLA lands in Sec. 16, T12S R15E through July 2010.

14. I hereby certify that the foregoing is true and correct.

Name (Printed/Typed)
Tracey Fallang

Title Regulatory Analyst

Signature

Tracey Fallang

Date 02/04/2010

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Manny Hernandez

Petroleum Engineer

Date

FEB 08 2010

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

PRICE FIELD OFFICE

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

UDOGM

COPY

UWI/API	LABEL	Status
430073007000	5-14-PETERS POINT	GAS
430073002300	9-PTRS PT UNIT	GAS
430071539300	4-PTRS PT UNIT	GAS
430071539100	2-PTRS PT UNIT	GAS
430073076100	36-2-PtrsPtFed	GAS
430073076200	36-3-PtrPtFed	GAS
430073076300	36-4-PtrsPtFed	GAS
430071021600	1-PETERS POINT UNIT	GAS
430071021600	1-PETERS POINT UNIT	GAS
430073098200	11-6-13-17	GAS
430073096500	16-35-12-16	GAS
430073131800	16-27-12-16	GAS
430073127900	8-34-12-16	GAS
430073127500	6-35D-12-16	GAS
430073129300	7-1D-13-16 Ultra Dee	GAS
430073100500	16-31D-12-17	GAS
430073100400	16-6D-13-17	GAS
430073101000	2-36D-12-16	GAS
430073100900	12-31D-12-17	GAS
430073101100	9-36-12-16	GAS
430073081000	4-31D-12-17	GAS
430073085900	6-7D-13-17 Deep	GAS
430073102400	8-35D-12-16	GAS
430073081200	16-26D-12-16	GAS
430073076400	14-25D-12-16	GAS
430073115800	2-12D-13-16 Deep	GAS
430073127700	14-26D-12-16	GAS
430073128100	6-34D-12-16	GAS
430073127200	6-36-12-16	GAS
430073127100	3-36-12-16	GAS
430073117500	12-36D-12-16	GAS
430073117400	10-36D-12-16	GAS
430073126100	15-6D-13-17 Deep	GAS
430073104900	4-12D-13-16 Deep ST	GAS
430073141100	9-27D-12-16	GAS
430073140900	11-27D-12-16	GAS
430073141000	15-27D-12-16	GAS
430073140600	10-26D-12-16	GAS
430073140400	15-26D-12-16	GAS
430073140700	11-26D-12-16	GAS
430073135200	13-25D-12-16	GAS
430073140300	13-26D-12-16	GAS
430073140800	12-26D-12-16	GAS
430073142700	1-34D-12-16	GAS
430073142800	7-34D-12-16	GAS
430073140500	3-35D-12-16	GAS
430073134500	2-35D-12-16	GAS
430073136500	1-35D-12-16	GAS
430073147400	10-35D-12-16	WOC
430073147600	9-35D-12-16	WOC
430073142900	5-35D-12-16	GAS


UWI/API	LABEL	Status
430073134700	4-35D-12-16	GAS
430073134600	7-35D-12-16	GAS
430073134800	7-36D-12-16	GAS
430073135000	5-36D-12-16	GAS
430073135100	15-25D-12-16	GAS
430073131900	10-27D-12-16	GAS
430073132600	2-7D-13-17 Deep	GAS
430073132000	2-34D-12-16	GAS
430073134900	11-36D-12-16	GAS
430073135300	4-36D-12-16	GAS

PETER'S POINT UNIT

Status Legend

GAS	Currently Producing
WOC	Waiting on Completion

Water could come from any of these GAS wells to be used in treatment process and reused for state completions.



WEST TAVAPUTS PILOT WATER TREATMENT FACILITY NESW, SECTION 16, T12S-R15E

This is being submitted as notification that Bill Barrett Corporation (BBC) will be setting a temporary "pilot" water treatment facility within existing disturbance (no surface-laid lines are proposed) at the Prickly Pear Unit State 11-16 location. This facility will test the ability for BBC to reuse and recycle Prickly Pear unit water for approximately 16 state wells in Section 16 which are to be completed in 2010. It would also reduce truck traffic through Harmon Canyon associated with water hauling by approximately 16 trucks per day. Wells on Prickly Pear mesa generate approximately 1000 barrels of water per day (BWPD) and each well completion will take approximately 1300 BWPD. Any additional water needed for completion will come from currently approved water sources. This pilot facility will be in operation from January through July of 2010 and if successful, BBC will discuss the potential of making the facility permanent.

The process description is listed below and attachments to this proposal include proposed facility diagrams and maps and spreadsheets which indicate Prickly Pear wells involved with the water treatment process.

PROCESS DESCRIPTION

BBC will use an electro-coagulation (EC) process which transmits an electrical current through the water between iron plates. Iron hydroxyl-oxide (IHO) is formed by the electrical current in the form of a floc which then adsorbs compounds in the water. Compounds bound to the IHO create larger floc/solids known as hematite. The hematite is then skimmed off and placed into a tank to be hauled off to a state approved disposal facility and a pH buffer is added to the water to lower the pH for re-use.

The EC system will treat approximately 1000-1200 BWPD (including flow-back water) and will be stored in clean tanks adjacent to the system. There will be ten 450-bbl holding tanks (two inlet water and eight treated water), three 450-bbl weir (skim) tanks and the actual EC system. There will also be a small generator to power a pump on location to assist in keeping the water flowing through the system. The tank battery will be bermed and the berms will be constructed to contain at a minimum 120 percent of the storage capacity of the largest tank within the berm. Any load lines and valves will be placed inside the berm.

After completion operations have ceased within Section 16, water will once again be diverted back to BBC's permitted saltwater disposal well in Sec. 24, T12S-R14E or a request for a permanent facility may be filed.

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING		FORM 9																														
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.		5. LEASE DESIGNATION AND SERIAL NUMBER: UTU-08107																														
1. TYPE OF WELL Gas Well		6. IF INDIAN, ALLOTTEE OR TRIBE NAME: 7. UNIT or CA AGREEMENT NAME: PETERS POINT																														
2. NAME OF OPERATOR: BILL BARRETT CORP		8. WELL NAME and NUMBER: PPU FED 9-27D-12-16																														
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300 , Denver, CO, 80202		9. API NUMBER: 43007314110000																														
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1050 FSL 0790 FEL QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SESE Section: 27 Township: 12.0S Range: 16.0E Meridian: S		9. FIELD and POOL or WILDCAT: PETERS POINT																														
11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		COUNTY: CARBON																														
STATE: UTAH																																
TYPE OF SUBMISSION <input checked="" type="checkbox"/> NOTICE OF INTENT Approximate date work will start: 2/27/2012 <input type="checkbox"/> SUBSEQUENT REPORT Date of Work Completion: <input type="checkbox"/> SPUD REPORT Date of Spud: <input type="checkbox"/> DRILLING REPORT Report Date:	TYPE OF ACTION <table style="width: 100%;"> <tr> <td><input type="checkbox"/> ACIDIZE</td> <td><input type="checkbox"/> ALTER CASING</td> <td><input type="checkbox"/> CASING REPAIR</td> </tr> <tr> <td><input type="checkbox"/> CHANGE TO PREVIOUS PLANS</td> <td><input type="checkbox"/> CHANGE TUBING</td> <td><input type="checkbox"/> CHANGE WELL NAME</td> </tr> <tr> <td><input type="checkbox"/> CHANGE WELL STATUS</td> <td><input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS</td> <td><input type="checkbox"/> CONVERT WELL TYPE</td> </tr> <tr> <td><input type="checkbox"/> DEEPEN</td> <td><input type="checkbox"/> FRACTURE TREAT</td> <td><input type="checkbox"/> NEW CONSTRUCTION</td> </tr> <tr> <td><input type="checkbox"/> OPERATOR CHANGE</td> <td><input type="checkbox"/> PLUG AND ABANDON</td> <td><input type="checkbox"/> PLUG BACK</td> </tr> <tr> <td><input type="checkbox"/> PRODUCTION START OR RESUME</td> <td><input type="checkbox"/> RECLAMATION OF WELL SITE</td> <td><input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION</td> </tr> <tr> <td><input type="checkbox"/> REPERFORATE CURRENT FORMATION</td> <td><input type="checkbox"/> SIDETRACK TO REPAIR WELL</td> <td><input type="checkbox"/> TEMPORARY ABANDON</td> </tr> <tr> <td><input type="checkbox"/> TUBING REPAIR</td> <td><input type="checkbox"/> VENT OR FLARE</td> <td><input type="checkbox"/> WATER DISPOSAL</td> </tr> <tr> <td><input type="checkbox"/> WATER SHUTOFF</td> <td><input type="checkbox"/> SI TA STATUS EXTENSION</td> <td><input type="checkbox"/> APD EXTENSION</td> </tr> <tr> <td><input type="checkbox"/> WILDCAT WELL DETERMINATION</td> <td><input checked="" type="checkbox"/> OTHER</td> <td>OTHER: <input type="text" value="lower tubing"/></td> </tr> </table>		<input type="checkbox"/> ACIDIZE	<input type="checkbox"/> ALTER CASING	<input type="checkbox"/> CASING REPAIR	<input type="checkbox"/> CHANGE TO PREVIOUS PLANS	<input type="checkbox"/> CHANGE TUBING	<input type="checkbox"/> CHANGE WELL NAME	<input type="checkbox"/> CHANGE WELL STATUS	<input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS	<input type="checkbox"/> CONVERT WELL TYPE	<input type="checkbox"/> DEEPEN	<input type="checkbox"/> FRACTURE TREAT	<input type="checkbox"/> NEW CONSTRUCTION	<input type="checkbox"/> OPERATOR CHANGE	<input type="checkbox"/> PLUG AND ABANDON	<input type="checkbox"/> PLUG BACK	<input type="checkbox"/> PRODUCTION START OR RESUME	<input type="checkbox"/> RECLAMATION OF WELL SITE	<input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION	<input type="checkbox"/> REPERFORATE CURRENT FORMATION	<input type="checkbox"/> SIDETRACK TO REPAIR WELL	<input type="checkbox"/> TEMPORARY ABANDON	<input type="checkbox"/> TUBING REPAIR	<input type="checkbox"/> VENT OR FLARE	<input type="checkbox"/> WATER DISPOSAL	<input type="checkbox"/> WATER SHUTOFF	<input type="checkbox"/> SI TA STATUS EXTENSION	<input type="checkbox"/> APD EXTENSION	<input type="checkbox"/> WILDCAT WELL DETERMINATION	<input checked="" type="checkbox"/> OTHER	OTHER: <input type="text" value="lower tubing"/>
<input type="checkbox"/> ACIDIZE	<input type="checkbox"/> ALTER CASING	<input type="checkbox"/> CASING REPAIR																														
<input type="checkbox"/> CHANGE TO PREVIOUS PLANS	<input type="checkbox"/> CHANGE TUBING	<input type="checkbox"/> CHANGE WELL NAME																														
<input type="checkbox"/> CHANGE WELL STATUS	<input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS	<input type="checkbox"/> CONVERT WELL TYPE																														
<input type="checkbox"/> DEEPEN	<input type="checkbox"/> FRACTURE TREAT	<input type="checkbox"/> NEW CONSTRUCTION																														
<input type="checkbox"/> OPERATOR CHANGE	<input type="checkbox"/> PLUG AND ABANDON	<input type="checkbox"/> PLUG BACK																														
<input type="checkbox"/> PRODUCTION START OR RESUME	<input type="checkbox"/> RECLAMATION OF WELL SITE	<input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION																														
<input type="checkbox"/> REPERFORATE CURRENT FORMATION	<input type="checkbox"/> SIDETRACK TO REPAIR WELL	<input type="checkbox"/> TEMPORARY ABANDON																														
<input type="checkbox"/> TUBING REPAIR	<input type="checkbox"/> VENT OR FLARE	<input type="checkbox"/> WATER DISPOSAL																														
<input type="checkbox"/> WATER SHUTOFF	<input type="checkbox"/> SI TA STATUS EXTENSION	<input type="checkbox"/> APD EXTENSION																														
<input type="checkbox"/> WILDCAT WELL DETERMINATION	<input checked="" type="checkbox"/> OTHER	OTHER: <input type="text" value="lower tubing"/>																														
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. BBC is proposing to lower the tubing on this well to enhance production. Tubing is currently set at 5565'. Please contact Brian Hilgers with questions at 303.312.8183.																																
Accepted by the Utah Division of Oil, Gas and Mining Date: February 16, 2012 By: <u>Derek Quist</u>																																
NAME (PLEASE PRINT) Brady Riley		PHONE NUMBER 303 312-8115																														
SIGNATURE N/A		TITLE Permit Analyst																														
DATE 2/13/2012																																

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING		FORM 9
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.		5. LEASE DESIGNATION AND SERIAL NUMBER: UTU-08107
		6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
1. TYPE OF WELL Gas Well		7. UNIT or CA AGREEMENT NAME: PETERS POINT
2. NAME OF OPERATOR: BILL BARRETT CORP		8. WELL NAME and NUMBER: PPU FED 9-27D-12-16
3. ADDRESS OF OPERATOR: 1099 18th Street Ste 2300 , Denver, CO, 80202	PHONE NUMBER: 303 312-8164 Ext	9. API NUMBER: 43007314110000
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1050 FSL 0790 FEL QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: Qtr/Qtr: SESE Section: 27 Township: 12.0S Range: 16.0E Meridian: S		9. FIELD and POOL or WILDCAT: PETERS POINT
		COUNTY: CARBON
		STATE: UTAH

11.

CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION		
<input type="checkbox"/> NOTICE OF INTENT Approximate date work will start:	<input type="checkbox"/> ACIDIZE <input type="checkbox"/> CHANGE TO PREVIOUS PLANS <input type="checkbox"/> CHANGE WELL STATUS <input type="checkbox"/> DEEPEN <input type="checkbox"/> OPERATOR CHANGE <input type="checkbox"/> PRODUCTION START OR RESUME <input type="checkbox"/> REPERFORATE CURRENT FORMATION <input type="checkbox"/> TUBING REPAIR <input type="checkbox"/> WATER SHUTOFF <input type="checkbox"/> WILDCAT WELL DETERMINATION	<input type="checkbox"/> ALTER CASING <input checked="" type="checkbox"/> CHANGE TUBING <input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS <input type="checkbox"/> FRACTURE TREAT <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> RECLAMATION OF WELL SITE <input type="checkbox"/> SIDETRACK TO REPAIR WELL <input type="checkbox"/> VENT OR FLARE <input type="checkbox"/> SI TA STATUS EXTENSION <input type="checkbox"/> OTHER	<input type="checkbox"/> CASING REPAIR <input type="checkbox"/> CHANGE WELL NAME <input type="checkbox"/> CONVERT WELL TYPE <input type="checkbox"/> NEW CONSTRUCTION <input type="checkbox"/> PLUG BACK <input type="checkbox"/> RECOMPLETE DIFFERENT FORMATION <input type="checkbox"/> TEMPORARY ABANDON <input type="checkbox"/> WATER DISPOSAL <input type="checkbox"/> APD EXTENSION OTHER: <input style="width: 100px;" type="text"/>
<input checked="" type="checkbox"/> SUBSEQUENT REPORT Date of Work Completion: 4/1/2012			
<input type="checkbox"/> SPUD REPORT Date of Spud:			
<input type="checkbox"/> DRILLING REPORT Report Date:			

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

Attached to this sundry are the procedures that took place to lower the tubing on this well from 3/29/2012 through 4/1/2012. Please contact Brady Riley at 303-312-8115 with questions.

Accepted by the
Utah Division of
Oil, Gas and Mining
FOR RECORD ONLY
 April 18, 2012

NAME (PLEASE PRINT) Brady Riley	PHONE NUMBER 303 312-8115	TITLE Permit Analyst
SIGNATURE N/A		DATE 4/12/2012

**Peter's Point #9-27D-12-16 3/29/2012 00:00 - 3/30/2012 00:00**

API/UWI 43-007-31411	State/Province UT	County CARBON	Field Name West Tavaputs	Well Status Released for Work	Total Depth (ftKB) 7,697.0	Primary Job Type Workover
-------------------------	----------------------	------------------	-----------------------------	----------------------------------	-------------------------------	------------------------------

Time Log

Start Time	Dur (hr)	End Time	Code	Category	Com
00:00	3.50	03:30	RMOV	Rig Move	RIG MOVE F/ 12-26D TO 9-27D, SPOT IN RIG & EQUIPMENT, READY TO PULL CVR IN AM
03:30	20.50	00:00	CTRL	Crew Travel	CREW TRAVEL, WELL FLOWING TO SALES

Peter's Point #9-27D-12-16 3/30/2012 00:00 - 3/31/2012 00:00

API/UWI 43-007-31411	State/Province UT	County CARBON	Field Name West Tavaputs	Well Status Released for Work	Total Depth (ftKB) 7,697.0	Primary Job Type Workover
-------------------------	----------------------	------------------	-----------------------------	----------------------------------	-------------------------------	------------------------------

Time Log

Start Time	Dur (hr)	End Time	Code	Category	Com
00:00	1.00	01:00	CTRL	Crew Travel	CREW TRAVEL, SAFETY MEETING, TFP 250, SICP 315
01:00	2.00	03:00	SRIG	Rig Up/Down	SET 2 RIG ANCHORS & TEST ALL ON LOCATION, RIG UP RIG
03:00	1.00	04:00	BOPI	Install BOP's	PUMP 5 BBL KILL ON TBG, ND WELL HEAD, NUBOP'S, RU FLOOR
04:00	5.00	09:00	PULT	Pull Tubing	PUMP KILL ON CSG, PULL TBG HANGER, RU SPOOLER, POOH W/ JTS 2 3/8 TBG & CAP STRING, PULL CAP STRING INSIDE 2 7/8 UF VERY TIGHT, CAP STRING PARTED, RIG DOWN SPOOLER
09:00	2.50	11:30	PULT	Pull Tubing	LAY DOWN 62 JTS 2 7/8 UF W/ CAP STRING INSIDE, STUCK IN BOTTOM JT
11:30	0.50	12:00	GOP	General Operations	SECURE WELL, TURN CSG TO SALES, SDFN
12:00	12.00	00:00	CTRL	Crew Travel	CREW TRAVEL

Peter's Point #9-27D-12-16 3/31/2012 00:00 - 4/1/2012 00:00

API/UWI 43-007-31411	State/Province UT	County CARBON	Field Name West Tavaputs	Well Status Released for Work	Total Depth (ftKB) 7,697.0	Primary Job Type Workover
-------------------------	----------------------	------------------	-----------------------------	----------------------------------	-------------------------------	------------------------------

Time Log

Start Time	Dur (hr)	End Time	Code	Category	Com
00:00	1.00	01:00	CTRL	Crew Travel	CREW TRAVEL, SAFETY MEETING, CFP
01:00	1.00	02:00	GOP	General Operations	CLEAN UP CUT CAP STRING, MOVE 2 7/8 DS F/ RACKS, LOAD NEW TBG ON RACKS & TALLY
02:00	2.50	04:30	RUTB	Run Tubing	MU MSC, 1 JT 2 3/8, XN NIPPLE & RIH TALLYING TO LAND TBG @ 6414.68 W/ 204 JTS 2 3/8 L80 TOTAL IN WELL
04:30	1.00	05:30	IWHD	Install Wellhead	RD FLOOR, ND BOP'S, NU WELL HEAD, SECURE WELL, TURN TBG TO SALES
05:30	1.00	06:30	SRIG	Rig Up/Down	RD RIG
06:30	17.50	00:00	FBCK	Flowback Well	TBG FLOWING TO SALES

Division of Oil, Gas and Mining
OPERATOR CHANGE WORKSHEET (for state use only)

ROUTING
CDW

X - Change of Operator (Well Sold)

Operator Name Change/Merger

The operator of the well(s) listed below has changed, effective:

1/1/2014

FROM: (Old Operator):

N2165-Bill Barrett Corporation
 1099 18th Street, Suite 230
 Denver, CO 80202

Phone: 1 (303) 312-8134

TO: (New Operator):

N4040-EnerVest Operating, LLC
 1001 Fannin Street, Suite 800
 Houston, TX 77002

Phone: 1 (713) 659-3500

CA No.

Unit:

Peter Point

WELL NAME	SEC	TWN	RNG	API NO	ENTITY NO	LEASE TYPE	WELL TYPE	WELL STATUS
See Attached List								

OPERATOR CHANGES DOCUMENTATION

Enter date after each listed item is completed

- (R649-8-10) Sundry or legal documentation was received from the **FORMER** operator on: 1/7/2014
- (R649-8-10) Sundry or legal documentation was received from the **NEW** operator on: 1/7/2014
- The new company was checked on the **Department of Commerce, Division of Corporations Database** on: 1/28/2014
- a. Is the new operator registered in the State of Utah: _____ Business Number: 8850806-0161
- 5a. (R649-9-2)Waste Management Plan has been received on: Not Yet
- 5b. Inspections of LA PA state/fee well sites complete on: Yes
- 5c. Reports current for Production/Disposition & Sundries on: 1/24/2014
- Federal and Indian Lease Wells:** The BLM and or the BIA has approved the merger, name change, or operator change for all wells listed on Federal or Indian leases on: BLM Not Yet BIA N/A
- Federal and Indian Units:**
The BLM or BIA has approved the successor of unit operator for wells listed on: Not Yet
- Federal and Indian Communization Agreements ("CA"):**
The BLM or BIA has approved the operator for all wells listed within a CA on: N/A
- Underground Injection Control ("UIC")** Division has approved UIC Form 5 Transfer of Authority to Inject, for the enhanced/secondary recovery unit/project for the water disposal well(s) listed on: Yes

DATA ENTRY:

- Changes entered in the **Oil and Gas Database** on: 1/28/2014
- Changes have been entered on the **Monthly Operator Change Spread Sheet** on: 1/28/2014
- Bond information entered in RBDMS on: 1/28/2014
- Fee/State wells attached to bond in RBDMS on: 1/28/2014
- Injection Projects to new operator in RBDMS on: 1/28/2014
- Receipt of Acceptance of Drilling Procedures for APD/New on: 1/7/2014
- Surface Agreement Sundry from **NEW** operator on Fee Surface wells received on: 1/7/2014

BOND VERIFICATION:

- Federal well(s) covered by Bond Number: RLB7886
- Indian well(s) covered by Bond Number: RLB7886
- a. (R649-3-1) The **NEW** operator of any state/fee well(s) listed covered by Bond Number B008371
- b. The **FORMER** operator has requested a release of liability from their bond on: N/A

LEASE INTEREST OWNER NOTIFICATION:

- (R649-2-10) The **NEW** operator of the fee wells has been contacted and informed by a letter from the Division of their responsibility to notify all interest owners of this change on: 1/28/2014

COMMENTS:

Bill Barrett Corporation (N2165) to EnerVest Operating, LLC (N4040)

Effective 1/1/2014

Peter Point Unit

Well Name	Sec	TWN	RNG	API Number	Entity	Mineral Lease	Surface Lease	Well Type	Well Status
PPU FED 11-34D-12-16	34	120S	160E	4300731465		Federal	Federal	GW	APD
PPU FED 10-34D-12-16	34	120S	160E	4300731469		Federal	Federal	GW	APD
PETERS POINT UF 15X-36D-12-16	36	120S	160E	4300750178		Federal	Federal	GW	APD
PETERS POINT UF 10-1D-13-16	36	120S	160E	4300750182		Federal	Federal	GW	APD
PETERS POINT UF 9-1D-13-16	36	120S	160E	4300750183		Federal	Federal	GW	APD
PPU FED 9-34D-12-16	34	120S	160E	4300731430	17225	Federal	Federal	GW	OPS
PPU FED 15-35D-12-16	35	120S	160E	4300731475	2470	Federal	Federal	GW	OPS
PETERS POINT U FED 12A-6D-13-17	31	120S	170E	4300750034	2470	Federal	Federal	GW	OPS
PETERS POINT U FED 11A-31D-12-17	31	120S	170E	4300750036	2470	Federal	Federal	GW	OPS
PETERS POINT U FED 9-6D-13-17	6	130S	170E	4300750120	2470	Federal	Federal	GW	OPS
PETERS POINT U FED 14-6D-13-17	6	130S	170E	4300750121	2470	Federal	Federal	GW	OPS
PETERS POINT U FED 15-6D-13-17	6	130S	170E	4300750122	2470	Federal	Federal	GW	OPS
PETERS POINT UF 2-7D-13-17	6	130S	170E	4300750149	2470	Federal	Federal	GW	OPS
PETERS POINT UF 1-7D-13-17	6	130S	170E	4300750150	2470	Federal	Federal	GW	OPS
PETERS POINT U FED 36-2	36	120S	160E	4300730761	2470	Federal	Federal	GW	P
PETERS POINT U FED 36-3	36	120S	160E	4300730762	2470	Federal	Federal	GW	P
PETERS POINT U FED 36-4	36	120S	160E	4300730763	2470	Federal	Federal	GW	P
PETERS POINT U FED 14-25D-12-16	36	120S	160E	4300730764	2470	Federal	Federal	GW	P
PETERS POINT U FED 4-31D-12-17	36	120S	160E	4300730810	2470	Federal	Federal	GW	P
PETERS POINT U FED 16-26D-12-16	36	120S	160E	4300730812	2470	Federal	Federal	GW	P
PETERS POINT U FED 6-7D-13-17	6	130S	170E	4300730859	14692	Federal	Federal	GW	P
PETERS POINT U FED 16-35	35	120S	160E	4300730965	2470	Federal	Federal	GW	P
PETERS POINT U FED 11-6-13-17	6	130S	170E	4300730982	2470	Federal	Federal	GW	P
PETERS POINT U FED 16-6D-13-17	6	130S	170E	4300731004	2470	Federal	Federal	GW	P
PETERS POINT U FED 16-31D-12-17	6	130S	170E	4300731005	2470	Federal	Federal	GW	P
PETERS POINT U FED 12-31D-12-17	36	120S	160E	4300731009	2470	Federal	Federal	GW	P
PETERS POINT U FED 2-36D-12-16	36	120S	160E	4300731010	2470	Federal	Federal	GW	P
PETERS POINT U FED 9-36-12-16	36	120S	160E	4300731011	2470	Federal	Federal	GW	P
PETERS POINT U FED 8-35D-12-16	36	120S	160E	4300731024	2470	Federal	Federal	GW	P
PETERS POINT U FED 4-12D-13-16	2	130S	160E	4300731049	14692	Federal	State	GW	P
PETERS POINT U FED 2-12D-13-16	6	130S	170E	4300731158	14692	Federal	Federal	GW	P
PETERS POINT U FED 10-36D-12-16	36	120S	160E	4300731174	2470	Federal	Federal	GW	P
PETERS POINT U FED 12-36D-12-16	36	120S	160E	4300731175	2470	Federal	Federal	GW	P
PPU FED 15-6D-13-17	6	130S	170E	4300731261	16103	Federal	Federal	GW	P
PP UF 3-36-12-16	36	120S	160E	4300731271	2470	Federal	Federal	GW	P
PP UF 6-36-12-16	36	120S	160E	4300731272	2470	Federal	Federal	GW	P
PPU FED 6-35D-12-16	35	120S	160E	4300731275	2470	Federal	Federal	GW	P
PPU FED 8-34-12-16	34	120S	160E	4300731279	2470	Federal	Federal	GW	P
PPU FED 6-34D-12-16	34	120S	160E	4300731281	2470	Federal	Federal	GW	P
PPU FED 7-1D-13-16 ULTRA DEEP	6	130S	170E	4300731293	14692	Federal	Federal	GW	P
PPU FED 16-27-12-16	27	120S	160E	4300731318	2470	Federal	Federal	GW	P
PPU FED 10-27D-12-16	27	120S	160E	4300731319	2470	Federal	Federal	GW	P
PPU FED 2-34D-12-16	34	120S	160E	4300731320	2470	Federal	Federal	GW	P
PPU FED 2-7D-13-17 DEEP	6	130S	170E	4300731326	14692	Federal	Federal	GW	P
PPU FED 2-35D-12-16	35	120S	160E	4300731345	2470	Federal	Federal	GW	P
PPU FED 7-35D-12-16	35	120S	160E	4300731346	2470	Federal	Federal	GW	P
PPU FED 4-35D-12-16	35	120S	160E	4300731347	2470	Federal	Federal	GW	P
PPU FED 7-36D-12-16	36	120S	160E	4300731348	2470	Federal	Federal	GW	P
PPU FED 11-36D-12-16	36	120S	160E	4300731349	2470	Federal	Federal	GW	P
PPU FED 15-25D-12-16	36	120S	160E	4300731351	2470	Federal	Federal	GW	P
PPU FED 13-25D-12-16	36	120S	160E	4300731352	2470	Federal	Federal	GW	P
PPU FED 4-36D-12-16	36	120S	160E	4300731353	2470	Federal	Federal	GW	P
PPU FED 1-35D-12-16	35	120S	160E	4300731365	2470	Federal	Federal	GW	P
PPU FED 13-26D-12-16	26	120S	160E	4300731403	2470	Federal	Federal	GW	P
PPU FED 15-26D-12-16	26	120S	160E	4300731404	2470	Federal	Federal	GW	P
PPU FED 3-35D-12-16	26	120S	160E	4300731405	2470	Federal	Federal	GW	P

Bill Barrett Corporation (N2165) to EnerVest Operating, LLC (N4040)

Effective 1/1/2014

Peter Point Unit

Well Name	Sec	TWN	RNG	API Number	Entity	Mineral Lease	Surface Lease	Well Type	Well Status
PPU FED 10-26D-12-16	26	120S	160E	4300731406	2470	Federal	Federal	GW	P
PPU FED 11-26D-12-16	26	120S	160E	4300731407	2470	Federal	Federal	GW	P
PPU FED 12-26D-12-16	26	120S	160E	4300731408	2470	Federal	Federal	GW	P
PPU FED 11-27D-12-16	27	120S	160E	4300731409	2470	Federal	Federal	GW	P
PPU FED 15-27D-12-16	27	120S	160E	4300731410	2470	Federal	Federal	GW	P
PPU FED 9-27D-12-16	27	120S	160E	4300731411	2470	Federal	Federal	GW	P
PPU FED 1-34D-12-16	34	120S	160E	4300731427	2470	Federal	Federal	GW	P
PPU FED 7-34D-12-16	34	120S	160E	4300731428	2470	Federal	Federal	GW	P
PPU FED 5-35D-12-16	34	120S	160E	4300731429	2470	Federal	Federal	GW	P
PPU FED 3-34D-12-16	34	120S	160E	4300731466	2470	Federal	Federal	GW	P
PPU FED 5-34D-12-16	34	120S	160E	4300731467	2470	Federal	Federal	GW	P
PPU FED 4-34D-12-16	34	120S	160E	4300731468	2470	Federal	Federal	GW	P
PPU FED 10-35D-12-16	35	120S	160E	4300731474	2470	Federal	Federal	GW	P
PPU FED 9-35D-12-16	35	120S	160E	4300731476	2470	Federal	Federal	GW	P
PETERS POINT U FED 9-26D-12-16	25	120S	160E	4300750021	2470	Federal	Federal	GW	P
PETERS POINT U FED 11-25D-12-16	25	120S	160E	4300750022	2470	Federal	Federal	GW	P
PETERS POINT U FED 10-31D-12-17	31	120S	170E	4300750023	2470	Federal	Federal	GW	P
PETERS POINT U FED 11-31D-12-17	31	120S	170E	4300750024	2470	Federal	Federal	GW	P
PETERS POINT U FED 13A-31D-12-17	31	120S	170E	4300750025	2470	Federal	Federal	GW	P
PETERS POINT U FED 13-31D-12-17	31	120S	170E	4300750026	2470	Federal	Federal	GW	P
PETERS POINT U FED 14-31D-12-17	31	120S	170E	4300750027	2470	Federal	Federal	GW	P
PETERS POINT U FED 14A-31D-12-17	31	120S	170E	4300750028	2470	Federal	Federal	GW	P
PETERS POINT U FED 12-25D-12-16	25	120S	160E	4300750029	2470	Federal	Federal	GW	P
PETERS POINT U FED 12-6D-13-17	31	120S	170E	4300750033	2470	Federal	Federal	GW	P
PETERS POINT U FED 10-25D-12-16	25	120S	160E	4300750035	2470	Federal	Federal	GW	P
PETERS POINT U FED 13-36D-12-16	36	120S	160E	4300750037	2470	Federal	Federal	GW	P
PETERS POINT U FED 15-36D-12-16	36	120S	160E	4300750038	2470	Federal	Federal	GW	P
PETERS POINT U FED 11-1D-13-16	36	120S	160E	4300750039	2470	Federal	Federal	GW	P
PETERS POINT U FED 12-1D-13-16	36	120S	160E	4300750040	2470	Federal	Federal	GW	P
PETERS POINT U FED 3A-34D-12-16	27	120S	160E	4300750063	2470	Federal	Federal	GW	P
PETERS POINT U FED 4A-34D-12-16	27	120S	160E	4300750064	2470	Federal	Federal	GW	P
PETERS POINT U FED 12-27D-12-16	27	120S	160E	4300750065	2470	Federal	Federal	GW	P
PETERS POINT U FED 13-27D-12-16	27	120S	160E	4300750066	2470	Federal	Federal	GW	P
PETERS POINT U FED 13A-27D-12-16	27	120S	160E	4300750067	2470	Federal	Federal	GW	P
PETERS POINT U FED 14A-27D-12-16	27	120S	160E	4300750069	2470	Federal	Federal	GW	P
PETERS POINT U FED 5-31D-12-17	36	120S	160E	4300750109	2470	Federal	Federal	GW	P
PETERS POINT U FED 6-31D-12-17	36	120S	160E	4300750116	2470	Federal	Federal	GW	P
PETERS POINT U FED 9X-36D-12-16	36	120S	160E	4300750117	2470	Federal	Federal	GW	P
PETERS POINT U FED 1-36D-12-16	36	120S	160E	4300750118	2470	Federal	Federal	GW	P
PETERS POINT U FED 10-6D-13-17	6	130S	170E	4300750119	2470	Federal	Federal	GW	P
PETERS POINT U FED 15-31D-12-17	6	130S	170E	4300750123	2470	Federal	Federal	GW	P
PETERS POINT UF 12-5D-13-17	6	130S	170E	4300750151	2470	Federal	Federal	GW	P
PETERS POINT UF 13-5D-13-17	6	130S	170E	4300750152	2470	Federal	Federal	GW	P
PETERS POINT UF 13-30D-12-17	30	120S	170E	4300750153	18347	Federal	Federal	GW	P
PETERS POINT UF 14-30D-12-17	30	120S	170E	4300750154	18350	Federal	Federal	GW	P
PETERS POINT UF 12-30D-12-17	30	120S	170E	4300750155	18346	Federal	Federal	GW	P
PETERS POINT UF 11-30D-12-17	30	120S	170E	4300750156	18348	Federal	Federal	GW	P
PETERS POINT UF 3-31D-12-17	30	120S	170E	4300750157	2470	Federal	Federal	GW	P
PETERS POINT UF 2-31D-12-17	30	120S	170E	4300750158	18349	Federal	Federal	GW	P
PETERS POINT UF 16-25D-12-16	30	120S	170E	4300750159	2470	Federal	Federal	GW	P
PETERS POINT UF 9-25D-12-16	30	120S	170E	4300750160	2470	Federal	Federal	GW	P
PETERS POINT UF 7X-36D-12-16	36	120S	160E	4300750231	2470	Federal	Federal	GW	P
PETERS POINT UF 8-36D-12-16	36	120S	160E	4300750232	2470	Federal	Federal	GW	P
PPU FED 14-26D-12-16	26	120S	160E	4300731277	2470	Federal	Federal	GW	S
PPU FED 5-36D-12-16	36	120S	160E	4300731350	2470	Federal	Federal	GW	S

COPY

FORM 9

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.

1. TYPE OF WELL OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER _____		5. LEASE DESIGNATION AND SERIAL NUMBER: (see attached well list)
2. NAME OF OPERATOR: ENERVEST OPERATING, LLC		6. IF INDIAN, ALLOTTEE OR TRIBE NAME: N/A
3. ADDRESS OF OPERATOR: 1001 FANNIN, ST. STE 800 CITY HOUSTON STATE TX ZIP 77002		7. UNIT or CA AGREEMENT NAME:
PHONE NUMBER: (713) 659-3500		8. WELL NAME and NUMBER: (see attached well list)
4. LOCATION OF WELL FOOTAGES AT SURFACE: (see attached well list)		9. API NUMBER:
QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN:		10. FIELD AND POOL, OR WILDCAT:

COUNTY:

STATE:

UTAH

11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION		
<input checked="" type="checkbox"/> NOTICE OF INTENT (Submit in Duplicate) Approximate date work will start: 1/1/2014	<input type="checkbox"/> ACIDIZE	<input type="checkbox"/> DEEPEN	<input type="checkbox"/> REPERFORATE CURRENT FORMATION
	<input type="checkbox"/> ALTER CASING	<input type="checkbox"/> FRACTURE TREAT	<input type="checkbox"/> SIDETRACK TO REPAIR WELL
	<input type="checkbox"/> CASING REPAIR	<input type="checkbox"/> NEW CONSTRUCTION	<input type="checkbox"/> TEMPORARILY ABANDON
	<input type="checkbox"/> CHANGE TO PREVIOUS PLANS	<input checked="" type="checkbox"/> OPERATOR CHANGE	<input type="checkbox"/> TUBING REPAIR
	<input type="checkbox"/> CHANGE TUBING	<input type="checkbox"/> PLUG AND ABANDON	<input type="checkbox"/> VENT OR FLARE
<input type="checkbox"/> SUBSEQUENT REPORT (Submit Original Form Only) Date of work completion:	<input type="checkbox"/> CHANGE WELL NAME	<input type="checkbox"/> PLUG BACK	<input type="checkbox"/> WATER DISPOSAL
	<input type="checkbox"/> CHANGE WELL STATUS	<input type="checkbox"/> PRODUCTION (START/RESUME)	<input type="checkbox"/> WATER SHUT-OFF
	<input type="checkbox"/> COMMINGLE PRODUCING FORMATIONS	<input type="checkbox"/> RECLAMATION OF WELL SITE	<input type="checkbox"/> OTHER: _____
	<input type="checkbox"/> CONVERT WELL TYPE	<input type="checkbox"/> RECOMPLETE - DIFFERENT FORMATION	

12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.

ENERVEST OPERATING, LLC IS SUBMITTING THIS SUNDRY AS NOTIFICATION THAT THE WELLS LISTED ON THE ATTACHED LIST HAVE BEEN SOLD TO ENERVEST OPERATING, LLC BY BILL BARRETT CORPORATION EFFECTIVE 1/1/2014. PLEASE REFER ALL FUTURE CORRESPONDENCE TO THE ADDRESS BELOW.

EnerVest Operating, L.L.C.

1001 Fannin, Suite 800

Houston, Texas 77002

713-659-3500

(BLM BOND # RLB 7886, STATE/FEE BOND # B008321)

BILL BARRETT CORPORATION

Duane Zavadih NAME (PLEASE PRINT)

Ron Young SIGNATURE

Senior Vice President -

EH&S, Government and Regulatory Affairs

N21165

ENERVEST OPERATING, LLC

Ronnie L Young NAME (PLEASE PRINT)

Ronnie L Young SIGNATURE

DIRECTOR - REGULATORY

N4040

NAME (PLEASE PRINT) RONNIE YOUNG

SIGNATURE

Ronnie L Young

TITLE DIRECTOR - REGULATORY

DATE 12/10/2013

(This space for State use only)

APPROVED

JAN 28 2014 4:00 PM

DIV. OF OIL, GAS & MINING

Rachael Medina

(See Instructions on Reverse Side)

RECEIVED

JAN 07 2014

DIV. OF OIL, GAS & MINING

UDOGM CHANGE OF OPERATOR WELL LIST

Well Name	Sec	TWN	RNG	API Number	Entity	Lease	Well Type	Well Status	Unit
JACK CANYON UNIT 8-32	32	120S	160E	4300730460	15167	State	WI	A	
JACK CYN U ST 14-32	32	120S	160E	4300730913	15166	State	WD	A	
PRICKLY PEAR U FED 12-24	24	120S	140E	4300730953	14467	Federal	WD	A	
PPU FED 11-23D-12-15	23	120S	150E	4300731440		Federal	GW	APD	PRICKLY PEAR
PPU FED 4-26D-12-15	23	120S	150E	4300731441		Federal	GW	APD	PRICKLY PEAR
PPU FED 14-23D-12-15	23	120S	150E	4300731442		Federal	GW	APD	PRICKLY PEAR
PPU FED 12-23D-12-15	23	120S	150E	4300731443		Federal	GW	APD	PRICKLY PEAR
PPU FED 11-34D-12-16	34	120S	160E	4300731465		Federal	GW	APD	PETERS POINT
PPU FED 10-34D-12-16	34	120S	160E	4300731469		Federal	GW	APD	PETERS POINT
HORSE BENCH FED 4-27D-12-16	27	120S	160E	4300750092		Federal	GW	APD	
HORSE BENCH FED 5-27D-12-16	27	120S	160E	4300750093		Federal	GW	APD	
PRICKLY PEAR U FED 12-7D-12-15	07	120S	150E	4300750094		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR U FED 11-7D-12-15	07	120S	150E	4300750095		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR U FED 13-7D-12-15	07	120S	150E	4300750096		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR U FED 14-7D-12-15	07	120S	150E	4300750097		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 11-8D-12-15	08	120S	150E	4300750124		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 12-8D-12-15	08	120S	150E	4300750125		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 13-8D-12-15	08	120S	150E	4300750126		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 14-8D-12-15	08	120S	150E	4300750127		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 9-21D-12-15	21	120S	150E	4300750128		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 9A-21D-12-15	21	120S	150E	4300750129		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 10-21D-12-15	21	120S	150E	4300750130		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 10A-21D-12-15	21	120S	150E	4300750131		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 15A-21D-12-15	21	120S	150E	4300750132		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 15X-21D-12-15	21	120S	150E	4300750133		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 16-21D-12-15	21	120S	150E	4300750134		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 16A-21D-12-15	21	120S	150E	4300750135		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 13A-22D-12-15	21	120S	150E	4300750148		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 1A-27D-12-15	22	120S	150E	4300750161		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 2A-27D-12-15	22	120S	150E	4300750162		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 3A-27D-12-15	22	120S	150E	4300750163		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 9A-22D-12-15	22	120S	150E	4300750164		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 10A-22D-12-15	22	120S	150E	4300750165		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 11A-22D-12-15	22	120S	150E	4300750166		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 12A-22D-12-15	22	120S	150E	4300750167		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 14A-22D-12-15	22	120S	150E	4300750168		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 15A-22D-12-15	22	120S	150E	4300750169		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 16A-22D-12-15	22	120S	150E	4300750170		Federal	GW	APD	PRICKLY PEAR
PETERS POINT UF 15X-36D-12-16	36	120S	160E	4300750178		Federal	GW	APD	PETERS POINT
PRICKLY PEAR UF 15A-15D-12-15	15	120S	150E	4300750180		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 11B-15D-12-15	15	120S	150E	4300750181		Federal	GW	APD	PRICKLY PEAR
PETERS POINT UF 10-1D-13-16	36	120S	160E	4300750182		Federal	GW	APD	PETERS POINT
PETERS POINT UF 9-1D-13-16	36	120S	160E	4300750183		Federal	GW	APD	PETERS POINT
PRICKLY PEAR UF 16A-15D-12-15	15	120S	150E	4300750184		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 3A-18D-12-15	07	120S	150E	4300750185		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 4A-18D-12-15	07	120S	150E	4300750186		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 11A-7D-12-15	07	120S	150E	4300750187		Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 2-18D-12-15	07	120S	150E	4300750188		Federal	GW	APD	PRICKLY PEAR

UDOGM CHANGE OF OPERATOR WELL LIST

PRICKLY PEAR UF 12A-7D-12-15	07	120S	150E	4300750189	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 13A-7D-12-15	07	120S	150E	4300750190	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 14A-7D-12-15	07	120S	150E	4300750191	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR FEDERAL 1-12D-12-14	12	120S	140E	4300750205	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 2-12D-12-14	12	120S	140E	4300750206	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 7-12D-12-14	12	120S	140E	4300750207	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 7A-12D-12-14	12	120S	140E	4300750208	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 8-12D-12-14	12	120S	140E	4300750209	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 4-7D-12-15	12	120S	140E	4300750210	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 5-7D-12-15	12	120S	140E	4300750211	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 8A-12D-12-14	12	120S	140E	4300750212	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 5A-7D-12-15	12	120S	140E	4300750213	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 7-14D-12-15	14	120S	150E	4300750214	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 7A-14D-12-15	14	120S	150E	4300750215	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 9-14D-12-15	14	120S	150E	4300750217	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 9A-14D-12-15	14	120S	150E	4300750218	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 10-14D-12-15	14	120S	150E	4300750219	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 10A-14D-12-15	14	120S	150E	4300750220	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 15A-14D-12-15	14	120S	150E	4300750222	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 16-14D-12-15	14	120S	150E	4300750223	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 16A-14D-12-15	14	120S	150E	4300750224	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 1A-18D-12-15	07	120S	150E	4300750225	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 2A-18D-12-15	07	120S	150E	4300750226	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 9A-7D-12-15	07	120S	150E	4300750227	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 10A-7D-12-15	07	120S	150E	4300750228	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 15A-7D-12-15	07	120S	150E	4300750229	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 16A-7D-12-15	07	120S	150E	4300750230	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 9A-12D-12-14	12	120S	140E	4300750233	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 10A-12D-12-14	12	120S	140E	4300750234	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 15A-12D-12-14	12	120S	140E	4300750235	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 12A-8D-12-15	08	120S	150E	4300750236	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 16A-12D-12-14	12	120S	140E	4300750237	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 11A-8D-12-15	08	120S	150E	4300750238	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 13A-8D-12-15	08	120S	150E	4300750239	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 14A-8D-12-15	08	120S	150E	4300750240	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 5A-8D-12-15	08	120S	150E	4300750260	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 6A-8D-12-15	08	120S	150E	4300750261	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 4-8D-12-15	08	120S	150E	4300750262	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 3-8D-12-15	08	120S	150E	4300750263	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 2-8D-12-15	08	120S	150E	4300750264	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 7A-8D-12-15	08	120S	150E	4300750265	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 7-8D-12-15	08	120S	150E	4300750266	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 5-8D-12-15	08	120S	150E	4300750267	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 6-8D-12-15	08	120S	150E	4300750268	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 10A-8D-12-15	08	120S	150E	4300750269	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 9A-8D-12-15	08	120S	150E	4300750270	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 8-8D-12-15	08	120S	150E	4300750271	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 1-8D-12-15	08	120S	150E	4300750272	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 8A-8D-12-15	08	120S	150E	4300750273	Federal	GW	APD	PRICKLY PEAR

UDOGM CHANGE OF OPERATOR WELL LIST

PRICKLY PEAR UF 5-9D-12-15	09	120S	150E	4300750274	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 5A-9D-12-15	09	120S	150E	4300750275	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 4-9D-12-15	09	120S	150E	4300750276	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 3-9D-12-15	09	120S	150E	4300750277	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 6A-9D-12-15	09	120S	150E	4300750278	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 11-9D-12-15	09	120S	150E	4300750279	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 12A-9D-12-15	09	120S	150E	4300750280	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 6-9D-12-15	09	120S	150E	4300750281	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 11A-9D-12-15	09	120S	150E	4300750282	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR US 1X-16D-12-15	10	120S	150E	4300750283	State	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 5A-15D-12-15	10	120S	150E	4300750284	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 6A-15D-12-15	10	120S	150E	4300750285	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 3-15D-13-15	10	120S	150E	4300750286	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 15A-10D-12-15	15	120S	150E	4300750287	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 13-10D-12-15	10	120S	150E	4300750288	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 15-10D-12-15	15	120S	150E	4300750289	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 16A-10D-12-15	15	120S	150E	4300750290	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 9-10D-12-15	15	120S	150E	4300750291	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 14A-10D-12-15	10	120S	150E	4300750292	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 10-10D-12-15	15	120S	150E	4300750293	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 16-10D-12-15	15	120S	150E	4300750294	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 13-11D-12-15	15	120S	150E	4300750295	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 13A-11D-12-15	15	120S	150E	4300750296	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 12-11D-12-15	15	120S	150E	4300750297	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 13A-10D-12-15	10	120S	150E	4300750298	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 12-10D-12-15	10	120S	150E	4300750299	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 11-10D-12-15	10	120S	150E	4300750300	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 3A-15D-12-15	10	120S	150E	4300750301	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 12-14D-12-15	14	120S	150E	4300750302	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 4-15D-12-15	10	120S	150E	4300750303	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 4A-15D-12-15	10	120S	150E	4300750304	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 14-10D-12-15	10	120S	150E	4300750305	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 9A-17D-12-15	17	120S	150E	4300750306	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 8A-17D-12-15	17	120S	150E	4300750307	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 10A-17D-12-15	17	120S	150E	4300750308	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 3-7D-12-15	07	120S	150E	4300750309	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 16A-17D-12-15	17	120S	150E	4300750310	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 6-7D-12-15	07	120S	150E	4300750311	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 15A-17D-12-15	17	120S	150E	4300750312	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 6A-7D-12-15	07	120S	150E	4300750313	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 7A-7D-12-15	07	120S	150E	4300750314	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 8A-7D-12-15	07	120S	150E	4300750315	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 6X-17D-12-15	17	120S	150E	4300750316	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 11A-17D-12-15	17	120S	150E	4300750317	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 15B-17D-12-15	17	120S	150E	4300750318	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 8A-20D-12-15	20	120S	150E	4300750319	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 1-7D-12-15	07	120S	150E	4300750320	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 7A-20D-12-15	20	120S	150E	4300750321	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 9A-20D-12-15	20	120S	150E	4300750322	Federal	GW	APD	PRICKLY PEAR

UDOGM CHANGE OF OPERATOR WELL LIST

PRICKLY PEAR UF 10A-20D-12-15	20	120S	150E	4300750323	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 10-20D-12-15	20	120S	150E	4300750324	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 2-7D-12-15	07	120S	150E	4300750325	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 14A-20D-12-15	20	120S	150E	4300750326	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 16A-20D-12-15	20	120S	150E	4300750327	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 15A-20D-12-15	20	120S	150E	4300750328	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 8-7D-12-15	07	120S	150E	4300750329	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 15-20D-12-15	20	120S	150E	4300750330	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 7-7D-12-15	07	120S	150E	4300750331	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 6-10D-12-15	09	120S	150E	4300750332	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 5A-10D-12-15	09	120S	150E	4300750333	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 11A-10D-12-15	09	120S	150E	4300750334	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 6A-10D-12-15	09	120S	150E	4300750335	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 5-10D-12-15	09	120S	150E	4300750336	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 12A-10D-12-15	09	120S	150E	4300750338	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 3-10D-12-15	09	120S	150E	4300750339	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 4-10D-12-15	09	120S	150E	4300750340	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 8-9D-12-15	09	120S	150E	4300750341	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 8A-9D-12-15	09	120S	150E	4300750342	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 7A-9D-12-15	09	120S	150E	4300750343	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 7-9D-12-15	09	120S	150E	4300750344	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 1-9D-12-15	09	120S	150E	4300750345	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 2-9D-12-15	09	120S	150E	4300750346	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 1-24D-12-1	24	120S	150E	4300750348	Federal	GW	APD	PRICKLY PEAR
PRICKLY PEAR UF 9-13D-12-15	13	120S	150E	4300750349	Federal	GW	APD	PRICKLY PEAR
HORSE BENCH FED 4-20D-12-17	19	120S	170E	4300750350	Federal	GW	APD	
Horse Bench Federal 16-18D-12-17	19	120S	170E	4300750351	Federal	GW	APD	
PPU FED 9-34D-12-16	34	120S	160E	4300731430	17225 Federal	GW	OPS	PETERS POINT
PPU FED 15-35D-12-16	35	120S	160E	4300731475	2470 Federal	GW	OPS	PETERS POINT
PETERS POINT U FED 12A-6D-13-17	31	120S	170E	4300750034	2470 Federal	GW	OPS	PETERS POINT
PETERS POINT U FED 11A-31D-12-17	31	120S	170E	4300750036	2470 Federal	GW	OPS	PETERS POINT
PRICKLY PEAR U FED 7-21D-12-15	21	120S	150E	4300750055	14794 Federal	GW	OPS	PRICKLY PEAR
PETERS POINT U FED 9-6D-13-17	06	130S	170E	4300750120	2470 Federal	GW	OPS	PETERS POINT
PETERS POINT U FED 14-6D-13-17	06	130S	170E	4300750121	2470 Federal	GW	OPS	PETERS POINT
PETERS POINT U FED 15-6D-13-17	06	130S	170E	4300750122	2470 Federal	GW	OPS	PETERS POINT
PETERS POINT UF 2-7D-13-17	06	130S	170E	4300750149	2470 Federal	GW	OPS	PETERS POINT
PETERS POINT UF 1-7D-13-17	06	130S	170E	4300750150	2470 Federal	GW	OPS	PETERS POINT
PRICKLY PEAR US 1A-16D-12-15	09	120S	150E	4300750192	14794 State	GW	OPS	PRICKLY PEAR
PRICKLY PEAR US 2A-16D-12-15	09	120S	150E	4300750193	14794 State	GW	OPS	PRICKLY PEAR
PRICKLY PEAR US 2-16D-12-15	09	120S	150E	4300750194	14794 State	GW	OPS	PRICKLY PEAR
PRICKLY PEAR UF 9A-9D-12-15	09	120S	150E	4300750196	14794 Federal	GW	OPS	PRICKLY PEAR
PRICKLY PEAR UF 10-9D-12-15	09	120S	150E	4300750197	14794 Federal	GW	OPS	PRICKLY PEAR
PRICKLY PEAR UF 10A-9D-12-15	09	120S	150E	4300750198	14794 Federal	GW	OPS	PRICKLY PEAR
PRICKLY PEAR UF 14-9D-12-15	09	120S	150E	4300750199	14794 Federal	GW	OPS	PRICKLY PEAR
PRICKLY PEAR UF 14A-9D-12-15	09	120S	150E	4300750200	14794 Federal	GW	OPS	PRICKLY PEAR
PRICKLY PEAR UF 15-9D-12-15	09	120S	150E	4300750201	14794 Federal	GW	OPS	PRICKLY PEAR
PRICKLY PEAR UF 15A-9D-12-15	09	120S	150E	4300750203	14794 Federal	GW	OPS	PRICKLY PEAR
PRICKLY PEAR UF 16A-9D-12-15	09	120S	150E	4300750204	14794 Federal	GW	OPS	PRICKLY PEAR
SHARPLES 1 GOVT PICKRELL	11	120S	150E	4300716045	7030 Federal	GW	P	

UDOGM CHANGE OF OPERATOR WELL LIST

STONE CABIN UNIT 1	13	120S	140E	4300716542	12052 Federal	GW	P	
STONE CABIN FED 1-11	11	120S	140E	4300730014	6046 Federal	GW	P	
STONE CABIN FED 2-B-27	27	120S	150E	4300730018	14794 Federal	GW	P	PRICKLY PEAR
JACK CANYON 101-A	33	120S	160E	4300730049	2455 Federal	GW	P	
PETERS POINT ST 2-2-13-16	02	130S	160E	4300730521	14387 State	GW	P	
PRICKLY PEAR ST 16-15	16	120S	150E	4300730522	14794 State	GW	P	PRICKLY PEAR
PETERS POINT U FED 36-2	36	120S	160E	4300730761	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 36-3	36	120S	160E	4300730762	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 36-4	36	120S	160E	4300730763	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 14-25D-12-16	36	120S	160E	4300730764	2470 Federal	GW	P	PETERS POINT
HUNT RANCH 3-4	03	120S	150E	4300730775	13158 State	GW	P	
PETERS POINT U FED 4-31D-12-17	36	120S	160E	4300730810	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 16-26D-12-16	36	120S	160E	4300730812	2470 Federal	GW	P	PETERS POINT
PRICKLY PEAR UNIT 13-4	13	120S	140E	4300730825	14353 Federal	GW	P	
PRICKLY PEAR UNIT 21-2	21	120S	150E	4300730828	14794 Federal	GW	P	PRICKLY PEAR
PETERS POINT U FED 6-7D-13-17	06	130S	170E	4300730859	14692 Federal	GW	P	PETERS POINT
PETERS POINT ST 4-2-13-16	02	130S	160E	4300730866	14386 State	GW	P	
PRICKLY PEAR U ST 13-16	16	120S	150E	4300730933	14794 State	GW	P	PRICKLY PEAR
PRICKLY PEAR U ST 11-16	16	120S	150E	4300730944	14794 State	GW	P	PRICKLY PEAR
PRICKLY PEAR U ST 7-16	16	120S	150E	4300730945	14794 State	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 7-25	25	120S	150E	4300730954	14794 Federal	GW	P	PRICKLY PEAR
PETERS POINT U FED 16-35	35	120S	160E	4300730965	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 11-6-13-17	06	130S	170E	4300730982	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 16-6D-13-17	06	130S	170E	4300731004	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 16-31D-12-17	06	130S	170E	4300731005	2470 Federal	GW	P	PETERS POINT
PRICKLY PEAR U FED 5-13-12-14	13	120S	140E	4300731008	14897 Federal	GW	P	
PETERS POINT U FED 12-31D-12-17	36	120S	160E	4300731009	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 2-36D-12-16	36	120S	160E	4300731010	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 9-36-12-16	36	120S	160E	4300731011	2470 Federal	GW	P	PETERS POINT
PRICKLY PEAR U ST 36-06	36	120S	150E	4300731018	14794 State	GW	P	PRICKLY PEAR
PETERS POINT U FED 8-35D-12-16	36	120S	160E	4300731024	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 4-12D-13-16	02	130S	160E	4300731049	14692 Federal	GW	P	PETERS POINT
PETERS POINT ST 5-2D-13-16 DEEP	02	130S	160E	4300731056	15909 State	GW	P	
PRICKLY PEAR U FED 13-23-12-15	23	120S	150E	4300731073	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 1-27D-12-15	23	120S	150E	4300731074	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 3-26D-12-15	23	120S	150E	4300731075	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 15-22D-12-15	23	120S	150E	4300731076	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 3-28D-12-15	21	120S	150E	4300731121	14794 Federal	GW	P	PRICKLY PEAR
PETERS POINT U FED 2-12D-13-16	06	130S	170E	4300731158	14692 Federal	GW	P	PETERS POINT
PRICKLY PEAR U FED 15-21-12-15	21	120S	150E	4300731164	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 7-28D-12-15	21	120S	150E	4300731165	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 13-21D-12-15	21	120S	150E	4300731166	14794 Federal	GW	P	PRICKLY PEAR
PETERS POINT U FED 10-36D-12-16	36	120S	160E	4300731174	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 12-36D-12-16	36	120S	160E	4300731175	2470 Federal	GW	P	PETERS POINT
PRICKLY PEAR U FED 15-17-12-15	17	120S	150E	4300731183	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 11-17D-12-15	17	120S	150E	4300731184	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 7-22D-12-15	22	120S	150E	4300731186	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 3-22-12-15	22	120S	150E	4300731187	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 5-22D-12-15	22	120S	150E	4300731188	14794 Federal	GW	P	PRICKLY PEAR

UDOGM CHANGE OF OPERATOR WELL LIST

PRICKLY PEAR 11-15D-12-15	22	120S	150E	4300731189	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 9-18D-12-15	18	120S	150E	4300731192	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 15-18-12-15	18	120S	150E	4300731193	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 16-27D-12-15	27	120S	150E	4300731194	15569 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 12-27D-12-15	27	120S	150E	4300731195	15568 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 10-27-12-15	27	120S	150E	4300731196	15570 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 9-20D-12-15	20	120S	150E	4300731197	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 7-20-12-15	20	120S	150E	4300731198	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 1-20-12-15	20	120S	150E	4300731206	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U ST 2-36-12-15	36	120S	150E	4300731226	15719 State	GW	P	
PRICKLY PEAR U ST 4-36-12-15	36	120S	150E	4300731227	14794 State	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 4-27D-12-15	22	120S	150E	4300731237	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 13-22-12-15	22	120S	150E	4300731238	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 3-27D-12-15	22	120S	150E	4300731239	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U ST 9-16-12-15	16	120S	150E	4300731240	14794 State	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 9-28D-12-15	28	120S	150E	4300731241	16028 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 5-27D-12-15	28	120S	150E	4300731242	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 1-28-12-15	28	120S	150E	4300731243	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 8-28D-12-15	28	120S	150E	4300731244	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U ST 1-16-12-15	16	120S	150E	4300731245	14794 State	GW	P	PRICKLY PEAR
PPU FED 11-18D-12-15	18	120S	150E	4300731257	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 11-20D-12-15	20	120S	150E	4300731258	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 4-25D-12-15	25	120S	150E	4300731259	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 12-25D-12-15	25	120S	150E	4300731260	16068 Federal	GW	P	PRICKLY PEAR
PPU FED 15-6D-13-17	06	130S	170E	4300731261	16103 Federal	GW	P	PETERS POINT
PP UF 3-36-12-16	36	120S	160E	4300731271	2470 Federal	GW	P	PETERS POINT
PP UF 6-36-12-16	36	120S	160E	4300731272	2470 Federal	GW	P	PETERS POINT
PPU FED 6-35D-12-16	35	120S	160E	4300731275	2470 Federal	GW	P	PETERS POINT
PPU FED 14-26D-12-16	26	120S	160E	4300731277	2470 Federal	GW	P	PETERS POINT
PPU FED 8-34-12-16	34	120S	160E	4300731279	2470 Federal	GW	P	PETERS POINT
PP ST 8-2D-13-16 (DEEP)	02	130S	160E	4300731280	16069 State	GW	P	
PPU FED 6-34D-12-16	34	120S	160E	4300731281	2470 Federal	GW	P	PETERS POINT
PPU FED 14-26D-12-15	35	120S	150E	4300731282	16224 Federal	GW	P	PRICKLY PEAR
PPU FED 2-35-12-15	35	120S	150E	4300731283	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 10-26D-12-15	35	120S	150E	4300731284	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 9-17-12-15	17	120S	150E	4300731287	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 1-17D-12-15	17	120S	150E	4300731288	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 7-17D-12-15	17	120S	150E	4300731289	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 7-1D-13-16 ULTRA DEEP	06	130S	170E	4300731293	14692 Federal	GW	P	PETERS POINT
PPU FED 1-18D-12-15	18	120S	150E	4300731294	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 7-18D-12-15	18	120S	150E	4300731295	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 5-17D-12-15	18	120S	150E	4300731296	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 10-17D-12-15	17	120S	150E	4300731307	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 8-17D-12-15	17	120S	150E	4300731308	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 12-17D-12-15	17	120S	150E	4300731309	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 13-17D-12-15	17	120S	150E	4300731310	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 14-17D-12-15	17	120S	150E	4300731311	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 16-18D-12-15	17	120S	150E	4300731312	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 8-18D-12-15	18	120S	150E	4300731313	14794 Federal	GW	P	PRICKLY PEAR

UDOGM CHANGE OF OPERATOR WELL LIST

PPU FED 3-18D-12-15	18	120S	150E	4300731314	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 4-18-12-15	18	120S	150E	4300731315	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 5-18D-12-15	18	120S	150E	4300731316	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 6-18D-12-15	18	120S	150E	4300731317	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 16-27-12-16	27	120S	160E	4300731318	2470 Federal	GW	P	PETERS POINT
PPU FED 10-27D-12-16	27	120S	160E	4300731319	2470 Federal	GW	P	PETERS POINT
PPU FED 2-34D-12-16	34	120S	160E	4300731320	2470 Federal	GW	P	PETERS POINT
PPU FED 16-17D-12-15	17	120S	150E	4300731321	14794 Federal	GW	P	PRICKLY PEAR
PPU ST 15-16D-12-15	16	120S	150E	4300731322	14794 State	GW	P	PRICKLY PEAR
PPU ST 16-16D-12-15	16	120S	150E	4300731323	14794 State	GW	P	PRICKLY PEAR
PPU ST 14-16D-12-15	16	120S	150E	4300731324	14794 State	GW	P	PRICKLY PEAR
PPU FED 2-7D-13-17 DEEP	06	130S	170E	4300731326	14692 Federal	GW	P	PETERS POINT
PPU FED 3-21D-12-15	21	120S	150E	4300731328	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 4-21D-12-15	21	120S	150E	4300731329	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 2-35D-12-16	35	120S	160E	4300731345	2470 Federal	GW	P	PETERS POINT
PPU FED 7-35D-12-16	35	120S	160E	4300731346	2470 Federal	GW	P	PETERS POINT
PPU FED 4-35D-12-16	35	120S	160E	4300731347	2470 Federal	GW	P	PETERS POINT
PPU FED 7-36D-12-16	36	120S	160E	4300731348	2470 Federal	GW	P	PETERS POINT
PPU FED 11-36D-12-16	36	120S	160E	4300731349	2470 Federal	GW	P	PETERS POINT
PPU FED 15-25D-12-16	36	120S	160E	4300731351	2470 Federal	GW	P	PETERS POINT
PPU FED 13-25D-12-16	36	120S	160E	4300731352	2470 Federal	GW	P	PETERS POINT
PPU FED 4-36D-12-16	36	120S	160E	4300731353	2470 Federal	GW	P	PETERS POINT
PPU FED 13-15D-12-15	22	120S	150E	4300731358	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 14-15D-12-15	22	120S	150E	4300731359	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 4-22D-12-15	22	120S	150E	4300731360	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 6-22D-12-15	22	120S	150E	4300731361	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 2-28D-12-15	28	120S	150E	4300731362	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 16X-21D-12-15	28	120S	150E	4300731363	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 5A-27D-12-15	28	120S	150E	4300731364	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 1-35D-12-16	35	120S	160E	4300731365	2470 Federal	GW	P	PETERS POINT
PPU FED 1A-28D-12-15	28	120S	150E	4300731368	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 14A-18D-12-15	18	120S	150E	4300731393	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 10-18D-12-15	18	120S	150E	4300731394	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 15A-18D-12-15	18	120S	150E	4300731395	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 16A-18D-12-15	18	120S	150E	4300731396	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 12-22D-12-15	22	120S	150E	4300731398	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 11-22D-12-15	22	120S	150E	4300731399	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 14-22D-12-15	22	120S	150E	4300731400	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 4A-27D-12-15	22	120S	150E	4300731401	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 13-26D-12-16	26	120S	160E	4300731403	2470 Federal	GW	P	PETERS POINT
PPU FED 15-26D-12-16	26	120S	160E	4300731404	2470 Federal	GW	P	PETERS POINT
PPU FED 3-35D-12-16	26	120S	160E	4300731405	2470 Federal	GW	P	PETERS POINT
PPU FED 10-26D-12-16	26	120S	160E	4300731406	2470 Federal	GW	P	PETERS POINT
PPU FED 11-26D-12-16	26	120S	160E	4300731407	2470 Federal	GW	P	PETERS POINT
PPU FED 12-26D-12-16	26	120S	160E	4300731408	2470 Federal	GW	P	PETERS POINT
PPU FED 11-27D-12-16	27	120S	160E	4300731409	2470 Federal	GW	P	PETERS POINT
PPU FED 15-27D-12-16	27	120S	160E	4300731410	2470 Federal	GW	P	PETERS POINT
PPU FED 9-27D-12-16	27	120S	160E	4300731411	2470 Federal	GW	P	PETERS POINT
PPU FED 11-21D-12-15	21	120S	150E	4300731412	14794 Federal	GW	P	PRICKLY PEAR

UDOGM CHANGE OF OPERATOR WELL LIST

PPU FED 6-21D-12-15	21	120S	150E	4300731413	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 12-21D-12-15	21	120S	150E	4300731414	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 8-20D-12-15	20	120S	150E	4300731419	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 1A-20D-12-15	20	120S	150E	4300731420	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 2-20D-12-15	20	120S	150E	4300731421	14794 Federal	GW	P	PRICKLY PEAR
PPU ST 7A-16D-12-15	16	120S	150E	4300731422	14794 State	GW	P	PRICKLY PEAR
PPU ST 6-16D-12-15	16	120S	150E	4300731423	14794 State	GW	P	PRICKLY PEAR
PPU ST 10A-16D-12-15	16	120S	150E	4300731424	14794 State	GW	P	PRICKLY PEAR
PPU ST 3-16D-12-15	16	120S	150E	4300731425	14794 State	GW	P	PRICKLY PEAR
PPU FED 1-34D-12-16	34	120S	160E	4300731427	2470 Federal	GW	P	PETERS POINT
PPU FED 7-34D-12-16	34	120S	160E	4300731428	2470 Federal	GW	P	PETERS POINT
PPU FED 5-35D-12-16	34	120S	160E	4300731429	2470 Federal	GW	P	PETERS POINT
PPU FED 5-21D-12-15	21	120S	150E	4300731451	14794 Federal	GW	P	PRICKLY PEAR
PPU ST 8-16D-12-15	16	120S	150E	4300731455	14794 State	GW	P	PRICKLY PEAR
PPU ST 12-16D-12-15	16	120S	150E	4300731456	14794 State	GW	P	PRICKLY PEAR
PPU ST 12A-16D-12-15	16	120S	150E	4300731457	14794 State	GW	P	PRICKLY PEAR
PPU ST 15A-16D-12-15	16	120S	150E	4300731458	14794 State	GW	P	PRICKLY PEAR
PPU ST 10-16D-12-15	16	120S	150E	4300731459	14794 State	GW	P	PRICKLY PEAR
PPU ST 11A-16D-12-15	16	120S	150E	4300731460	14794 State	GW	P	PRICKLY PEAR
PPU ST 13A-16D-12-15	16	120S	150E	4300731461	14794 State	GW	P	PRICKLY PEAR
PPU FED 3-34D-12-16	34	120S	160E	4300731466	2470 Federal	GW	P	PETERS POINT
PPU FED 5-34D-12-16	34	120S	160E	4300731467	2470 Federal	GW	P	PETERS POINT
PPU FED 4-34D-12-16	34	120S	160E	4300731468	2470 Federal	GW	P	PETERS POINT
PPU FED 10-7D-12-15	07	120S	150E	4300731470	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 15-7D-12-15	07	120S	150E	4300731471	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 9-7D-12-15	07	120S	150E	4300731472	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 16-7D-12-15	07	120S	150E	4300731473	14794 Federal	GW	P	PRICKLY PEAR
PPU FED 10-35D-12-16	35	120S	160E	4300731474	2470 Federal	GW	P	PETERS POINT
PPU FED 9-35D-12-16	35	120S	160E	4300731476	2470 Federal	GW	P	PETERS POINT
PPU ST 6A-16D-12-15	16	120S	150E	4300731477	14794 State	GW	P	PRICKLY PEAR
PPU ST 4-16D-12-15	16	120S	150E	4300731478	14794 State	GW	P	PRICKLY PEAR
PPU ST 4A-16D-12-15	16	120S	150E	4300731479	14794 State	GW	P	PRICKLY PEAR
PPU ST 5A-16D-12-15	16	120S	150E	4300731480	14794 State	GW	P	PRICKLY PEAR
PPU ST 3A-16D-12-15	16	120S	150E	4300731481	14794 State	GW	P	PRICKLY PEAR
PPU ST 16A-16D-12-15	16	120S	150E	4300731484	14794 State	GW	P	PRICKLY PEAR
PPU ST 9A-16D-12-15	16	120S	150E	4300731485	14794 State	GW	P	PRICKLY PEAR
PPU ST 16B-16D-12-15	16	120S	150E	4300731514	14794 State	GW	P	PRICKLY PEAR
PPU ST 14B-16D-12-15	16	120S	150E	4300731515	14794 State	GW	P	PRICKLY PEAR
PPU ST 13B-16D-12-15	16	120S	150E	4300731516	14794 State	GW	P	PRICKLY PEAR
PETERS POINT U FED 9-26D-12-16	25	120S	160E	4300750021	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 11-25D-12-16	25	120S	160E	4300750022	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 10-31D-12-17	31	120S	170E	4300750023	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 11-31D-12-17	31	120S	170E	4300750024	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 13A-31D-12-17	31	120S	170E	4300750025	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 13-31D-12-17	31	120S	170E	4300750026	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 14-31D-12-17	31	120S	170E	4300750027	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 14A-31D-12-17	31	120S	170E	4300750028	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 12-25D-12-16	25	120S	160E	4300750029	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 12-6D-13-17	31	120S	170E	4300750033	2470 Federal	GW	P	PETERS POINT

UDOGM CHANGE OF OPERATOR WELL LIST

PETERS POINT U FED 10-25D-12-16	25	120S	160E	4300750035	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 13-36D-12-16	36	120S	160E	4300750037	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 15-36D-12-16	36	120S	160E	4300750038	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 11-1D-13-16	36	120S	160E	4300750039	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 12-1D-13-16	36	120S	160E	4300750040	2470 Federal	GW	P	PETERS POINT
PRICKLY PEAR U FED 9-22D-12-15	22	120S	150E	4300750041	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 10-22D-12-15	22	120S	150E	4300750042	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 16-22D-12-15	22	120S	150E	4300750043	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 2-27D-12-15	22	120S	150E	4300750044	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 16-15D-12-15	15	120S	150E	4300750045	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 15-15D-12-15	15	120S	150E	4300750046	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 10-15D-12-15	15	120S	150E	4300750047	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 9-15D-12-15	15	120S	150E	4300750048	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 11A-15D-12-15	15	120S	150E	4300750049	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 1-21D-12-15	21	120S	150E	4300750050	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 2-21D-12-15	21	120S	150E	4300750051	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 2A-21D-12-15	21	120S	150E	4300750052	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 4A-22D-12-15	21	120S	150E	4300750053	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 5A-22D-12-15	21	120S	150E	4300750054	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 7A-21D-12-15	21	120S	150E	4300750056	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 8-21D-12-15	21	120S	150E	4300750057	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 8A-21D-12-15	21	120S	150E	4300750058	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 16-8D-12-15	08	120S	150E	4300750059	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 15-8D-12-15	08	120S	150E	4300750060	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 2-17D-12-15	08	120S	150E	4300750061	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 1A-17D-12-15	08	120S	150E	4300750062	14794 Federal	GW	P	PRICKLY PEAR
PETERS POINT U FED 3A-34D-12-16	27	120S	160E	4300750063	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 4A-34D-12-16	27	120S	160E	4300750064	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 12-27D-12-16	27	120S	160E	4300750065	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 13-27D-12-16	27	120S	160E	4300750066	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 13A-27D-12-16	27	120S	160E	4300750067	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 14-27D-12-16	27	120S	160E	4300750068	18204 Federal	GW	P	
PETERS POINT U FED 14A-27D-12-16	27	120S	160E	4300750069	2470 Federal	GW	P	PETERS POINT
PRICKLY PEAR U FED 1-22D-12-15	22	120S	150E	4300750076	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 2-22D-12-15	22	120S	150E	4300750077	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 8-22D-12-15	22	120S	150E	4300750078	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 3-17D-12-15	17	120S	150E	4300750079	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 3A-17D-12-15	17	120S	150E	4300750080	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 4-17D-12-15	17	120S	150E	4300750081	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 4A-17D-12-15	17	120S	150E	4300750082	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 5A-17D-12-15	17	120S	150E	4300750083	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 6-17D-12-15	17	120S	150E	4300750084	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 6A-17D-12-15	17	120S	150E	4300750085	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 7A-17D-12-15	17	120S	150E	4300750086	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 12A-17D-12-15	17	120S	150E	4300750087	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 9-12D-12-14	12	120S	140E	4300750088	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 10-12D-12-14	12	120S	140E	4300750089	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 15-12D-12-14	12	120S	140E	4300750090	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 16-12D-12-14	12	120S	140E	4300750091	14794 Federal	GW	P	PRICKLY PEAR

UDOGM CHANGE OF OPERATOR WELL LIST

PRICKLY PEAR U FED 3-20D-12-15	20	120S	150E	4300750098	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 3A-20D-12-15	20	120S	150E	4300750099	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 4-20D-12-15	20	120S	150E	4300750100	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 4A-20D-12-15	20	120S	150E	4300750101	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 5-20D-12-15	20	120S	150E	4300750102	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 6-20D-12-15	20	120S	150E	4300750104	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 6A-20D-12-15	20	120S	150E	4300750105	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 11A-20D-12-15	20	120S	150E	4300750106	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR U FED 12A-20D-12-15	20	120S	150E	4300750107	14794 Federal	GW	P	PRICKLY PEAR
PETERS POINT U FED 5-31D-12-17	36	120S	160E	4300750109	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 6-31D-12-17	36	120S	160E	4300750116	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 9X-36D-12-16	36	120S	160E	4300750117	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 1-36D-12-16	36	120S	160E	4300750118	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 10-6D-13-17	06	130S	170E	4300750119	2470 Federal	GW	P	PETERS POINT
PETERS POINT U FED 15-31D-12-17	06	130S	170E	4300750123	2470 Federal	GW	P	PETERS POINT
PRICKLY PEAR UF 7A-18D-12-15	17	120S	150E	4300750136	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 8A-18D-12-15	17	120S	150E	4300750137	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 9A-18D-12-15	17	120S	150E	4300750138	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 12-20D-12-15	20	120S	150E	4300750139	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 16A-8D-12-15	08	120S	150E	4300750140	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 15A-8D-12-15	08	120S	150E	4300750141	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 13A-9D-12-15	08	120S	150E	4300750142	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 13-9D-12-15	08	120S	150E	4300750143	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 12-9D-12-15	08	120S	150E	4300750144	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 10-8D-12-15	08	120S	150E	4300750145	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 9-8D-12-15	08	120S	150E	4300750146	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 2A-17D-12-15	08	120S	150E	4300750147	14794 Federal	GW	P	PRICKLY PEAR
PETERS POINT UF 12-5D-13-17	06	130S	170E	4300750151	2470 Federal	GW	P	PETERS POINT
PETERS POINT UF 13-5D-13-17	06	130S	170E	4300750152	2470 Federal	GW	P	PETERS POINT
PETERS POINT UF 13-30D-12-17	30	120S	170E	4300750153	18347 Federal	GW	P	PETERS POINT
PETERS POINT UF 14-30D-12-17	30	120S	170E	4300750154	18350 Federal	GW	P	PETERS POINT
PETERS POINT UF 12-30D-12-17	30	120S	170E	4300750155	18346 Federal	GW	P	PETERS POINT
PETERS POINT UF 11-30D-12-17	30	120S	170E	4300750156	18348 Federal	GW	P	PETERS POINT
PETERS POINT UF 3-31D-12-17	30	120S	170E	4300750157	2470 Federal	GW	P	PETERS POINT
PETERS POINT UF 2-31D-12-17	30	120S	170E	4300750158	18349 Federal	GW	P	PETERS POINT
PETERS POINT UF 16-25D-12-16	30	120S	170E	4300750159	2470 Federal	GW	P	PETERS POINT
PETERS POINT UF 9-25D-12-16	30	120S	170E	4300750160	2470 Federal	GW	P	PETERS POINT
PRICKLY PEAR UF 1A-22D-12-15	22	120S	150E	4300750171	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 6A-22D-12-15	22	120S	150E	4300750173	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 7A-22D-12-15	22	120S	150E	4300750174	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 8A-22D-12-15	22	120S	150E	4300750175	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 14B-15D-12-15	22	120S	150E	4300750176	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 9-9D-12-15	09	120S	150E	4300750195	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 16-9D-12-15	09	120S	150E	4300750202	14794 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 8-14D-12-15	14	120S	150E	4300750216	18289 Federal	GW	P	PRICKLY PEAR
PRICKLY PEAR UF 15-14D-12-15	14	120S	150E	4300750221	18290 Federal	GW	P	PRICKLY PEAR
PETERS POINT UF 7X-36D-12-16	36	120S	160E	4300750231	2470 Federal	GW	P	PETERS POINT
PETERS POINT UF 8-36D-12-16	36	120S	160E	4300750232	2470 Federal	GW	P	PETERS POINT
PETERS POINT ST 6-2D-13-16	02	130S	160E	4300731017	14472 State	D	PA	

UDOGM CHANGE OF OPERATOR WELL LIST

PTS 33-36 STATE	36	110S	140E	4301330486	6190 State	GW	PA	ARGYLE
PRICKLY PEAR U FED 10-4	10	120S	140E	4300730823	14462 Federal	GW	S	
PRICKLY PEAR U FASSELIN 5-19-12-15	19	120S	150E	4300730860	14853 Fee	GW	S	
PRICKLY PEAR U ST 5-16	16	120S	150E	4300730943	14794 State	GW	S	PRICKLY PEAR
PRICKLY PEAR U FED 7-33D-12-15	33	120S	150E	4300730985	14771 Federal	GW	S	
PETERS POINT ST 8-2D-13-16	02	130S	160E	4300731016	14471 State	GW	S	
PPU FED 4-35D-12-15	35	120S	150E	4300731285	16223 Federal	GW	S	PRICKLY PEAR
PPU FED 5-36D-12-16	36	120S	160E	4300731350	2470 Federal	GW	S	PETERS POINT
PRICKLY PEAR U FED 5A-20D-12-15	20	120S	150E	4300750103	14794 Federal	GW	S	PRICKLY PEAR
PRICKLY PEAR U FED 13A-17D-12-15	20	120S	150E	4300750108	14794 Federal	GW	S	PRICKLY PEAR
PRICKLY PEAR UF 2A-22D-12-15	22	120S	150E	4300750172	14794 Federal	GW	S	PRICKLY PEAR